



AA CALIBRATION PVT.LTD

CALIBRATION CERTIFICATE

540E-01



Certificate No. CC - 2646

Certificate No	AACPL / 00765F	Field	Mech.	Group	Speed	Page No.	1 of 1
SRF No & Date	210118.2	DT -	18 / 01 / 2021	ULR No.	CC2646210000	00765F	
Calibration Method :	Comparison Method						
Company Name	M/s Hira Clinical Lab						
Address	Civil Hospital Hoshiapur - (P.B)						
		Calibration Date	18.01.2021				
		Cal. Due On (As Sugg. By Cust.)	17.01.2022				
		Certificate Issue Dt.	21.01.2021				
		UUC Condition	Good				

Calibration Instrument Detail

SI	Instrument Name	Range	Least Count	Make / SI.No	Party ID / Location
1	Centrifuge M/C	0 - 5000 RPM	10 RPM	Remi / BHLC - 2833	HCL/LAB/CF/01 Laboratory

Standard Equipments Used (Traceable to National Standard)

SI	Instrument Name	Make	Calibrated By	Cal Certificate No	Cal. Valid Upto
1	Tachometer	Line Seiki / 109-0407V	Lawkim Motors Group	C-200215-9-1/A	17/02/2021

Reference Standard	Calibration Purpose	Humidity	Temperature	Calibration Performed At
IS : 12508:2013	RPM Measurement	(50 ± 15)%RH	(25 ± 10) °C	Site

Calibration Procedure : As per Calibration Procedure Manual AACPL / CP / 01B, Section No : CP - 07

Calibration Result

SI	Centrifuge M/c. Knob Set at	Calibration Gauge Value		Deviation (in RPM)	Uncertainty at approx 95% confidence level and coverage factor k = 2 is ± (in %)
		UUC (in RPM)	Master Gauge Value (in RPM)		
1	1	1000	1000.3	-0.3	0.70
2	2	2000	2001.2	-1.2	0.70
3	3	3000	3001.8	-1.8	0.70
4	4	4000	4002.3	-2.3	0.70
5	5	5000	5003.2	-3.2	0.20

Note

- The calibration results reported in this calibration certificate are valid at the time of & under stated condition
- This certificate cannot be reproduced except in full without our prior permission in writing
- This certificate refers only to the particular item(s) submitted for calibration
- UUC - Unit under calibration



Calibrated by

Approved by

Rajesh Prasad
(Tech. Manager)

LAB : Plot No. C18, Sector-13, First Floor, "Vasundhara Haat"
Vasundhara, Ghaziabad - 201012
Mob.: 09672294758, 8249287436
Email: aacplinfo2005@gmail.com, aacplinfo@rediffmail.com



REMI R-8C

00

OPEN

POWER



FOR USE ONLY - DO NOT OPENING
DURING POWER FAILURE.
DO NOT OPENING AT NIGHT
PLEASE FULL IT

CAUTION

Model	Capacity	Max. Temp. (°C)
REMI R-8C BL	8L	121

REMI R-8C BL

Temp. (°C)	Time (min)	Pressure (psi)
121	15	15
121	30	15
121	45	15
121	60	15
121	75	15
121	90	15
121	105	15
121	120	15
121	135	15
121	150	15
121	165	15
121	180	15
121	195	15
121	210	15
121	225	15
121	240	15
121	255	15
121	270	15
121	285	15
121	300	15
121	315	15
121	330	15
121	345	15
121	360	15
121	375	15
121	390	15
121	405	15
121	420	15
121	435	15
121	450	15
121	465	15
121	480	15
121	495	15
121	510	15
121	525	15
121	540	15
121	555	15
121	570	15
121	585	15
121	600	15
121	615	15
121	630	15
121	645	15
121	660	15
121	675	15
121	690	15
121	705	15
121	720	15
121	735	15
121	750	15
121	765	15
121	780	15
121	795	15
121	810	15
121	825	15
121	840	15
121	855	15
121	870	15
121	885	15
121	900	15
121	915	15
121	930	15
121	945	15
121	960	15
121	975	15
121	990	15
121	1005	15
121	1020	15
121	1035	15
121	1050	15
121	1065	15
121	1080	15
121	1095	15
121	1110	15
121	1125	15
121	1140	15
121	1155	15
121	1170	15
121	1185	15
121	1200	15
121	1215	15
121	1230	15
121	1245	15
121	1260	15
121	1275	15
121	1290	15
121	1305	15
121	1320	15
121	1335	15
121	1350	15
121	1365	15
121	1380	15
121	1395	15
121	1410	15
121	1425	15
121	1440	15
121	1455	15
121	1470	15
121	1485	15
121	1500	15
121	1515	15
121	1530	15
121	1545	15
121	1560	15
121	1575	15
121	1590	15
121	1605	15
121	1620	15
121	1635	15
121	1650	15
121	1665	15
121	1680	15
121	1695	15
121	1710	15
121	1725	15
121	1740	15
121	1755	15
121	1770	15
121	1785	15
121	1800	15
121	1815	15
121	1830	15
121	1845	15
121	1860	15
121	1875	15
121	1890	15
121	1905	15
121	1920	15
121	1935	15
121	1950	15
121	1965	15
121	1980	15
121	1995	15
121	2010	15
121	2025	15
121	2040	15
121	2055	15
121	2070	15
121	2085	15
121	2100	15
121	2115	15
121	2130	15
121	2145	15
121	2160	15
121	2175	15
121	2190	15
121	2205	15
121	2220	15
121	2235	15
121	2250	15
121	2265	15
121	2280	15
121	2295	15
121	2310	15
121	2325	15
121	2340	15
121	2355	15
121	2370	15
121	2385	15
121	2400	15
121	2415	15
121	2430	15
121	2445	15
121	2460	15
121	2475	15
121	2490	15
121	2505	15
121	2520	15
121	2535	15
121	2550	15
121	2565	15
121	2580	15
121	2595	15
121	2610	15
121	2625	15
121	2640	15
121	2655	15
121	2670	15
121	2685	15
121	2700	15
121	2715	15
121	2730	15
121	2745	15
121	2760	15
121	2775	15
121	2790	15
121	2805	15
121	2820	15
121	2835	15
121	2850	15
121	2865	15
121	2880	15
121	2895	15
121	2910	15
121	2925	15
121	2940	15
121	2955	15
121	2970	15
121	2985	15
121	3000	15

REMI R-8C BL

oPEn 06

SET SET





AA CALIBRATION PVT.LTD.

CALIBRATION CERTIFICATE

5.10E_01



Certificate No. CC - 2646

Certificate No	AACPL / 00766F	Field	Mech.	Group	Speed	Page No.	1 of 1
SRF No & Date	210118.2	DT -	18 / 01 / 2021	ULR No.	CC2646210000	00766F	
Calibration Method :	Comparison Method						
Company Name Address	M/s Hira Clinical Lab Civil Hospital Hoshiapur - (P.B)						
		Calibration Date	18.01.2021				
		Cal. Due On (As Sugg. By Cust.)	17.01.2022				
		Certificate Issue Dt.	21.01.2021				
		UUC Condition	Good				

Calibration Instrument Detail

SI	Instrument Name	Range	Least Count	Make / SI.No	Party ID / Location
1	Centrifuge M/C	0 - 6000 RPM	10 RPM	Remi / ZBIN - 25712	HCL/LAB/CF/02 Laboratory

Standard Equipments Used (Traceable to National Standard)

SI	Instrument Name	Make	Calibrated By	Cal Certificate No	Cal. Valid Upto
1	Tachometer	Line Seiki / 109-0407V	Lawkim Motors Group	C-200215-9-1/A	17/02/2021

Reference Standard	Calibration Purpose	Humidity	Temperature	Calibration Performed At
IS : 12508:2013	RPM Measurement	(50 ± 15)%RH	(25 ± 10) °C	Site

Calibration Procedure : As per Calibration Procedure Manual AACPL / CP / 01B, Section No : CP - 07

SI	Centrifuge M/c. Knob Set at	Calibration Result			
		Calibration Gauge Value UUC (in RPM)	Master Gauge Value (in RPM)	Deviation (in RPM)	Uncertainty at approx 95% confidence level and coverage factor k = 2 is ± (in %)
1	1	1200	1200.3	-0.3	0.70
2	2	2400	2400.6	-0.6	0.70
3	3	3600	3601.3	-1.3	0.70
4	4	4800	4802.4	-2.4	0.70
5	5	6000	6004.2	-4.2	0.20

Note

- 1 The calibration results reported in this calibration certificate are valid at the time of & under stated condition
- 2 This certificate cannot be reproduced except in full without our prior permission in writing
- 3 This certificate refers only to the particular item(s) submitted for calibration
- 4 UUC - Unit under calibration




Calibrated by
[Signature]

Approved by

[Signature]
Rajesh Prasad
(Tech. Manager)

LAB : Plot No. C18, Sector-13, First Floor, "Vasundhara Haat"
Vasundhara, Ghaziabad - 201012
Mob.: 09672294758, 8249287436
Email: aacplinfo2005@gmail.com, aacplinfo@rediffmail.com


 A & CALIBRATION PVT. LTD.
Ph. No. 9672294758, 7062822526
Certi No. AACPI
I.D./S.N. HCL/LAB/CF/01
Calibration Date 18.01.2024
Due on 17.01.2022 Cal By \downarrow

REMI CENTRIFUGE CE

CAT. NO./DATE : R8C 02/14
SERIAL NO : BHLC-2833
R.P.M : 5250 AMPS. 1.45
SUPPLY : 220 / 230 V, 50Hz, 1 \emptyset AC

REMI ELEKTROTECHNIK LIMITED
(INSTRUMENTS DIVISION)
VASAI - 401 208. (INDIA)



 **AACPI CALIBRATION PVT. LTD.**
Ph. No.: 9672294758, 7062822526
Certi No.: AACPI
I.D./S.N.: HCL/LABI/CF/02
Calibration Date: 18-01-2024
Due on: 17-01-2022 By: ↓

REMI		CENTRIFUGE		CE	
MODEL	R-8CBL	MFG	09-2015		
SER. NO.	ZBIN 25712				
MAX AMP.	1.6	RPM	6000		
SUPPLY	220 V, 50Hz, 1ØAC				
REMI ELEKTROTECHNIK LTD (INSTRUMENTS DIVISION) VASAI - 401208 (INDIA)					



RESET
FUSE 5x20 2A


HAZARDOUS VOLTAGE ENCLOSED

WARNING
Voltage or current hazards sufficient to cause shock.
Disconnect power before servicing.

