An ISO 9001-2015 Certified Company No: 3/751, 1st Cross Street, Surveyor Colony, K.Pudur, Madurai - 625 007.

Phone: 0452 - 2561691 Mobile: +91 94434 74610



GSTIN. 33AAHCA8053H1ZR • DL No. MDU/4205/20B,MDU/3971/21B

CIN: U33110TN2009PTC072140



CALIBRATION CERTIFICATE

Customer	M/S. Gowtham Diagnostic Centre,	Certificate No	: AMS/LAB/2889723
Name &	744-B, Uthukuli Main Road, OPP. GH,	Issuing Date:	14/08/2021
Address:	Kunnathur, Tirupur Dt 638 103.	Page No:	1 of 1

Details of Device under Calibration (DUC):

DUC:	Micro Pipette	Id. No:	GDC/LAB/VMP/001
Make:	Dragon Lab	Department:	Laboratory
Model:	Variable ·	Calibrated On:	13/08/2021
Sl. No:	YE16CAA0129898	Calibration	
Type:	Variable	Due Suggested:	12/08/2022
Range &	.5 to50µl	DUC Condition	
Least Count:		on Receipt:	OK

Traceability Details:

Sl.No.	Test Equipment	Make .	Certificate Number	Valid Up to
1	Electronic Weighing Scale	EWC/SF400C	PC/01/21/ATL/0339-01	22/01/2022
2	Thermo Hygrometer	Beetech/088	PC/01/21/ATL/0194-01	22/01/2022

Room Temperature: 25°C±2

Room Humidity: 30-60%

(At the time of Calibration)

Test Results:

SL.	DUC Reading	Standard Reading (µl)		Correction
No. (μl)	No.	Trial 1	Trial 2	(µl)
1	5	4.5	4.5	-0.5
2	10	11.0	11.0	+1.0
3	20	28.0	28.0	+8.0
4	30 -	35.0	35.0	+5.0
4.	50	45.0	45.0	-5.0

Allowable Tolerance: User Defined

Note:

- 1. Calibration Points were selected as per customer request.
- 2. Each reading were taken by Repeatability Test (i.e.) each reading in a row is a mean of 10 readings.
- 3. Results Reported are valid at the time of and under the stated conditions of measurements

Calibrated By:

(Calibration Engineer)

B. 89.L




Approved by:

(Technical Manager)

An ISO 9001-2015 Certified Company

No: 3/751, 1st Cross Street, Surveyor Colony, K.Pudur, Madurai - 625 007.





GSTIN. 33AAHCA8053H1ZR

DL No. MDU/4205/20B,MDU/3971/21B

CIN: U33110TN2009PTC072140

CALIBRATION CERTIFICATE



	M/S. Gowtham Diagnostic Centre,	Certificate No:	AMS/LAB/2889724
	744-B, Uthukuli Main Road, OPP. GH,	Issuing Date:	14/08/2021
Address:	Kunnathur, Tirupur Dt 638 103.	Page No:	1 of 1 '

Details of Device under Calibration (DUC):

DUC:	Micro Pipette	Id. No:	GDC/LAB/VMP/002
Make:	Bio System	Department:	Laboratory
Model:	Variable	Calibrated On:	13/08/2021
SI. No:		Calibration	1000000
Type:	Variable	Due Suggested:	12/08/2022
Range & .	5 to50μl	DUC Condition	Control of the contro
Least Count:		on Receipt:	OK

Traceability Details:

SI.No.	Test Equipment.	Make	Certificate Number	Valid Up to
11	Electronic Weighing Scale	EWC/SF400C	PC/01/21/ATL/0339-01	22/01/2022
2	Thermo Hygrometer	Beetech/088	PC/01/21/ATL/0194-01	22/01/2022

Room Temperature: 25°C±2

Room Humidity: 30-60%

(At the time of Calibration)

Test Results:

SL. DUC Reading		Standard Reading (µl)		Correction
No. (μl)	Trial 1	Trial 2	· (µl)	
1	5	5.0	5.0	+0.0
2	10	11.0	11.0	+1.0
3	20	22.0	22.0	+2.0
4	30	31.0	31.0	+1.0
4	50	50.0	50.0	+0.0

Allowable Tolerance: User Defined

Note:

- 1. Calibration Points were selected as per customer request.
- 2. Each reading were taken by Repeatability Test (i.e.) each reading in a row is a mean of loreadings.
- 3. Results Reported are valid at the time of and under the stated conditions of measurements.

Calibrated By:

(Calibration Engineer)

b.89:



Approved by:

(Technical Manager)

B.89.

An ISO 9001-2015 Certified Company

No: 3/751, 1st Cross Street, Surveyor Colony, K.Pudur, Madurai - 625 007.

Phone: 0452 - 2561691 Mobile: +91 94434 74610



GSTIN. 33AAHCA8053H1ZR

DL No. MDU/4205/20B,MDU/3971/21B

CIN: U33110TN2009PTC072140

CALIBRATION CERTIFICATE



	M/S. Gowtham Diagnostic Centre,	Certificate No:	AMS/LAB/2889725
	744-B, Uthukuli Main Road, OPP. GH,	Issuing Date:	14/08/2021
Address:	Kunnathur, Tirupur Dt 638 103.	Page No:	1 of 1

Details of Device under Calibration (DUC):

DUC:	Micro Pipette .	Id. No:	GDC/LAB/VMP/003
Make:	Dragon Lab	Department:	Laboratory
Model:	Variable	Calibrated On:	13/08/2021
Sl. No:	YE173AB0043895	Calibration	13/00/2021
Type:	Variable.	Due Suggested:	12/08/2022
Range & Least Count:	100 to1000μl	DUC Condition on Receipt:	

Traceability Details:

Sl.No.	Test Equipment	Make	Certificate Number	Valid Up to
1	Electronic Weighing Scale	EWC/SF400C	PC/01/21/ATL/0339-01	22/01/2022
2	Thermo Hygrometer	Beetech/088	PC/01/21/ATL/0194-01	22/01/2022

Room Temperature: 25°C±2

Room Humidity: 30-60%

(At the time of Calibration)

Test Results:

SL. DUC Reading		Standard	Reading (µl)	Correction
No. (μl)	(1)	. Trial 2	(ul)	
1	100	90.0	90.0	-10.0
2	200	· 180.0	180.0	-20.0
3	500	500.0	500.0	+00.0
4	800	800.0	800.0	+00.0
4	1000 .	1000.0	1000.0	+00.0

Allowable Tolerance: User Defined

Note:

- 1. Calibration Points were selected as per customer request.
- 2. Each reading were taken by Repeatability Test (i.e.) each reading in a row is a mean of 10 readings.
- 3. Results Reported are valid at the time of and under the stated conditions of measurements.

Calibrated By:

(Calibration Engineer)

63.09 =



Approved by:

(Technical Manager)

B.89:

An ISO 9001-2015 Certified Company

No: 3/751, 1st Cross Street, Surveyor Colony, K.Pudur, Madurai - 625 007.



M/S. Gowtham Diagnostic Centre,



GSTIN. 33AAHCA8053H1ZR

DL No. MDU/4205/20B,MDU/3971/21B

CIN: U33110TN2009PTC072140

Certificate No:





AMS/LAB/2889726

X1 0	744 0 714 1 11361 7	certificate No.	AMS/LAB/2889/26
Name &	744-B, Uthukuli Main Road, OPP. GH,	Issuing Date:	14/08/2021
Address:	Kunnathur, Tirupur Dt 638 103.	Page No:	1 of 1
Details of De	vice under Calibration (DUC):		1.0.1
DUC:	Micro Pipette	Id. No:	GDC/LAB/VMP/004
Make:	Lab .	Department:	Laboratory
Model:	Variable	Calibrated On:	13/08/2021
SI. No:		Calibration	13/00/2021
Type:	Variable	Due Suggested:	12/08/2022
Range & Least Count:	100 to1000μl .	DUC Condition on Receipt:	2000
T		on receipt.	OK

Traceability Details:

Customer

Test Equipment	Make ·	Certificate Number	Valid Up to
Electronic Weighing Scale	EWC/SF400C	PC/01/21/ATL/0339-01	22/01/2022
Thermo Hygrometer	Beetech/088		22/01/2022
	Electronic Weighing Scale	Electronic Weighing Scale EWC/SF400C Thermo Hygrometer Beetech/088	Electronic Weighing Scale EWC/SF400C PC/01/21/ATL/0339-01 Thermo Hygrometer Beetech/088 PC/01/21/ATL/0194-01

Room Temperature: 25°C±2

Room Humidity: 30-60%

(At the time of Calibration)

Test Results:

SL. DUC Reading No. (µl)	DUC Reading	Standard Rea	ading (µl)	Correction (µl)
	(µl)	Trial 1	Trial 2	
1	100	100.0	100.0	0.0
2	200	200.0	200.0	0.0
3	500	500.0	500.0	0.0
4	800	800.0	800.0	0.0
4	1000	980.0	980.0	0.0

Allowable Tolerance: User Defined

Note:

- 1. Calibration Points were selected as per customer request.
- 2. Each reading were taken by Repeatability Test (i.e.) each reading in a row is a mean of 10 readings.
- 3. Results Reported are valid at the time of and under the stated conditions of measurements.

Calibrated By:

(Calibration Engineer)




Approved by:

(Technical Manager)

An ISO 9001-2015 Certified Company

No: 3/751, 1st Cross Street, Surveyor Colony, K.Pudur, Madurai - 625 007.





GSTIN. 33AAHCA8053H1ZR

DL No. MDU/4205/20B,MDU/3971/21B

CIN: U33110TN2009PTC072140

CALIBRATION CERTIFICATE



Customer	M/S. Gowtham Diagnostic Centre,	Certificate No:	AMS/LAB/2889727
Name &	744-B, Uthukuli Main Road, OPP. GH,	Issuing Date:	14/08/2021
Address:	Kunnathur, Tirupur Dt 638 103.	Page No:	1 of 1

Details of Device under Calibration (DUC):

DUC:	Micro Pipette	Id. No:	GDC/LAB/VMP/005
Make:	PATHO PETTE	Department:	Laboratory
Model:	Variable	Calibrated On:	13/08/2021
Sl. No:		Calibration	
Type:	Variable ·	Due Suggested:	12/08/2022
Range &	100 to1000μl	DUC Condition	
Least Count:		on Receipt:	OK

Traceability Details:

Sl.No.	Test Equipment	Make ·	Certificate Number	Valid Up to
1	Electronic Weighing Scale	EWC/SF400C	PC/01/21/ATL/0339-01	22/01/2022
2	Thermo Hygrometer	Beetech/088	PC/01/21/ATL/0194-01	22/01/2022

Room Temperature: 25°C±2

Room Humidity: 30-60%

(At the time of Calibration)

Test Results:

SL.	DUC Reading	Standard Reading (µl)		C Reading Standard Reading (µl)	Correction
No.	(µl)	Trial 1	Trial 2	(µl)	
1	100	105.0	105.0	+05.0	
2	200	210.0	210.0	+10.0	
3	. 500	480.0	480.0	-20.0	
4	800	.770.0	770.0	-30.0	
4	1000	960.0	960.0	-40.0	

Allowable Tolerance: User Defined

Note:

- 1. Calibration Points were selected as per customer request.
- 2. Each reading were taken by Repeatability Test (i.e.) each reading in a row is a mean of 40 readings.
- 3. Results Reported are valid at the time of and under the stated conditions of measurements.

Calibrated By:

(Calibration Engineer)

6.8gc



Approved by:

(Technical Manager)

B. 89=