



## CERTIFICATE OF CALIBRATION

	Page. No: 1 of 1
ULR No.	CC272521000012182F
SRF No.	VCI-21-22-L-838
Date of Receipt	23.12.2021
Date of Calibration	23.12.2021
Due Date for Calibration	22.12.2022
Date of Issue	24.12.2021
	SRF No.  Date of Receipt  Date of Calibration  Due Date for Calibration

Digital Thermometer	Make	
-30 to 70°C	Model	
0.1°C	Condition of UUC	Good
	Instrument Location	
DTM-01	Cal. At	Thermal Lab
	-30 to 70°C 0.1°C 	-30 to 70°C Model  0.1°C Condition of UUC  Instrument Location

Environmental Condition		Calibratio	Calibration Method Used		
Temperature (°C)	25±4	National / International Standard	DKD-R-5-1		
Humidity (%RH)	35 - 75	Cal Procedure No	VCI-L03-WI-THER-002		

Standard Used

Sl. No.	Description	ID.No. / SI. No.	Certificate No.	Make/Model	Traceability	Valid till
	RTD Sensor with	VCI-T-RTD-001&			Traceability	vand nn
1 1	•		2020-21/CFC/2515/2	Aparajit Instruments	National	00.00.000
	Indicator	VCI-ET-DT-008		riparajit instruments	Standards	03.03.2022
			<u> </u>		Startantas	

Results of Calibration				
Sl. No.	Standard Reading (°C)	UUC Reading (°C)	Error (°C)	Measurement Uncertainty ± (°C)
01	-20.24	-20.0	0.24	0.27
02	0.31	0.0	-0.31	0.27
03	10.46	10.0	-0.46	0.27
04	20.59	20.0	-0.59	0.27
05	30.62	30.0	-0.62	0.27

## Remarks:

- 1. UUC is Defined as the Unit Under Calibration.
- 2. This Calibration Certificate Results relates only to the above UUC. & This report shall not be reproduced except in full/ part without approval of the Venus Calibration and Instruments.
- 3. The reported results are valid at the time of under stated condition of measurement.
- 4. Calibration of the UUC are traceable to National / International Standards.
- 5. The recalibration interval shall be decided by the user.
- 6. Nabl-133 guidelines are adopted for use of NABL symbol.
- 7. The Measurement uncertainty is expressed at 95.45% confidence level with coverage factor k = 2.
- 8. Temperature Chart: ITS-90

Checked & Issued by:

M. Muss

M.Manju

(Engineer - Calibration)

Authorised by:

C.Dhinakaran

(Technical / Quality Manager)