MK BEST CALIBRATION SERVICES

MK Best Calibrations

FF/7.8/01

NABL ACCREDITED CALIBRATION LABORATORY AS PER ISO/IEC17025: 2017

No. 27, F-2, 1st Floor, 2nd Street, Varalakshmi Nagar, Maduravoyal, (Opp. MGR Engineering College), Chennai - 600 095.

Ph.: 044 - 23780211, Cell : 93802 66480 / 86958 18108 / 90032 77250 E-mail: mkbestcalibration@gmail.com, www.mkbestcalibrationservices.com



CERTIFICATE OF CALIBRATION

CC-3340

1 of 1

Page No

ULR No	CC334022000013010F	Date of Calibratio	n 21.07.202	2 Date of 1	Reciept	21.07.2022	
Certificate No	MKBL/22/07/0871-002	Recom. Due Date	20.07.202	3 Date of 1	Issue	25.07.2022	
CUSTOMER II	NFORMATION		DETAILS OF U	NIT UNDER CAI	IBRATION		
M/S ., SRI SUB	HAM LAB,	Description	Description		MICROPIPETTE - 2		
DEVANATHAS	WAMY NAGAR,	Make / Model	Make / Model Range/Resolution Serial No		 5 to 50 μl VV100		
EAST PONDY I	ROAD,	Range/Resolution					
VILLUPURAM	- 605 103	Serial No					
			Identification No	Identification No Manufacturer Name Calibrated at		SSV/EQP/CB/004	
			Manufacturer Na			ERBA	
			Calibrated at			LAB	
STANDARD IN	ISTRUMENTS DETAILS	(The Standards Use	ed are Traceable to Natio	nal /Internationa	Standards)		
S.No	Description	1	Id.No/Sl. No	Certific	Certificate No Validity		
01	Electronic Semi Micro Bala	nce MI	MK/CAL-96/477904 TVCSPL 2		1/07/863-01	23.07.2022	
ENVIRONMEN	NTAL & DUC CONDITION	NS REFERE	NCE STANDARD & AC	CEPTANCE LIN	1IT		
Temperature 23 ± 1.5 °C		PC .	Reference Std		ISO 8655 - 6 : 2002		
Humidity 40 - 60 % RH		RH	Procedure No		MKBCS - MBV - 03		
Condition of DU	C Receipt Good						
		CAI	LIBRATION RESUL	TS			

1.VOLUME CALIBRATION

S.No	DUC Reading (Mean) μΙ	STD Reading (Mean)	Deviation µl	Expanded Uncertainity (±) µl
1	10	10.15	-0.15	
2	20	20.22	-0.22	1.18
3	50	50.38	-0.38	

Remarks

- 1. The Expanded Uncertainty Associated with the Results is Calculated at a Confidence Level of Approximately 95% with a Coverage factor of K=2.
- 2. The Calibration Certificate Shall not be Reproduced Expect In Full, Without Written Approval Of The Laboratory.
- 3. The Recalibration Interval Should be Determined on the User Requirement.
- 4. The Results Stated In This Certificate Relate Only to the Item Calibrated.
- 5. The User Should Determine The Suitablity Of The Instrument For Is Intended Use.
- 6. Resulted Volume Convert at 27°c of Water Temperature.
- 7. Expanded Uncertainity is also Included Correction Factors.

x-x-x-End Of Certificate -x-x-x-x

S.Murugesan (Calibration Engineer)

Calibrated by

CHENNAI RE

Authorised By

L.Magesh (MD/QM)