MK BEST CALIBRATION SERVICES



NABL ACCREDITED CALIBRATION LABORATORY AS PER ISO/IEC17025: 2017

No. 27, F-2, 1st Floor, 2nd Street, Varalakshmi Nagar, Maduravoyal, (Opp. MGR Engineering College), Chennai - 600 095.

Ph.: 044 - 23780211, Cell : 93802 66480 / 86958 18108 / 90032 77250 E-mail: mkbestcalibration@gmail.com, www.mkbestcalibrationservices.com



CC-3340

CERTIFICATE OF CALIBRATION

FF/7.8/01						Page No	1 of 1	
ULR No	CC3340220000	14534F	Date of Calibration	10.08.2022	Date of	Reciept	10.08.2022	
Certificate No	MKBL/22/08/09	65-004	Recom. Due Date	09.08.2023	Date of	Issue	13.08.2022	
CHOTOMED IN	CODMITTON			Incress of the	T UNDER CA	LIDDATION		
CUSTOMER INFORMATION				DETAILS OF UNIT UNDER CALIBRATION				
M/S ., BIO TECH DIAGNOSTIC CENTRE ,				Description		MICROPIPETTE - 2		
ULUNDUR PET .				Make / Model		SSCIENCES / YE187AL0026852		
				Range/Resolution	Range/Resolution		100 µl to 1000 µl /5 µl	
				Serial No	Serial No		VV 100 - 1000	
				Identification No	Identification No		BTU/CB/GEN/03	
				Calibrated at			LAB	
STANDARD INS	TRUMENTS DI	ETAILS	(The Standards Used ar	e Traceable to Nationa	al /Internationa	l Standards)		
S.No	Description		Id.N	Id.No/SI. No		rate No	Validity	
01 EI	Electronic Semi Micro Balance		ce MK/CA	MK/CAL-96/477904		22/07/1229	22.07.2023	
ENVIRONMENT	TAL & DUC CO	NDITIO	NS REFERENCE	STANDARD & ACC	EPTANCE LIN	MIT		
Temperature 23 ± 1.5°C		С	Reference Std		ISO 8655 - 6 : 2002			
Humidity		0 - 60 % F	ин 🤌	Procedure No		MKBCS - MBV - 03		
Condition of DUC Receipt Good			400 400					
	0.75	argel -	CALIBI	RATION RESULT	S			

I.VOLUME CALIBRATION

S.No	DUC Reading (Mean)	STD Reading (Mean) µl	Deviation µl	Expanded Uncertainity (±) µl	
1	100	100.04	-0.04		
2	300	300.12	-0.12		
3	500	500.24	-0.24	7.29	
3	700	700.38	-0.38		
3	1000	1000.52	-0.52	12. T	

Remarks:

- 1. The Expanded Uncertainty Associated with the Results is Calculated at a Confidence Level of Approximately 95% with a Coverage factor of K=2.
- 2. The Calibration Certificate Shall not be Reproduced Expect In Full, Without Written Approval Of The Laboratory.
- 3. The Recalibration Interval Should be Determined on the User Requirement.
- 4. The Results Stated In This Certificate Relate Only to the Item Calibrated.
- 5. The User Should Determine The Suitablity Of The Instrument For Is Intended Use.
- 6. Resulted Volume Convert at 27°c of Water Temperature.
- 7. Expanded Uncertainty is also Included Correction Factors.

x-x-x-End Of Certificate -x-x-x-x

S.Murugesan (Calibration Engineer)

Calibrated by

CALIBRATION SERVICE CHENICAL PROPERTY OF THE P

Authorised By

L.Magesh
(MD/QM)