



Technofab Enterprises lited Laboratory Vide Certificate No.: CC-3225

or, Functional Industrial Estate, Patpargani, Delhi -110092 41764006 **Mobile**: 9810943334, 8920678805

E-mail: multitech.technofab@gmail.com / mtedelhi2020@gmail.com

Website: www.multitechtechnofab.com



| | | | | CALIBRAT | ΓΙΟΝ | I CERTIFICA | ATE | | | |
|-------------------|------------------|----------------------------------|----------------------------------|---------------|--|----------------------------------|-----------|------------------------------------|------------------|--------------------|
| Calibration Ce | rtificate No.: M | TE/204/CC/659 | 98 | ι | JLR : C | C322522000001 | L928F | | Calibration Issu | ued on: 04-06-2022 |
| Job / Identific | ation No. : MTE | /CAL/JOB/825 | 9 | | Date | of Calibration : | 04-06-20 |)22 | | |
| Item Receipt D | Pate: 01-06-202 | 2 | | | Reco | mmended Date | of Next (| Calibration: 04-06-20 | 023 | |
| Calibrated For | | Care and Diagr Aryan Hospital | nostic Centre , Old Railway R | Road, Gurugra | ım Har | yana | Referen | nce : Order thru Telep | ohonic | |
| Discipline | e Mechanical | | | | Group | p Volume | | | | |
| Certificate for | : Micropipette | • | | | | | | | I | tem Location : Lab |
| Make / I | Model | Serial / I. | D. No. | Inst. Ra | nge | Least | Count | Unit | Ite | em Condition |
| Erbo / QA | 573899 | NA / OHC | /MP/07 | 100 to 1 | .000 | | 5 | μL | μL Working | |
| Envi | ronmental Con | dition | | 25.6 ± 0.5 °C | ± 0.5 °C 54 ± 3% RH Atm. Pr in (hPa) 992 | | | | | |
|) | | | Trac | | | ERENCE DETAIL International S | _ | | | |
| Name of th | e Standard | Make | / Model | С | ertific | ate No. | C | Calibration Agency | v | /alid up to |
| Semi Micr | o Balance | DANWER | / DWA265 | МТ | E/204, | /CC/3781 | N | lultitech Technofab Enterprises | 0 | 6-01-2023 |
| . Cali | bration Proced | ure | Lab Procedur | re : MTE-2/M/ | 2.9 | | | STD Procedure : ISO | D 8655-6 | |

RESULTS: In-Lab Calibration All Readings are in µL, Specified Otherwise

| U.U.C. READING | Volume @ 27°(ml) Chanel 1 | UNCERTAINTY^ |
|----------------|---------------------------|--------------|
| 100 | 0.100401 | ± 2.8879 |
| 500 | 0.501659 | ± 2.8879 |
| 1000 | 1.003183 | ± 2.8879 |

^The reported uncertainty in measurement is stated as the standard uncertainty multiplied by the coverage factor k = 2, which for a normal distribution corresponds to a coverage probability of approximately 95% confidence level.

... MARKS:

• The recommended date for next calibration is mentioned, as asked by the customer.

- 1. This report is not to be reported wholly or in part and cannot be used as evidence in any court of law and not to be used in any advertising media without our special permission in writing.
- 2. The result listed refers only to the calibrated samples and applicable parameters Endorsement of products is neither inferred nor implied.
- 3. Total liability of our organization is limited to the invoiced amount.
- 4. Samples will be destroyed after one month from the date of issue of calibration Certificate unless otherwise specified.
- 5. In case any reconfirmation of contents of Calibration Certificate is required, please contact our office

****** END OF REPORT ******

Calibrated By Sachin Deputy Quality Manager

For and on behalf of **Multitech Technofab Enterprises**

Laboratory Head