

B-59, SECTOR-64, NOIDA (U.P.) 201 307 PH.: 0120-4252360-65, Email: pmmpl.india@gmail.com Website: www.pmmpl.in, www.parashar.info



Galibration Gertificate

ULR - CC2795	23000032978F		Page 1 of 1
Certificate Number	er : PMM/130623/24-1	UUC Received	on 13.06.2023
Calibrated For	M/s. Department Of Pathology	Calibrated on	14.06.2023
	Tej Bahadur Sapru Hospital,	Valid Upto	13.06.2024
	Prayagraj.	Cert. Issue Dat	e 16.06.2023
	Descri	ption of Equipments	
Nomenclature	Micro Pipette	Accuracy/Class	Not Mentioned
Range	5 - 50 ul	Condition of UUC	Physically Ok

Serial No.

Party ID Mark No.

Material / Type			The state of the s	Location	Pathology	
	Master Equipment / Standard Used					
Sr.No.	Nomenclature	Make & Model	Serial No. / I/D Mark	Calibrated From	Certificate No.	Due Date of Calibration
1	Digital Weighing Machine	Sartorius	PMM/WM/06	PMMPL, Noida	PMM/1486	12.05.2024

Standard used for calibration are traceable to Accredited lab, for Standard ISO/IEC: 17025-2017 or National Standards through unbroken chain of calibration.

Calibration Performed at	Laboratory	Environmental	Temperature = 23 ± 2° C
Calibration Procedure No.	CP/M/MV/04	Condition(s)	Humidity = 50 ± 10 % RH
Method Used	Gravimetric Method	Atmospheric Pressure	990 hPa
Reference Standard / Guideline	ISO 8655-6		

Mechanical Calibration

Resolution / Least Count

Make & Model No.

CALIBRATION RESULTS					
Sr.No.	Nominal Value in UUC (in µl)	Actual Observed Value Mean Value in Std. (in µl)	Mean Average Value at 27°C (in µl)	Systematic Error (in µl)	Random Error (in µl)
1	10	10.00	10.01	0.01	0.08
2	25	25.08	25.11	0.11	0.11
3	50	50.22	50.27	0.27	0.08

UUC:- Unit Under Calibration. Std. - Standard Instrument

Uncertainty of Measurement (at approx 95% Confidence Level with Coverage factor k = 2) = \pm

1 µl

Drops

0.65 µl

TBSH/DP/PIP-01

Calibrated By: Pankaj Yadav Designation : Calibration Engineer

Approved By: Jai Prakash

Designation: Tech. Manager / Auth. Sign.

Conditions: 1. This certificate refers only to the particular item submitted for calibration. 2. The calibration result reported in this certificate are valid at the time of and under the stated conditions of measurement. 3. This particular certificate can not be reproduced except in full, without prior permission of chief executive officer of the lab.