Parashar Micro Measurement Pvt. Ltd.



B-59, SECTOR-64, NOIDA (U.P.) 201 307 PH.: 0120-4252360-65, Email : pmmpl.india@gmail.com Website : www.pmmpl.in, www.parashar.info



The way to Technology (20 Years of Excellence

Calibration Certificate

	- CC2795230000						Page 1 of 1
Tej Bah		l/s. Departm	epartment Of Pathology nadur Sapru Hospital,		UUC Received on Calibrated on Valid Upto Cert. Issue Date		13.06.2023 14.06.2023 13.06.2024 16.06.2023
			Descrip	otion of Equipme	nts		
Nomenclature Range Resolution / Least Count Make & Model No. Material / Type		0 to 50 0.1	Thermo Hygrometer ° C / 20 to 99 % RF °C / 1 % RH ′ HTC-1	Condition	of UUC	Not Mentioned Physically Ok TBSH/DP/TH-02 Pathology	
			Master Equ	ipment / Standar	d Used		
Sr. No.	Nomenclature	Make & Model	Serial No. / I/D Mark	Calibrated Fro	m	Certificate No.	Due Date of Calibration
1	Digital RH Indicator with Sensor	Yudian	15H313252 / PMM/RHI/02	ATCL, Gurgao	on	CC263522000007365F	12.11.2023

Standard used for calibration are traceable to Accredited lab, for Standard ISO/IEC: 17025 - 2017 or National Standards Through unbroken chain of calibration

perature = 25 ± 4 °C	
idity = 30 to 75 % RH	

Thermal Calibration

CALIBRATION RESULTS (HUMIDITY AT 25 °C)						
S.N.	Nominal Value in UUC (in %RH)	Actual Observed Value in Std. (in %RH)	Error (in %RH)	± Uncertainty in Measurement (in %RH)		
1	30	28.6	1.4			
2	50	48.6		2.0		
3	70	68.2	1.4	2.0		
1			1.8	2.0		
4	90	91.7	-1.7	2.0		

UUC - Unit Under Calibration

Std. - Standard Instrument

Uncertainty of Measurement (at approx 95% Confidence Level with Coverage factor k = 2)

Calibrated By : Pankaj Yadav
Designation : Calibration Engineer



Approved By: Jai Prakash

Designation: Tech. Manager / Auth. Sign.

Conditions: 1. This certificate refers only to the particular item submitted for calibration.

2. The calibration result reported in this certificate are valid at the time of and under the stated conditions of measurement.

3. This particular certificate can not be reproduced except in full, without prior permission of chief executive officer of the lab.



B-59, SECTOR-64, NOIDA (U.P.) 201 307 PH.: 0120-4252360-65, Email : pmmpl.india@gmail.com Website: www.pmmpl.in, www.parashar.info



Certif	icate Number : P	MM/130623/2	24-3Δ		Tours -		Page 1 of 1
		M/s. Departr	nent Of Pathology Sapru Hospital,		UUC Received on Calibrated on Valid Upto Cert. Issue Date		13.06.2023 14.06.2023 13.06.2024 16.06.2023
			Descrip	ption of Equipmen			10.00.2023
Nomenclature Range Resolution / Least Count Make & Model No. Material / Type		0 to 50 0.1	Digital Thermo Hygrometer 0 to 50 ° C / 20 to 99 % RH 0.1 °C / 1 % RH Hsetin / HTC-1		class of UUC rk No.	Not Mentioned Physically Ok TBSH/DP/TH-02 Pathology	
			Master Equ	ipment / Standard	Used		
Sr. No.	Nomenclature	Make & Model	Serial No. / I/D Mark	Calibrated From		Certificate No.	Due Date of
		Fluke	DMM/CDDT/04			The second second	Calibration

Standard used for calibration are traceable to Accredited lab, for Standard ISO/IEC: 17025 - 2017 or National Standards Through unbroken chain of calibration

PMM/SPRT/01

PMM/CTR/01

Calibration Performed at Calibration Procedure No.	Laboratory	Environmental	Temperature = 25 ± 4 °C	
- unaration i rocedure No.	CP/T/01	Condition(s)	Humidity = 30 to 75 % RH	
Reference Standard / Guideline	DKD - R 5 - 1			

Tempsens, Udaipur

Thermal Calibration

Temperature Scale - ITS-90

SPRT with Indicator

	CALIBRATION RESULTS (TEMPERATURE)						
S.N.	Nominal Value in UUC (in °C)		Error (in °C)	± Uncertainty in Measurement			
1	10.2	10.143	0.057	(in °C)			
2	15.1	100000	0.057	0.23			
3	20.3	15.267	-0.167	0.23			
4		20.476	-0.176	0.23			
5	25.1	25.274	-0.174	0.23			
-	Unit Under Calibration	35.328	-0.128	0.23			

Std. - Standard Instrument

Uncertainty of Measurement (at approx 95% Confidence Level with Coverage factor k = 2)

Fluke

Fluke

Calibrated By : Pankaj Yadav Designation : Calibration Engineer



Approved By: Jai Prakash

Designation: Tech. Manager / Auth. Sign.

TL/022/1121.2.1

09.10.2023

Conditions: 1. This certificate refers only to the particular item submitted for calibration. 2. The calibration result reported in this certificate are valid at the time of and under the stated conditions of measurement.

3. This particular certificate can not be reproduced except in full, without prior permission of chief executive officer of the lab.