## INSTALLATION QUALIFICATION

For

### VITROS 350



Manufactured by: Ortho Clinical Diagnostics, Inc., US

# **Table of Contents**

Sr. No.	Contents	Page No.
I	Approval of the IQ procedure	3
II	Instructions	4
III	Scope	5
IV	Ancillary Information	6
V	Installation Qualification	8
VI	Comments	12
VII	System certification	13

### I. Approval of the IQ procedure

Both LUPIN HEALTHCARE LIMITED and Ortho-Clinical Diagnostics are jointly responsible for the installation of *VITROS 350*, Sr. No. 25014391 in the LUPIN HEALTHCARE LTD LAB.

**Protocol Performed By:** 

Ortho-Clinical Diagnostics Representative

Name

SARAS RAJENDRA

WADHONKAR

Signature:

Designation

SERVICE ENGINEER,

ORTHO CARE- SERVICE

Company

Ortho-Clinical Diagnostics

Date: 30/07/2022

# Validation Team from LUPIN HEALTHCARE LIMITED:

Name

: Dr Sagar Kylat

Signature: Okuu

10- Wary

Designation

: Lab Head

Date: 3017/22

Department

Name

: clinical chemistry

Signature:

Designation

& last Til

Date:

30/7/22

Department

· --7 LUPIN DIAGNOSTIC

Behind Zopadi Cantin, Opp. Monica D.Ed. College Savedi, Ahmednagar-414001

**Customer Authorizations:** 

Customet Authorizations

30,000,7

Name

: Dr Sagar Kulat

Designation: 101

Lab Head

Site

upin Diagnostics, Ahmedna

Signature:

Date:

30/07/22

LUPIN DIAGNOSTIC

Behind Zopadi Cantin, Opp. Monica D.Ed. College Savedi, Ahmednagar-414001

### II. INSTRUCTIONS:

- This document is to be completed at the time the system is installed and set up for operation.
- 2. An authorized Ortho Clinical Diagnostics representative will check the system and enter the specific data as outlined in the appropriate Installation Qualification. Each result will be initialed and dated.
- 3. Employees of (customer) **LUPIN HEALTHCARE LIMITED** will verify each result and sign in the last page.
- 4. <u>ALL</u> deviations from normal specification to include any problems with installation will be noted under COMMENTS. All resolution to such problems will also be noted in the COMMENTS section. Additional space is provided at the end of this installation protocol for the same.
- 5. This document contains proprietary information and is in no way to be copied, photographed or duplicated in any way without expressed written authorization from Ortho-Clinical Diagnostics and LUPIN HEALTHCARE LIMITED.

#### III. SCOPE

This Installation Qualification protocol will be performed on the VITROS 350 bearing Sr. No. 25014391 located at **LUPIN HEALTHCARE LIMITED**. This Installation protocol will define the documentation that will be used to evaluate the instrument installation in accordance with the manufacturer's specifications and intended use. Successful completion of this protocol will verify that the instrument identified has been installed in accordance with the intended usage.

Installation checks will also be performed to verify that the Instrument has been installed with proper connections and utilities.

Trained, knowledgeable personnel will perform qualification studies.

Any exceptional conditions encountered during the qualification studies will be identified for review. Exceptional conditions will be investigated and the appropriate course of action determined. All documents will be initialed and dated.

#### IV. Ancillary Information.

### A. Certification of Purchase Order Compliance

I certify to the best of my knowledge, the instrument installed on 30/07/2022 is in compliance with the specifications of the purchase order.

Verified By: SARAS RAJENDRA WADHONKAR

Date:30/07/2022

#### B. Utilities

Sr. No	Ut	ility	Verified by	Date	
	En	vironmental conditions:		71.481	
	a.	Analyzer will be placed away from the direct sunlight.	SARAS WADHONKAR	30/07/2022	
	b.	Installation site shall be free from dust, significant vibrations and shall be well ventilated.	SARAS WADHONKAR	30/07/2022	
	c.	Installation site floor construction shall be able to support approximately 272 kg.	SARAS WADHONKAR	30/07/2022	
1.	d.	Room temperature will be maintained between $15^{\circ}$ C to $27^{\circ}$ C and the temperature fluctuation during analysis shall not be more than $\pm 2^{\circ}$ C.	SARAS WADHONKAR	30/07/2022	
	e.	The analyzer shall be kept away from strong electromagnetic sources and electrical interferences.	SARAS WADHONKAR	30/07/2022	
	f.	It will be kept near to the power sources.	SARAS WADHONKAR	30/07/2022	
	g.	Maximum relative humidity allowed up to 70%.	SARAS WADHONKAR	30/07/2022	
	h.	If the temperature and humidity fluctuations are not within the specified range, the analyzer cannot maintain data reliability.	SARAS WADHONKAR	30/07/2022	
2.	side (H)		SARAS WADHONKAR	30/07/2022	
3.		etrical Outlets: ual Voltage on site [AC 220-230 Volts 16A 50 HZ]	SARAS WADHONKAR	30/07/2022	

Note: Document any significant changes in Comments section on page 12.

### C. The instrument has been verified for the following

Sr.	Verification		Verified by	Date
<b>No.</b> 1.	Instrument is identified	Yes	SARAS WADHONKA R	30/07/2022
2.	Manufacturer's specifications are included	Yes	SARAS WADHONKA R	30/07/2022
3.	Accessories / Consumables are listed	Yes	SARAS WADHONKA R	30/07/2022
4.	Equipment manual from the manufacturer is documented	Yes	SARAS WADHONKA R	30/07/2022
5.	Manufacturer's Certificate attached	Yes	SARAS WADHONKA R	30/07/2022

# V. Installation Qualification

# A. Equipment Description

The VITROS 350 is a fully automated Dry chemistry analyzer

Instrui	nent Identification	Verified by	Date
	Dry Chemistry Analyzer	SARAS WADHONKAR	30/07/2022
Manufacturer:	Ortho-Clinical Diagnostics	SARAS WADHONKAR	30/07/2022
Model:	VITROS 350	SARAS WADHONKAR	30/07/2022
Serial Number:	25014391	SARAS WADHONKAR	30/07/2022
Size (in cm):	115 (L) x 71 (W) x 120 (H)	SARAS WADHONKAR	30/07/2022
Power:	AC 220-230 V 16A 50Hz±2Hz	SARAS WADHONKAR	30/07/2022
Power consumption:	6880KW hours per year	SARAS WADHONKAR	30/07/2022

### B. Accessories/Consumables

The following accessories were supplied with the instrument. Check ( $\checkmark$ ) 'verified by' in case they are found to be in order.

START UP KIT	1H4182		1 no
	353999	350 TIP RACK	1 no.
	354009	350 MICRO COLLECTION TUBE ADAPTER	l no.
	354007	350 SAMPLE CUP ADAPTER	1 no.
	354000	350 UNIVERSAL SAMPLE TRAY	1 no.
	354011	350 DILUENT TRAY	1 no.
		350 HEIGHT ADAPTER	1 no.
	354002	LINE CORD CONTINENTAL	1 no
	353671		1 no
	354004	MIXING CUP ARRAY	1 no
	8251878	CAL DISK (ver. 5609)	
	8321622	CLIN CHEM PROD INSTRUCTION USE	1 no
	6801855/8175333	350 SYS SOFTWARE (ver. 9.2)	1 no.

250 ANALYZE	CR		
SPARE PART			
KIT	356704		1 no.
	355637	Air Filter	
	TL 3225	Serial Loop Back Connector TL 3225	1 no.
	999339	10 ml Diluent Vials (3 Nos)	1 no.
	999340	5 ml Diluent Vials (3 Nos)	1 no.
		Dispense blade	1 no.
	1C3197		1 no.
	3380/3381	Wrist strap Elastic	1 no.
	J02315	White Reference Slide Box	
	J02316	Black Reference Slide Box	1 no.
	356666	Lamp	1 no.
		Lamp Extractor	1 no.
	583561	RM / IR TL 4538	1 no.
	995298	1 <del>11</del> 11 11 11 11 11 11 11 11 11 11 11 11	1 no.
	356864	Reservoir Seal (3 Nos)	1 110

	356497	Reservoir Cap (3 Nos)	1 no.
	J02253 / J02255 1H0116 339739 994654 356526	Evaporation Cap (23 Nos) Evaporation Cap Spring (5 Nos) Proboscis Screw (2 Nos) Tubing (2 Nos) Read Sync Tool TL 4502 Monitor with stand Touch Screen	1 no. 1 no. 1 no. 1 no. 1 no. 1 no.

## C. List of Manuals, Certificates and Drawings:

Ortho Clinical Diagnostics provides the following with the instrument.

		1 set
8986507	250 REFERENCE SET consist of:	1 no.
	119017 - Operators Manual	1 no.
	1053032 - Operators Quick Guide	1 no.
	8044505 - Maintenance & Diag. Guide	1 no.
	J04190 - Accessories Guide	

## D. Change Control Procedure:

The instrument will not be altered, enhanced, modified or substituted for another system until a formal Change Control Authorization is approved from Ortho Clinical Diagnostics and Micro Therapeutic Research Labs Pvt. Ltd., Chennai.

#### E. Maintenance:

The instrument listed within this document will be placed under the control of the purchasing institution with respect to proper maintenance procedures as detailed in the operations manual.

The maintenance procedures will be filed separately.

A trained analyst using the manuals provided with the instrumentation can perform simple maintenance. Upon expiration of the warranty period Ortho Clinical Diagnostics offers several levels of Maintenance Agreements and Performance Testing services to assist you in maintaining GLP/GMP compliance. Contacting your local representative and requesting for additional Service Agreement can supply additional information.

### F. Spare Parts:

Ortho Clinical Diagnostics recommends the end user to maintain a basic of consumable parts onsite to minimize down time due to minor failures. The list of such consumable parts provided by them is included in the Operator's Manual.

### G. Installation Procedure:

#### 1. Installation Process:

The analyzer PC comes with preinstalled Analyzer Application Software. For any reasons, if the software is to be installed on another PC, the PC will meet the following requirements.

Environment	System Requirement		
Desktop	PII		
Key Board	English Key Board or Standard 101/102 or Microsoft Natural K Board		
Operating System	Qunix		
Port	<ul><li>2 ports for printer</li><li>One port for LIS</li></ul>		
Regional settings	> Language English.		

The system has a preloaded operating software

The Analyser has been installed satisfactorily: No Yes V

Verified by : SARAS RAJENDRA WADHONKAR

,				Ortho Clinical Diagnostics
	VI.	COMMENTS:		

#### VII. **System Certification**

Study data has determined that the system described in this document either meets all criteria outlined in this Installation Qualification Protocol, or exceptional conditions have been identified and documentation included.

Report Performed By: Ortho Clinical Diagnostics Representative

Name

Company:

: SARAS RAJENDRA WADHONKAR

Signature:

Pallonias

Designation: SERVICE ENGINEER, ORTHO CARE- SERVICE

Ortho Clinical Diagnostics

Date: 30/07/2022

#### **Customer Authorizations:**

Name

Name: Dr. Scique Kulat

Designation: Lab Head

Organization: Lypin Diagnostics, Ahmednager

LUPIN DIAGNOSTIC

Behind Zopadi Cantin, Opp. Monica D.Ed. College Savedi, Ahmednagar-414001

### **OPERATION QUALIFICATION**

For VITROS 350



Manufactured by: Ortho Clinical Diagnostics, Inc., US

### **Table of Contents**

Sr. No.	Contents	Page No.
I	Approval of the OQ procedure	3
II	Instructions	4
III	Scope	5
iV	Operation Qualification	6
V	Comments	15
VI	System certification	15

### I. Approval of the IQ procedure

Both Lupin Diagnostics, Ahmednagar and Ortho Clinical Diagnostics are jointly responsible for the operation qualification of VITROS 350, Sr. No. 25014391 in the Laboratory of Lupin Diagnostics, Ahmednagar, as per the Operational Qualification Protocol.

**Protocol Performed By:** Ortho Clinical Diagnostics Representative

Name

Mr. Pankaj Paitwar

Signature:

Designation

Application Support

Date: 1/8/2022

Company

Ortho Clinical Diagnostics

# Validation Team from Lupin Diagnostics, Ahmednagar:

Name

: Bhalsing makesh

Signature:

Designation

Las Tec.

Department

Department of Biochemistry

Name

Sagar modere

Date: 01/08/22
Signature: 01/08/22

Designation

Lab Tee.

Date:

Department

Department of

Biochemistry

### **Customer Authorizations:**

Name

: Dro. Sagar Kulat

Designation: Chief of Labourdour

Site

Ahmednagar

Date:

**LUPIN DIAGNOSTIC** 

118/2022

Behind Zopadi Cantin,

Opp. Monica D.Ed. College Savedi, Ahmednagar-414001

Page 3 of 15

### II. INSTRUCTIONS

- 1. An authorized Ortho Clinical Diagnostics representative will check each module and enter the specific data as outlined in the Operational Qualification. Each result will be noted and dated.
- 2. The concerned employees of Lupin Diagnostics, Ahmednagar will verify each result and sign in the each page. The member of the validation team will carry this out.
- 3. ALL deviations from the acceptance criteria detailed in this document will be noted in the COMMENTS section at the end of the OQ protocol. All resolution to such problems will also be noted in the COMMENTS section, and must be resolved prior to issuance of a SYSTEM CERTIFICATION.

#### III. SCOPE

This Operational Qualification protocol will be performed on the VITROS 350, Sr. No. 25014391 located at Biochemistry Department, Lupin Diagnostics, Ahmednagar. This OQ protocol will define the documentation that will be used to evaluate the completion of the instruments installation in accordance with the manufacturer's specifications and intended use. Successful completion of this protocol will verify that the instrument identified has been installed in accordance with the intended usage.

Trained, knowledgeable personnel will perform qualification studies.

Any exceptional conditions encountered during the qualification studies will be identified for review. Exceptional conditions will be investigated and the appropriate course of action determined. All documents will be initialed and dated.

# OPERATIONAL QUALIFICATION:

### **Instrument Identification**

a. Model Name

VITROS 350

2. Serial Number 25014391

# B. Following is a list of tests to be performed and verified:

Test No.	Test Name	Test purpose	Verified By and date
01	Start up	To make the equipment ready for operation	Mr. Pankaj Paitwar Date – 1/8/2022
02	Daily maintenance	To clean appropriate modules so as to maintain accuracy and precision	Mr. Pankaj Paitwar Date – 1/8/2022
03	Inventory of reagents and consumables	To check the slide supply of installed Vitros 350	Mr. Pankaj Paitwar Date – 1/8/2022
04	Calibration for the assays used	To calibrate the system for every new lot of assay	Mr. Pankaj Paitwar Date – 1/8/2022
05	QC check	To confirm that systems, reagents & consumables are acceptable and working within specifications for each assay used	Mr. Pankaj Paitwar Date – 1/8/2022
06	Sample programming and Analysis	To run the samples	Mr. Pankaj Paitwar Date – 1/8/2022

Test: 1: Starting the system

Purpose: To make the instrument READY for operation

#### Summary:

Instrument checks functioning of different parts of the instrument automatically; if there is an error code, initialize the system and follow corrective action instructions provided for the error code.

#### Procedure:

- Check the room temperature and switch on the Air Conditioner.
- Check the UPS.
- Switch on the Vitros V 350 system by pressing the main switch and hold it for about 10 15 sec.
- Wait for the instrument to get ready after initialization
- The machine is ready for next step if it displays "READY" on the status console
- If not, initialize by pressing the initialize button on the error code screen
- Follow instructions provided for the error codes

Acceptance criteria: System to display READY status

PARAMETER PA

PASS

FAIL

Parameter values for verification: "READY" on Status console PASS

Test: 2: Daily Maintenance

Purpose: To clean appropriate modules so as per the daily maintenance protocol on the display

Method:

Refer detailed procedure for Daily Maintenance

Sr No	Activity	Done by	Date
01	Empty waste container	Mr Pankaj Paitwar	1/8/2022
02	Clean ERF Reservoir Holder & Base	Mr.Pankaj Paitwar	1/8/2022
03	Replace ERF Reservoir	Mr.Pankaj Paitwar	1/8/2022
04	Replace ERF Tip	Mr.Pankaj Paitwar	1/8/2022
05	Clean ERF Tip Sleeve	Mr.Pankaj Paitwar	1/8/2022
06	Clean IWF Reservoir Holder & Base	Mr.Pankaj Paitwar	
07	Replace IWF Reservoir	Mr.Pankaj Paitwar	1/8/2022
08	Replace IWF Tip	Mr.Pankaj Paitwar	1/8/2022
09	Clean IWF Tip Sleeve	Mr.Pankaj Paitwar	1/8/2022
10	Load supplies and remove outdated and empty reagents	Mr.Pankaj Paitwar	1/8/2022
11	Perform Quality Control	Mr.Pankaj Paitwar	1/8/2022

Acceptance criteria System should be "Ready" after daily maintenance without any error

**PARAMETER** 

**PASS** 

**FAIL** 

Parameter values for verification: System found "Ready"

**PASS** 

after daily maintenance

Test: 3: Inventory of reagents and consumables

Purpose: To check the reagent management module of VITROS 350 Dry

Chemistry system

#### Procedure:

Sr No	Activity	Done By	Date
01	Loading of Reagent cartridge in the appropriate slide supply – Supply 1 and Supply 2.	Mr. Pankaj Paitwar	1/8/2022
02	Verify the status of reagents loaded.	Mr. Pankaj Paitwar	1/8/2022

### Acceptance criteria:

No error codes

• All reagents should show "Ready"/cal status

PARAMETER PASS FAIL

Parameter values for verification: No Error codes PASS

Test: 4: Calibration of the assays used

Purpose: To calibrate the system for every new lot of assay

Procedure:

Sr. No.	Activity	Done By	Date
01	Reconstitution of the cal kits for appropriate reagent	Mr. Pankaj Paitwar	1/8/2022
02	Performing Calibration with calibration programming screen	Mr. Pankaj Paitwar	1/8/2022
03	Verification of Calibration report	Mr. Pankaj Paitwar	1/8/2022

Acceptance criteria: "Calibration Successful" should come on screen

PARAMETER PASS FAIL

Parameter values for verification

: "Calibration Successful" found and the report of the same from the analyzer

**PASS** 

Test: 5: QC check

Purpose: To confirm that systems, reagents and consumables are acceptable &

working within specifications for each

assay used.

Procedure:

Sr. No.	Activity	Done By	Date
01	Preparing Liquid or Lyophilized control fluids	Mr. Pankaj Paitwar	1/8/2022
02	Creating QC file	Mr. Pankaj Paitwar	1/8/2022
03	QC sample programming and analysis	Mr. Pankaj Paitwar	1/8/2022
04	Verification of QC results obtained	Mr. Pankaj Paitwar	1/8/2022

Acceptance criteria: QC results within specified limits mentioned on the control product insert

PARAMETER PASS FAIL

**Parameter values for verification:** QC values within  $\pm$  2SD **PASS** 

Test: 6: Sample programming and Analysis

Purpose: To run the samples

**Procedure:** 

Sr.	Activity	Done By	Data
No.	,	Done by	Date
01	Loading and Processing of samples	Mr. Pankaj	1/8/2022
		Paitwar	1/6/2022
02	Programming samples	Mr. Pankaj	1/8/2022
		Paitwar	
03	Unloading the samples	Mr. Pankaj	1/8/2022
-		Paitwar	
04	Viewing samples in process	Mr. Pankaj	1/8/2022
		Paitwar	
05	Review results: Monitoring results	Mr. Pankaj	1/8/2022
		Paitwar	

Acceptance criteria: Samples Analysis & Report without any error

**PARAMETER** 

PASS FAIL

Parameter values for verification:

Sample analysis & Report PASS without any error

### H. Operational procedure:

### a. Certificate of Training

#### 1. Technician Training

This certifies that the technicians have received basic user training in the following categories for the system described in this Operational Qualification.

Mr. Pankaj Paitwar from Ortho Clinical Diagnostics has conducted the training.

Sr. No.	Training program	Initials	Date
1.	Instrument Setup	Mr. Pankaj Paitwar	1/8/2022
2.	System Operation	Mr. Pankaj Paitwar	1/8/2022
3.	Calibration	Mr. Pankaj Paitwar	1/8/2022
4.	Quality Control	Mr. Pankaj Paitwar	1/8/2022
5.	Maintenance	Mr. Pankaj Paitwar	1/8/2022
6.	Basic trouble shooting	Mr. Pankaj Paitwar	1/8/2022

### 2. Operator Training

The users responsible for the operation of this equipment have been trained in the proper usage of the system. Training focused on the basic operation and maintenance of the system.

Sr. No.	Operators	Department	Initials	Date
1	Bhalsing makesh	CC	MTB	1/8/22
2	Sagur mulve	CC	SAM	118122
3	Amol Swall	CC	ACS	118127
4	Tukiv shaiky	CC	IRS	118122
5	meghana kalapirek	CC	mvk	118122

#### V. COMMENTS:

### VI. SYSTEM CERTIFICATION:

Study data has determined that the system described in this document either meets all criteria outline in this Operational Qualification Protocol, or exceptional conditions have been identified and documentation included. Exceptional conditions, if any, have been addressed. The system is ready for Performance Qualification.

## Report Performed By: Ortho Clinical Diagnostics Representative

Name

: Mr. Pankaj Paitwar

Designation: Application Support

Signature:

Company:

Ortho Clinical Diagnostics

Date: 1/8/2022

#### **Customer Authorizations:**

Name

Name: <u>Dr. Sagar Kulat</u>
Designation: <u>Chief of Lab</u>

Organization: Lupin Diagnostics

### LUPIN DIAGNOSTIC

Behind Zopadi Cantin, Opp. Monica D.Ed. College Savedi, Ahmedangar- 4 101

### PERFORMANCE QUALIFICATION

For

#### **VITROS 350**



Manufactured by: Ortho Clinical Diagnostics, Inc., US

#### **Table of Contents**

Sr. No.	Contents	Page No.
I	Approval of the PQ procedure	3
II	Instructions	4
III	Scope	5
iV	Performance Qualification	6
V	Comments	9
VI	System certification	10

#### I. Approval of the PQ procedure

Both Lupin Diagnostics, Ahmednagar and Ortho Clinical Diagnostics are jointly responsible for conducting the Performance Check of the Biochemistry Analyzer, Model -VITROS 350, Serial. No. 25014391 in the Biochemistry Department of Lupin Diagnostics, Ahmednagar as per the attached protocol.

Protocol Performed By: Ortho Clinical Diagnostics Representative

Name

: Mr. Pankaj Paitwar

Signature: Co

Designation

: Application Support

Date: 1/8/2022

Company

: Ortho Clinical Diagnostics

Validation Team from Lupin Diagnostics, Ahmednagar:

Name

Signature:

Designation

Date:

Department

Name

Signature:

Designation

Date:

Department

**Customer Authorizations:** 

Name

: Der. Sagar Keel at

Designation: Chief of Labordom

Site

: Ahmednagar

LUPIN DIAGNOSTIC

Behind Zopadi Cantin, Opp. Monica D.Ed. College Savedi, Ahmednagar-414001

#### II. Instructions.

- 1. An authorized Ortho Clinical Diagnostics representative will check for the performance of the instrument and enter the specific data as outlined in the Performance Qualification. Each result will be noted and dated.
- 2. Performance checks on a regular basis described in the Further Performance Checks will be the responsibility of customer's personnel.
- 3. Employees of Lupin Diagnostics, Ahmednagar will verify each result and sign in the last page.
- 4. ALL deviations from the acceptance criteria detailed in this document will be noted in the **COMMENTS** section at the end of the PQ protocol. All resolution to such problems will also be noted in the **COMMENTS** section, and must be resolved prior to issuance of a SYSTEM CERTIFICATION.
- 5. Any test data that does not meet the specified acceptance criteria will be submitted to the appropriate laboratory personnel for solution. All steps taken subsequently will be documented.
- 6. This document contains proprietary information and is in <u>no</u> way to be copied, photographed or duplicated in any way without expressed written authorization by **Lupin Diagnostics**, **Ahmednagar** and Ortho-Clinical Diagnostics.

#### III. Scope

This Performance Qualification protocol will be performed on the VITROS 350 Serial No. 25014391 located in Biochemistry Department of Lupin Diagnostics, , located in Ahmednagar. This Performance qualification protocol will define the documentation that will be used to evaluate the instrument operation in accordance with the manufacturer's specifications and intended use. Successful completion of this protocol will verify that the instrument identified is performing in accordance with the intended usage.

Trained, knowledgeable personnel will perform qualification studies.

Any exceptional conditions encountered during the Performance qualification studies will be identified for review. Exceptional conditions will be investigated and the appropriate course of action determined. All data will be documented.

### IV. Performance Qualification

#### A. Instrument Identification

**Verified Date** 

1. Model Name

VITROS 350

1/8/2022

2. Serial Number

25014391

1/8/2022

### B. Following is a list of tests to be performed and verified:

Sr.No	Test Name	Test Purpose	Initial / Date
01	QC Run	To see the performance of quality control material on the equipment on selected assay parameters as per the specifications given	1/8/2022
02	Accuracy Study	To compare the obtained value with true values of processed control.	1/8/2022
03	Precision Study	To check the precision performance of the equipment	1/8/2022

#### C. Performance Testing:

Test I

Test Name : QC Run

Purpose : To see the performance of quality control

material on the equipment as per the

specifications given

Method : Microslide – Rate Chemistry

Microslide - Endpoint Chemistry Microslide - Potentiometric Chemistry; Microslide - Immunorate Chemsitry;

Analysis of controls:

Note: Analyze controls for ALT (Microslide Rate Chemistry);

Amylase (Microslide - Two point rate Chemistry);

Sodium (Potentiometric Chemistry);

Potassium (Potentiometric Chemistry);

Sr.	Activity	Procedure done as per the	Remarks	Done By
No.		protocol defined in VITROS 350 Chemistry System Operator's manual – Quality Control	Pass/Fail	Date
01	Preparing Liquid or Lyophilized control fluids	"Instructions for use" of QC material	PASS	Mr. Pankaj Paitwar 1/8/2022
02	Creating QC file	Quality Control – Define control fluids	PASS	Mr. Pankaj Paitwar 1/8/2022
03	QC sample programming and analysis	Quality Control – Process Control fluid samples & Review the Control sample results.	PASS	Mr. Pankaj Paitwar 1/8/2022

Test II

**Test Name** 

Accuracy •

**Purpose** 

To see the accuracy of obtained quality control value in comparison with the :

expected mean values.

Method

Microslide method as mentioned above 0

#### Analysis of controls:

Note: Analyze controls as mentioned above.

Sr. No.	Activity	Procedure done as per the protocol defined in VITROS	Remarks	S Done By
1.00		350 System Operator's manual - Quality Control	Pass/Fail	Date
01	Preparing Liquid or Lyophilized control fluids	'Instructions for use' of QC material	PASS	Mr. Pankaj Paitwar 1/8/2022
02	QC sample programming and analysis	Quality Control – Process Control fluid samples & Review the Control sample results.	PASS	Mr. Pankaj Paitwar 1/8/2022
03	Accuracy Analysis	Compare the obtained Q.C value with mean of expected value as mentioned in the Performance verifier / QC Value chart.	PASS	Mr. Pankaj Paitwar 1/8/2022

## Ortho Clinical Diagnostics

Test III:

**Test Name** 

: Precision Study (As per criteria attached)

Purpose

: To estimate the imprecision or random error of the analytical method

Procedure:

Analyze Performance Verifier Level 1 control for tests ALT (2 x 12 times), Amylase and Na+ (3 x 10 times).

Analyze Performance Verifier Level 2 for Potassium (3 x 10 times) and Phenytoin (3 x 6 times).

Calculate the Mean, SD and CV%.

#### Acceptance Criteria:

Sr. No.	Analyte	Control Level	Precision Limit
01	ALT	PV I	≤ 2.3 SD
02	Amylase	PV I	≤3.9 SD
03	Sodium	PVI	≤ 0.8% CV
04	Potassium	PV I	≤1.0% CV
05	CRBM	TDM	≤4 % CV

#### Ortho Clinical Diagnostics

**COMMENTS: NIL** 

#### V. System Certification

Study data has determined that the VITROS 350 Dry Chemistry system described in this document either meets all criteria outline in this Performance Qualification Protocol, or exceptional conditions have been identified and documentation included. conditions, if any, have been addressed. The system is ready for specified usage.

Report Performed By: Ortho Clinical Diagnostics Representative

Name

: Mr. Pankaj Paitwar

Designation: Application Support

Company : Ortho Clinical Diagnostics

Signature: (

Date: 1/8/2022

Validation Team from Lupin Diagnostics, Ahmednagar:

Name

: Dr Sagar Kulat : Chief of Lab

Signature:

Designation

Date:

Department

: 00

Name

Bhalsing makesh

Signature:

Designation

Date:

Department

: (0.

**Customer Authorizations:** 

Name

Designation: Site

Signature:

Date:

LUPIN DIAĞNOSTIC

Behind Zopadi Cantin, Opp. Monica D.Ed. College

Savedi, Ahmedhagar-414001

Page 10 of 10

#### Ortho Clinical Diagnostics

403, Leela Business Park, Andheri Kurla Road, Andheri East, Mumbai – 400059 T:+91 22 6787 9300 F: +91 22 6787 9333

# **Calibration Certificate**

The below mentioned instrument has been calibrated and tests performed to check the system performance.

Instrument

: VITROS 350

Serial No

25014391

**Customer Name** 

: LUPIN HEALTHCARE LIMITED, AHMEDNAGAR

Calibration performed on

: 18/02/2023

The system's calibration includes optics calibration and checking the reproducibility performance of the instrument as per the guidelines provided by the manufacturer.

Next Calibration will be performed in AUGEST 2023

For Ortho Clinical Diagnostics India Pvt Ltd.



Saras Wadhonkar Service Engineer,Ortho Care Service Pune

Date: 18/02/2023

SS1 SS2 ST INC IR R/C PM INOP Current voltages for all wavelengths.
Touch RETURN to exit or START to repeat tests. RETURN DIAGNOSTICS - Setup/Adjustment - Reflecto 4.89 400 START 5.24 6.08 460 540 MAIN DIAG 6.98 600 LAB COMP: 6.15 630 5.39 670 6.03 688 V9.7 \*\*250 SA12A Feb 18 23 20:47:11 HILP

SH SM SS1 SS2 ST INC IR R/C PM INOP TESTING COMPLETE SAMPLE METERING PERFORMANCE TESTS Leak Test- A∕D Ref. Voltage Check TUB COME:

Reference 4.961 Vdc

Resolution 0.039 Vdc

Ambient Pressure = 2.578

> Pressure to current specifications.
> Do you wish to continue with the Leak Test? Compare Precision Reference Voltage, Resolution Voltage and Ambient

OL NUOLIU MAIN DIAG

Feb 18 23

20:48:03 U9.7 \*\*250

SH SM SS1 SS2 ST INC IR N/C PM INOP SAMPLE METERING PERFORMANCE TESTS Leak Test - Voltage Differential TESTING COMPLETE

Feb 18 23

20:49:33

U9.7 \*\*250

Aspirate = 0.059 Vdc

Dispense = 0.039 Udc

Ambient Pressure = 2.578 Vdc

Compare dispense and aspirate leak voltages to current specifications.
You wish to continue to Hysteresis Test? NUTASI II

DISPLAY PREVIOUS SCREEN

NEXT.

HELP

RETURN

	Compare all mean, max, min values to cu Touch DISPLAY NEXT SCREEN to view data.	Pressure P0: Pressure P1: Pressure P2:	Husteresis	SH SM SS1 SS2 ST INC IR R/C PM INOP SAMPLE METER Hyst
DISPLAY PREVIOUS SCREEN SCREEN SCREEN	min values to current speci EEN to view data.		MEAN 3	ING P
	specifications.		MAX 3 676	LAB COMP: TESTING COMPLETE ERFORMANCE TESTS S Test
4110H		2. 598 3. 711 2. 559	MIN	Feb 18 23 20:53:07 U9.7 **250 PT01C

ED TURN	Revolution 1 2 3 4 5 6 7 10	SH SM SS1 SS2 ST INC
DISPLAY PROVIOU SCREEN		
DISPLAY PREVIOUS SCREEN SCREEN SCREEN	Hysteresis Test esis P0  2.598 0 2.598 0 2.598 0 2.598 0 2.598 0 2.598 0 2.598 0 2.598 0 2.598 0 2.598	INOP ETERING P
		LAB COMP: TESTING COMPLETE ERFORMANCE TESTS
	P2 2.598 2.598 2.598 2.598 2.598 2.598 2.598 2.598 2.598 2.598	SAMPLING ON OFF
		Feb 18 23 20:53:15 U9.7 **250 PT01H

Pi D

SH SM SS1 SS2 ST INC IR R/C PM INOP DIAGNOSTICS - PERFORMANCE TESTS - INCUBATOR PAD REFLECTANCE TEST TESTING COMPLETE LAB COMP: 20:55:25 U9.7 \*\*250 Feb 18 23

MEAN MIN. = 0.9144 REFLECTANCE VALUE

MEAN MAX = 0.9263 REFLECTANCE VALUE

11

0.0120

GRAND MEAN = 0.9220 (MEAN OF ALL SLOT MEANS) (MAX. MEAN - MIN. MEAN)

STAND DEV = 0.0035 (STD. DEV. OF ALL SLOTS)

COMPARE RANGE AND GRAND MEAN TO CURRENT SPECIFICATIONS PRESS DISPLAY\_MORE\_DATA TO VIEW DATA THE MEANS AND RAW DATA 

~ ~		2
PRESS PRESS RETURN		SH SM SS1
		SS1
ETUH	S	SS2
N TO I	SLOT 1 2 3 4 5 6 7 10 11	S
TO VIE Y_MORE_ DISPLAY MORE DATA		INC IR R/C DIAGNOSTICS
EW 1		IR NOST
RETURN TO VIEW THE PREVIOUS PAGE DISPLAY_MORE_DATA TO VIEW THE ME RETURN MORE MORE MAIN DOTAL MENU	REFL1 0.92282 0.92299 0.92223 0.92367 0.92504 0.91579 0.92516 0.92516 0.92407 0.92410	R/C TICS
PREU		PM II
EW T		INOP ERFO D RE
PAGE HE ME ETURN AIN D	REFL2 8.92278 8.92289 8.92282 8.92367 8.92367 8.92386 8.92386 8.92386 8.92386	RMAN
RETURN TO VIEW THE PREVIOUS PAGE OF DISPLAY_MORE_DATA TO VIEW THE MEANS DISPLAY RETURN TO MAIN DIAG MAIN DIAG DATA	35555688888886°	INOP TESTING PERFORMANCE TESTS AD REFLECTANCE TESTS
		LAB CO TESTING E TESTS
DATA AND RAW DATA	REFL3 0. 92268 0. 92287 0. 92358 0. 92358 0. 92485 0. 91560 0. 92490 0. 92374 0. 92374 0. 92374 0. 92388	
표	30 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	P: - INCUBA
ATA		INCUBATO
	ME M	SAMPI ON OR
	MEAN . 92273 . 92292 . 92287 . 92364 . 92497 . 91578 . 91578 . 92582 . 92389 . 92389	
		DFF OFF
		Feb 20:1 09.
		7 55 1
НЕПР		[8 23 5:33 **250 PT16C
		(-)

PI D

RETURN HOLD ING MAIN DING MENU	>Compare the values to current specifications.  Do you wish to continue with the Leak Test?		2.500 Vdc	COARSE GAIN	Signal Processing Check	SH SM SS1 SS2 ST INC IR R/C PM INOP TESTING COMPLETE  DIAGNOSTICS - Performance Test  Reference Metering - System Check
						SAMPL ING ON OFF
d'IMI.	( <del>1</del> ):					Feb 18 23 20:57:08 U9.7 **250 PT22B

RETURN DISPLAY DISPLAY PREVIOUS NEXT SCREEN SCREEN	>Compare the values to current specifications. Do you wish to continue to Hysteresis Test?	Ambient Pressure = 2.578 Vdc	Aspirate = -0.039 Vdc Dispense = -0.039 Vdc	SH SM SS1 SS2 ST INC IR R/C PM INOP TESTING COMPLETE  DIAGNOSTICS - Performance Test  Leak Test - Voltage Differential
			-0.039 Vdc	SAMPL ING ON OFF
HELP	(f):			Feb 18 23 20:58:29 V9.7 **250 PT22D

RETURN	>Compare	PRI NO.		ISS MS HS
	the values	Hysteresis: Pressure P0: P1: P2:		AI ONI IS 285 ISS MS HS
DISPLAY	to currer	Pi Pi Pi		The second secon
RETURN TO MAIN DIAG	>Compare the values to current specifications.	0.163 2.617 4.473 2.598	MEAN	IAB COMP:  R/C PM INOP TESTING COMPLETE  DIAGNOSTICS - Performance Test  Reference Metering - System Check  Hysteresis Check
		1. 633 2. 637 4. 609 2. 617	XNM	P: COMPLETE Ce Test tem Check
				SAMPLING ON OFF
НЕПР		0.000 2.617 4.375 2.578	NIN	Feb 18 23 20:59:12 U9.7 **250 PT22L

Delay Time 0.0 ms 1.0 ms 1.5 ms 2.0 ms 2.5 ms 3.5 ms 4.0 ms 4.5 ms 5.0 ms	SCHEDULER * INCUBATOR ENVIRONMENT * temperature failure  LAB COMP:  SM SS1 SS2 ST INC IR R/C PM INOP  DIAGNOSTICS - Setup/Adjustments - Read
Signal 10716 10481 10481 10347 10250 10156 10142 10136 * 10238 10334 10503	T * temp etup∕Adj
Delay Time 5.5 ms 6.0 ms 6.5 ms 7.0 ms 7.5 ms 8.0 ms 9.0 ms 9.5 ms 10.0 ms	erature failure LAB COMP: TESTING COMPLETE ustments - Read Sy
Signal 11084 11450 11795 12228 12650 13177 13716 14072 14621 15123	SAMPLING Feb 18 23 ON OFF 21:21:36 U9.7 **250 Inc SA15B

Lowest signal is marked by flashing \*. Save new setting?
Touch RETURN or RETURN\_TO\_MAIN\_DIAG\_MENU to abort the changes.

MAIN DIAG

HELP

Holl	DISPENSE/ INCUBATOR	NAIN DIAG NAIN DIAG	ONEW CONTENT	RETURN
(Y):	2	new settin abort the	d by flashing . _TO_MAIN_DIAG_	Lowest signal is marked by flashing *. Save Touch RETURN or RETURN_TO_MAIN_DIAG_MENU to
14771	53	9605	43	INCUBATOR ROTOR SIZING
1325 <b>0</b> 13995	61 59	9511 9467 *	39 41	HLAGIT NLAGIT
11985 12672	57 57	9898 9631	33 3	
11381	ន	10172	33	
11005	된 :	10678	31	PATH
10483	49	11182	29 29	W/ DISP.
9866	3 5	12138	3 23	TWOIRPUTOR
SIGNAL	DISPENSE OFFSET	SIGNAL	DISPENSE OFFSET	DISPENSE INCUBATOR TO RI/CH METERING DEPTH
21:38:29 09.7 **256 SABSI	Q. P. F.	TESTING COMPLETE de Transport	PM INOP ustments - Slic	SM SS1 SS2 ST INC IR R/C PM INOP TESTING CO DIAGNOSTICS - Setup/Adjustments - Slide Transport
Feb 18 23	TdW	mperature failure	JIRONMENT * ter	SCHEDULER * INCUBATOR ENVIRONMENT * temperature failure

-

Delay Time  0.0 ms  1.0 ms  1.5 ms  2.0 ms  2.5 ms  3.6 ms  4.6 ms  5.6 ms	SCHEDULER * INCUBATOR ENVIRONMENT * temperature failure LAB COMP: SM SS1 SS2 ST INC IR R/C PM INOP TESTING COMPLETE DIAGNOSTICS - Setup/Adjustments - Read
Signal 18134 9898 9729 9729 9591 9499 9479 * 9571 9679 9857	ATOR ENVIRONMENT * temperature f LAB COMP IR R/C PM INOP TESTING C DIAGNOSTICS - Setup/Adjustments
Delay Time 5.5 ms 6.8 ms 7.8 ms 7.5 ms 8.8 ms 9.8 ms 9.8 ms 9.8 ms	Syr
Signal 10368 10775 11214 11634 12120 12639 13601 14158 14743	SAMPLING Feb 18 23 ON OFF 21:37:34 U9.7 **250 C SA15B

Lowest signal is marked by flashing \*. Save new setting?
Touch RETURN or RETURN\_TO\_MAIN\_DIAG\_MENU to abort the changes.

MAIN DIAG

HELLP

RETURN	Lowest signal Touch RETURN	ROTOR	INCHROTOR	DEPTH DE	马	PM		PATH	W DISP.	INCUBATOR		METERING DE	TO RT	DISPENSE INCU	DIAGNOSTICS -	SM SS1 SS2 ST I	SCHEDULER * INCUBATOR ENVIRONMENT * temperature failure
	Y Lowest signal is marked by flashing *. Save Touch RETURN or RETURN_TO_MAIN_DIAG_MENU to			DEPTH		INCURATOR						JEP TH	RT/CH (	INCUBATOR	DIAGNOSTICS - Setup/Adjustments	ADNI NA 3/4 NI ONI IS 2SS TSS MS	UBATOR ENVIRONMI
RETURN TO MAIN DIAG MENU	lashing *. Save [N_DIAG_MENU to	ŧ	41 43	39						27	25			DISPENSE	1		INI * tempe
	new settin abort the		9487 * 9536	9565	9796	10118	10571	18939	11648	11880	12323		SIGNAL		Slide Transport	TESTING COMPLETE	erature failure LAB COMP:
RESET DISPENSE/ INCUBATOR	g? changes.	٤	61	59	57 57	SA 8	원 (	2	49	47	45		OFFSET	DISPENSE			SAMPLING ON OFF
HELL	(Y): <b>•</b>	1.1000	13637 14566	12998	12288	11815	11143	18678	10202	9951	9652		SIGNAL		SA05B	U9.7 **250	Feb 18 23 21:45:52

- Light		RETURN TO MAIN DIAG MENU			RETURN
: (N/A)				update?	> Automatic update?
	**	8.8	0.98292		80 S
** 0.00999	0.00006 *** -0.0025 0.00006 *** -0.0025	S (S)	8.98754 Я.98699	630 nm	
** 0.00030	8.88885 *** -8.8829	8.8	0.99223	WIII 889	Masie
	* * * -0	s	0.98825 0.98995		DATA
** 0.00000 ** 0.00061	0.00012 ** -0.0011 0.00012		0.30650	486 mm	
D DODEO	K K	k k	0 46719	340	nrspray
Black Dr S.D.	White Dr S.D. New BCF	White	New WCT	<b>Wavelength</b>	
	ary	Summary			
tion Factors SA20G	Rate/CM Correction F	1	ιp∕Adjustmo	DIAGNOSTICS - Setup/Adjustments	DIAGN
0FF 22:02:48 09.7 **250		TAL	PM INOP	SM SS1 SS2 ST INC IR R/C PM INOP	SM SS1 SS2 S
SAMPLING Feb 18 23		* tempera	IRONMENT	SCHEDULER * INCUBATOR ENVIRONMENT * temperature failure	SCHEDULER *

DATA DATA DATA	SCHEDULER * 1 SM SS1 SS2 S1 DIAGNO
348 nm 468 nm 548 nm 688 nm 688 nm	SCHEDULER * INCUBATOR ENVIRONMEN  SM SS1 SS2 ST INC IR R/C PM INOP  DIAGNOSTICS - Setup/Adjus  Wavelength White
0.56340 0.85820 0.85850 0.85820 0.85470 0.85430 0.85660	RONMENT * temp M INOP /Adjustments - White Assay
8.45988 8.77518 8.95256 8.95716 8.95879 8.95771 8.95848	SCHEDULER * INCUBATOR ENVIRONMENT * temperature failure COMP:  SM SS1 SS2 ST INC IR R/C PM INOP TESTING COMPLETE  DIAGNOSTICS - Setup/Adjustments - Rate/CM Correction Factors  White Correction Factors  Wavelength White Assay Current MCF New MCF
0.46718 0.80650 0.98825 0.98995 0.99223 0.98754 0.98699 0.98292	SAMPLING ON OFF tion Factors Ractors
*** 0.00032 0.00012 0.00006 0.00007 0.00006 0.00006 0.00006	Feb 18 23 22:82:57 U9.7 **258 SA21A Dr S.D.

> Touch DISPLAY BLACK DATA to display more data.

RETURN

BRITT NI BM BOIL NI BM DI NI BM

DATA	DISPLAY	DISPLAY		SCHEDULER * 1 SM SS1 SS2 S1
670 nm 680 nm	548 nm 688 nm		<b>Wavelength</b>	SCHEDULER * INCUBATOR ENVIRONMEN  SM SS1 SS2 ST INC IR R/C PM INOP  DIAGNOSTICS - Setup/Adjus
0.02460 0.02430	8.02118 0.02190 0.02210 0.02310	0.01890 0.02280	Black Assay	T * temp
-0.0015 -0.0022	-0.0014 -0.0023 -0.0018	-0.0038 -0.0034	Black Correcti	erature failure LAB COMP: TESTING COMPLETE Rate/CM Correct
	*** -0.8022 *** -0.8021 *** -0.8029	** -0.8841 ** -0.8837	ion Factors New BCF	TE SAMPLING ON OFF
	** 0.00053 ** 0.00036	** 0.00058	Dr S.D.	G Feb 18 23 F 22:03:03 U9.7 **250 SA21B

> Touch DISPLAY WHITE DATA to display more data.

RETURN

RETURN TO MAIN DIAG MENU

HELP

670	340 460 540 600	Wavelength (nm)	SCHEDULER * INCUBATOR ENVIRONMENT SS1 SS2 ST INC IR R/C PM INOP DIAGNOSTICS - Performance
285	284 284 284 284 285	Mean Dark	TOR BNUIRON  R/C PM INOP  - Performa
0.5085 0.4795	0.4795 0.4983 0.4795 0.4795 0.4498 0.4795	- Summar SD Dark	MENI * temp
35459 39788	33601 31930 31930 34477 39670 45747	- Summary Screen - D Mean rk Signal	ER * INCUBATOR ENVIRONMENT * temperature failu LAB COMP: ST INC IR R/C PM INOP TESTING COMPL DIAGNOSTICS - Performance Tests - Reflectomete
1.0854	1. 0743 1. 4527 1. 7207 1. 7927 1. 7927 1. 7876 2. 0126	SD Signal	re r - St
3.06 5.01	3, 20 4, 55 4, 99 5, 80	%CU*1K	
			Feb 18 23 22:08:32 U9.7 **250 PT31D

- Compare SD of Dark and/or Signal reads to current specifications. Compare %CV\*1K to current specification. Touch DISPLAY MORE DATA to view detailed data.
- DISPLAY RETURN TO MAIN DIAG

RETURN

DATA

PNGM

HELP

	K+ Cl- ECOZ THEO Fe Touch targ	GLU UREA CREA AMON	READY Sample ID 89711
PATIBATA	K+ 3.75 CHOL C1- 92.2 TRIG ECO2 THEO Fe TOuch targets to review results and data - CONTROL sample	84.8 29.60 1.83	REVIEW RE Pos Track Tray
RESULT RECORD	CHOL TRIG URIC TP	AMYL LIPA Ca Mg PHOS	REVIEW RESULTS - ack Tray
REVIEW	F2 4		LAB CC TESTS I - Verificat Run Dat 02/18/2
REVIEW .	4.65		LAB COMP: TESTS IN PROCESS Verification and Edi Run Date Run Time 82/18/23 22:20:25
PREVIEW OROUP	ALKP F2 8: GGT TBIL Bu Bc	CEMB CE LEH AST	SAMPLING Feb 18 23 ON OFF 22:30:09 ON OFF 22:30:09 RU06A Priority Fluid Man Dil ROUTINE SERUM 1.000
	F2 edital	F2	Feb 22: U9. Uuid ERUM
E	83. 1.00 .93 0.00	43.	Feb 18 23 22:30:09 U9.7 **250 RU06A id Man Dil UM 1.000


RETURN PATIENT RESULT NEXT DATA RECORD SAMPLE	TIBC SALI Li CRP	K+ C1- ECO2 THEO	READY Sample ID 89711
EDIT I PATIENT R DAIN R		3.75 92.2	REVIEW R Pos Track Tray 1 1
DELETE RECORD SAI	PHBR CREW	CHOL TRIG	ESULTS -
1		F2 4.65	LAB DMP: TESTS IN PROCESS Verification and E Run Date Run Tim 82/18/23 22:20:2
Sample DM	LAC ALC PHYT	ALKP GGT TBIL Bu Bc	OCESS and Edit n Time F :20:25 F
REVIEW PREVIOUS GROUP		AP F2	AG Fe 22 U9 U9 SERUM
HINT		83. 1.88 . 93 8.88	Feb 18 23 22:30:17 U9.7 **250 RU06A id Man Dil id Man Dil

Touch targ	ASTJ	C/H TDTC	READY Sample ID 89711
ets to review PATIDNT DATA			Pos Track Tray
Touch targets to review results and data - CONTROL  EDIT  EDIT  PATIENT RESULT  NEXT  NEXT  ORDU  GROU	HLTU	OSMO %SAT	ESULTS -
or many contract of the contra	25.		LAB DMP: TESTS IN PROCESS  Uerification and Edit Run Date Run Time Priority Fluid Man D 02/18/23 22:20:25 ROUTINE SERUM 1.000
sample is not editable  PRIVIDUS  PRIVIOUS  HE	ALT2	DELB BELB	SAMPLING Fe ON OFF 22 nd Edit Time Priority Fluid 20:25 ROUTINE SERUM
ditable			Feb 18 23 22:30:30 U9.7 **250 RU06A Luid Man Dil BRUM 1.000

RETURN	Y Touch targets to review results	ECOZ THEO Fe	K+ C1-	AMON Na+	UREA	OTU	Sample ID 89712	READY
PATIBAT	ts to revie		5.83 82.8	122.9	83. <b>01</b>	246.8	REVIEW R Pos Track Tray 1 2	
RESULT RECORD	w results a	URIC TP	CHOL TRIG	Mg	LIPA	ТАМУ	REVIEW RESULTS ack Tray 2	
REUIEN NEXT SAMPLE	and data - (						- Ve	TAB C
REVIEW NEXT GROUP	CONTROL sample is not editable	3.24					rification and Edit Run Date Run Time Priority Fluid Man D 02/18/23 22:23:41 ROUTINE SERUM 1.000	TESTING COMPLETE
REU LEM PREU LOUS	ple is not	TBIL Bu Bc	ALKP GGT	CKMB		AST	it Priority ROUTINE	SAMPLING ON OFF
	edit	F2	<b>F</b> 3			F2	Fluid Serum	Fe 22 U9
НЕГР	able	4.72 4.47 8.88	377.			187.	RV06A Man Dil 1.000	Feb 18 23 22:33:12 U9.7 **250

	> Touch targo	SALI Li CRP	TIBC	THEO Fe	CI− K+	Sample ID 89712	READY
PATIENT	Nouch targets to review results and data - CON				5.83 82.8	REVIEW RI Pos Track Tray 1 2	
NESULT R	results and	CREAN CHE	ALB	URIC	CHOL	REVIEW RESULTS - ack Tray 2	
NEXT N	data - CONT		2.39	3.24		သက္	LAB COMP:
HEXT PI	TROL sample is not editable	PI AI	) LAC		ALK!	Run Time Priority Fluid Man D 22:23:41 ROUTINE SERUM 1.000	MPLETE
REUIDH PREUIOUS GROUP	is not edi	PHYT	n	TBIL F2 Bu F3	ALKP F3	ority Flu	MPL ING OFF
НШТР	tahlo			4.72 4.47 8.88	377.	RU86A id Man Dil JM 1.888	Feb 18 23 22:33:19 U9.7 **250

RETURN	Touch targets to review results and data - CONTROL sample is not editable	ASTJ	C/H ATDT TDTC	READY Sample ID 89712
EDIT PATIENT DATA	ets to revie			REVIEW RE Pos Track Tray
RESULT	w results a	AL TU	OSMO %SAT	REVIEW RESULTS - ack Tray
REVIEW NEXT SAMPLE	nd data - CC	88.		LAB COMP:  TESTING COMPLETE  Uerification and Edit  Run Date Run Time P  82/18/23 22:23:41 R
REVIEW NEXT GROUP	INTROL sampl			OMPLETE On and Edit Run Time Pr 22:23:41 RO
REVIEW PREVIOUS GROUP	e is not ed	ALT2	DELB % MB LDL	SAMPLING Feb 18 23  IAB COMP:  TESTING COMPLETE  rification and Edit Run Date Run Time Priority Fluid Man Dil 82/18/23 22:23:41 ROUTINE SERUM 1.800
ATKIH	itable			Feb 18 23 22:33:28 U9.7 **250 RU86A Lid Man Dil RUM 1.800





## **CALIBRATION REPORT**

**STATUS**: PASSED

DESCRIPTION: Variable Volume Pipette VV-200 (20-200 µl)

**DEVICE ID**: 21400599

**CALIBRATION DATE:** 16/11/2022 10:50 AM

**Method ID**: VV/20-200

**TERMINAL ID**: 19

ULR No.: CC270521000091802F

Location: Lucknow (Permanent Lab)




#### **ENVIRONMENTAL FACTORS**

TEMP: 25.00 °C Z FACTOR: 1.0026 mm³/mg BARO. PRESSURE: 80.00 KPa REL. HUMIDITY: 60.00%

#### **CALIBRATION STATISTICS**

						Inaccu	racy E%	Imprecis	ion CV%	a			
Vol (µl)	No	Cum Wt (mg)	Vol (µl)	Mean (µI)	SD (µI)	Actual	Target	Actual	Target	Status			
	1	20.600	20.654										
20.000	2	40.900	20.353	20.754	0.459	3.770	6.00	< 2.00	2.00	PASSED			
	3	62.100	21.255				1			. (*		191	
	1	99.300	99.558										
100.000	2	198.700	99.658	99.625	0.058	0.375	1.20	< 0.40	0.40	PASSED			
	3	298.100	99.658										
	1	199.000	199.517		,								
200,000	2	398.900	200.420	199.852	0.495	0.074	0.60	< 0.20	0.20	PASSED			
,	3	598.000	199.618						,				



\* Specifications conform to ISO:8655 standards.

\* Each instrument is individually calibrated on electronic balance.

\* 750 mmHg = 99.98 kPa.


\* Weight in mg or g.


\* Volume, Mean & S.D. in ml or µl.

#### Reference standard

The instrument is calibrated using a standard electronic balance with calibration traceability to NPL.

The reported expanded uncertainty of measurement is calculated by multiplying the standard uncertainty of measurement by the coverage factor k=2, which for normal distribution corresponds to a coverage probability of approximately 95%.







## **CALIBRATION REPORT**

STATUS: PASSED

DESCRIPTION: Variable Volume Pipette VV-200 (20-200 μΙ)

**DEVICE ID**: 21400602

CALIBRATION DATE: 15/11/2022 2:56 PM

Method ID: VV/20-200

TERMINAL ID: 19

ULR No.: CC270521000091800F

Location: Lucknow (Permanent Lab)



## **ENVIRONMENTAL FACTORS**

TEMP: 25.00 °C Z FACTOR: 1.0026 nim²/mg BARO. PRESSURE: 80.00 KPa REL. HUMIDITY: 60.00%

### **CALIBRATION STATISTICS**

Vol (µl)	N.	C				Inaccu	racy E%	Imprecis	ion CV%	
νοι (μι)	No	Cum Wt (mg)	Vol (µl)	Mean (µl)	SD (µI)	Actual	Target	Actual	Target	Status
	1	20.700	20.754						301	Otatas
20.000	. 2	41.500	20.854	20.787	0.058	3.937	6.00	< 2.00	2.00	DACCED
	3	62.200	20.754	1		0.007	0.00	1 2.00	2.00	PASSED
	1	99.600	99.859							
100.000	2	199.000	99.658	99.725	0.116	0.275	1.20	< 0.40	0.40	מאספרה
	3	298.400	99.658			0.270	1.20	10.40	0.40	PASSED
	1	200.000	200.520							
200.000	2	399.300	199.818	199.885	0.604	0.058	0.60	< 0.20	0.00	
	3	598.100	199.317			5.500	0.00	- 0.20	0.20	PASSED

Volume	Above 10 μl to 100 μl	Above 100 μl to 1000 μl	Above 1 ml to 10 ml	Above 10 ml to 100 ml	
Uncertainty (k=2)	0.1 µl	0.1 µl	0.1 µt	4 µi	

Specifications conform to ISO:8655 standards.

Each instrument is individually calibrated on electronic balance.

750 mmHg = 99.98 kPa.

· Weight in mg or g.

\* Volume, Mean & S.D. in ml or µl.

Reference standard

The instrument is calibrated using a standard electronic balance with calibration traceability to NPL.

The reported expanded uncertainty of measurement is calculated by multiplying the standard uncertainty of measurement by the coverage factor k=2, which for normal distribution corresponds to a coverage probability of approximately 95%.







# National Accreditation Board for Testing and Calibration Laboratories

## CERTIFICATE OF ACCREDITATION

#### **MICROLIT - LABORATORY**

has been assessed and accredited in accordance with the standard

**ISO/IEC 17025:2017** 

# "General Requirements for the Competence of Testing & Calibration Laboratories"

for its facilities at

629, PAKRAMAU, KURSI ROAD, LUCKNOW, UTTAR PRADESH, INDIA

in the field of

#### **CALIBRATION**

**Certificate Number:** 

CC-1032

**Issue Date:** 

30/04/2023

Valid Until:

29/04/2025

This certificate remains valid for the Scope of Accreditation as specified in the annexure subject to continued satisfactory compliance to the above standard & the relevant requirements of NABL.

(To see the scope of accreditation of this laboratory, you may also visit NABL website www.nabl-india.org)

Name of Legal Identity: MICROLIT - LABORATORY

Signed for and on behalf of NABL



N. Venkateswaran Chief Executive Officer



## INIKS ENGINEERING COMPA

Plot No. 21, Anand Nagar, Near Wasan Automobiles, Sahyadri Chowk, M.I.D.C. A'nagar - 414111. [M.S.] Tel. [0241] 2778918, E-mail : finiks97@rediffmail.com



## alibration Certificate

ULR: CC226723000003632F

CALIBRATED ON	ISSUED ON	CERTIFICATE NO.	NEXT CALIBRATION DUE ON (suggested by customer)	Page 1 of 1
12/07/2023	15/07/2023	23-EGC-12-3-1	11/07/2024	

CALIBRATED FOR

: M/S. LUPIN DIAGNOSTICS LIMITED,

Ahmednagar, Maharashtra

CUSTOMER'S CHALLAN NO.

Dated: 12/07/2023

Work Order No.: 23/G/12/3

TYPE OF INSTRUMENT

: DIGITAL CENTRIFUGE MACHINE(RPM)

**IDENTIFICATION** 

Remi

**Sr.No.** : ZHIN/36370

MAKE RANGE

0 to 5250 RPM

ID No.: LOL/HLM/LAB/CEN/01

L.C.

10 RPM

Model: R-8C

**TYPE** : Digital

LAB ID NO.

: 23/G/12/3/1

**ENVIRONMENTAL CONDITION** 

25°C±10°C /50%RH±10%RH

**CONDITION AT RECEIPT: OK** 

REFERENCE DOCUMENT USED: IS 12508 - 1988 & Sanas TR 45-01 (2008-2-15)

**CALIBRATION PROCEDURE** 

CP/81

**CALIBRATION LOCATION:** At Site

Product Field Discipline

: MECHANICAL-ACCELERATION AND SPEED

Equipment / Reference Standards Used For Calibration : Traceable to National / International standards.

Equipment / Reference Standard	Identification No.	Certificate No.	Date of Calibration	Valid Upto
DIGITAL TACHOMETER	FINIKS/TM-01	NI2023/06/0403	10/06/2023	09/06/2024

#### **CALIBRATION RESULTS**

#### Parameter: RPM (NON-CONTACT TYPE)

Calibration Point in RPM	Stanadard Reading in RPM	UUC Reading in RPM	Error in RPM	Stability (S) (RPM)	Measurement Uncertainty (±)
1000	999.5	1000	0.50	0.00	6.56 RPM
2000	1998.6	2000	1.40	0.00	10.30 RPM
3000	2995.6	3000	4.40	0.00	10.30 RPM
4000	3990.3	4000	9.70	0.00	10.30 RPM
5000	4980.1	5000	19.90	0.00	10.30 RPM

The reported uncertainty is at coverage factor K=2 which corresponds to a coverage probability of approximately 95.45% for normal distribution.

---- END OF CERTIFICATE ----

CALIBRATION

Mr.Mokal M.S

Calibration Engineer


This Certificate refers only to the item (s) submitted for calibration

This calibration results in this certificate are valid at the time of and under the stated conditions of measurements.

This certificate shall note be reproduced, except in full without our prior permission in writing

Authorized By Mr.Warpe B.S Technical Manager







## FINIKS ENGINEERING COMPA

Plot No. 21, Anand Nagar, Near Wasan Automobiles, Sahyadri Chowk, M.I.D.C. A'nagar - 414111. [M.S.] Tel. [0241] 2778918, E-mail : finiks97@rediffmail.com



## Calibration Certificate

ULR: CC226723000003633F

CALIBRATED ON ISSUED ON		CERTIFICATE NO.	NEXT CALIBRATION DUE ON (suggested by customer)	Page 1 of 1	
12/07/2023	15/07/2023	23-EGC-12-3-2	11/07/2024		

CALIBRATED FOR

: M/S. LUPIN DIAGNOSTICS LIMITED,

Ahmednagar, Maharashtra

CUSTOMER'S CHALLAN NO.

Dated: 12/07/2023

Work Order No.: 23/G/12/3

TYPE OF INSTRUMENT

: DIGITAL CENTRIFUGE MACHINE(RPM)

**IDENTIFICATION** 

MAKE Remi

Sr.No.: ZHIN/36374

RANGE

10 to 5250 RPM

ID No.: LOL/HLM/LAB/CEN/02

L.C. 10 RPM

Model: R-8C

**TYPE** 

: Digital

LAB ID NO.

: 23/G/12/3/2

**ENVIRONMENTAL CONDITION** 

: 25°C±10°C /50%RH±10%RH

**CONDITION AT RECEIPT: OK** 

REFERENCE DOCUMENT USED : IS 12508 - 1988 & Sanas TR 45-01 (2008-2-15)

**CALIBRATION PROCEDURE** 

: CP/81

**CALIBRATION LOCATION:** At Site

Product Field Discipline

: MECHANICAL-ACCELERATION AND SPEED

Equipment / Reference Standards Used For Calibration : Traceable to National / International standards.

	Equipment / Reference Standard	Identification No.	Certificate No.	Date of Calibration	Valid Upto
L	DIGITAL TACHOMETER	FINIKS/TM-01	NI2023/06/0403	10/06/2023	09/06/2024
				10/00/2023	03/00/2024

#### **CALIBRATION RESULTS**

#### Parameter: RPM (NON-CONTACT TYPE)

Calibration Point in RPM	Stanadard Reading in RPM	UUC Reading in RPM	Error in RPM	Stability (S) (RPM)	Measurement Uncertainty (±)
1000	998.6	1000	1.40	0.00	6.56 RPM
2000	1997.5	2000	2.50	0.00	6.56 RPM
3000	2992.3	3000	7.70	0.00	
4000	3986.5	4000			6.56 RPM
5000			13.50	0.00	6.56 RPM
The reported was a dai	4981.2	5000	18.80	0.00	6.56 RPM

The reported uncertainty is at coverage factor K=2 which corresponds to a coverage probability of approximately 95.45% for normal distribution.

---- END OF CERTIFICATE ----

CALIBRATION

LABORATORY

MEDNAGA

Mr.Mokal M.S Calibration Engineer

This Certificate refers only to the item (s) submitted for calibration

This calibration results in this certificate are valid at the time of and under the stated conditions of measurements.

This certificate shall note be reproduced, except in full without our prior permission in writing

Authorized By Mr.Warpe B.S Technical Manager

FM/25

