

RELIABLE TECHNICAL SERVI

(Division of Reliable Technocare Pvt. Ltd.)

"RELIABLE HOUSE" 497/2834-35, Sant Tukaram Nagar, Pimpri, Pune - 411018. MH, India. Telefax: 020-27421170 Cell: 7774055755, 7774055855, 7774058855, 7774022900 Email: reliable1010@gmail.com/reliabletechnocare@gmail.com

Web.: www.reliable.world





| - AI | DD 4 | TIONI | CERT | -11-1/ | OATE |
|------|------|---------|-------|--------|------|
| (,) | INPA | 11(1)(1 | CERI | 11-10 | AIF |
| UMI | | | OLIVI | 11 11 | |

1.CUSTOMER Tezu District Hospital COVID-19 Vaccination Center Lohit, Arunachal Pradesh - 792001. Temperature (°C) :- 23.1 Relative Humidity (%RH) :- 48.9

Condition of Item :- OK
Atmospheric Pressure :- 944.2 mbar

:- 1 of 1 Page No.

NABL Accreditation No. :- CC-2927 Certificate No. :- 23.03.08.001
Date of Received :- 08.03.2023 Date of Calibration :- 08.03.2023 Next Calibration Due On :- 07.03.2024 Location of calibration :- In lab

Calibration method No. :- RTS-WI-19 - 09 03 2023 Date of Issue

ULR No. :- CC292723000002017F

2. Description of Item

:- Micropippette ld. No.

Make :- Micropet Sr. No.

:- 100 to 1000 µl Range Resolution

10 µl Model No.

:- ICTC Location

3.Detail of Equipment used for calibration

:- WEIGHING BALANCE

Certificate No. :- 22.10.IH.004 :- RTS Certified By

ID/Sr. No. :- RTS-WBL-08 :- 5.1 g Range

Uncertainty :- ±0.006 mg Calibration Validity :- 27.10.2023

:- Mechanical Calibration Discipline

Group :- Mass and Volume-Volume

4 Calibration Results :-

| Sr.No. | Volume in | Observed mean volume at 27 °C (ref. Temp) | Systematic Error | Random Error | Expanded Uncertainty ± |
|--------|-----------|---|------------------|-----------------|------------------------|
| | μl | þі | μl | μl | ш |
| 1 | 100 | 100.674 | 0.674 | 0.004 | 0.03 |
| 2 | 500 | 502.807 | 2.807 | 0.006 | 1.8 |
| 3 | 1000 | 1004.810 | 4.810 | 0.008 | 1.8 |

Note:

- 1)The reported uncertainty is the expanded uncertainty in measurement obtained by multiplying the standard uncertainty by the coverage factor k=2, which corresponds to a coverage probability of approximately 95% for normal distribution
- 2) Barometric Pressure 950 mbar. Volumes are reported at 20°C.
- 3) This certificate refers only to the particular item submitted for calibration.
- 4) The calibration results reported in the certificate are valid at the time of and under the stated conditions of measurement.
- 5) Calibration point were selected as per customer specifications.
- 6) This certificate shall not be reproduced, except in full unless written permission for the publication of an approved abstract has been obtained from the Technical Manager of "Reliable Technical Services, Pune".

7) The Standard used are traceable to National / International Standard

8)Calibration of volumetric measures done by any ag

Calibrated By V. Salunkil

Calibration Engineer

V. Salunke RF-21, RO

es is meant for scientific and industrial purpose only. Approved By

Technical Manager

SACHIN A. MHASAWADE

