

| | | CALIE | RATIO | N CERTII | FICATE | | | |
|-----------------------------------|------------------|--------------|---------------|------------------|---------------|----------------|---------------|--|
| CERTIFICATE NO: | SBS/CL | 23/00221 | | М | ECHANICAL | P | age No:1 of 1 | |
| Issue Date | | | 13- | 01-2023 | | | | |
| SRF No & Date | | | SR | F/23/00009-0001 | & 12-01-2023 | | | |
| Receipt Date | | | 60.3 | 01-2023 | | | | |
| Calibration Date | | | 12- | 01-2023 | | | | |
| Calibration Due | | | 11- | 11-01-2024 | | | | |
| Customer Name & Ad | iress | | • | | | | | |
| GOVERNMENT PRIM | ARY HEALT | H CENTRE, | | | | | | |
| RAMAPURAM-60320 | 1,MADURAN | THAKAM TA | LUK, CHENGA | LPATTU DISTRI | CT. | | | |
| | 1.73.71.121. | Deta | ils of Device | Under Calibratio | on (DUC) | | | |
| Description : | CENTR | FUGE | Ma | ike & Model | : | LABOTECH 8 | BDI-152 | |
| Range : | 3500 | RPM | Sr. | No | | | | |
| Least Count : | 1 | RPM | Ide | entification No | | 19 | | |
| DUC Condition : Satisfactory | | Lo | Location | | LABORATOR | Y | | |
| | Envi | onmental C | onditions & S | tandard Operati | ng Procedure | | | |
| Environmental Details Temperatu | | ure: 25.8 °C | Relative H | umidity | 50% Rh | | | |
| Calibration Procedure No SBS/CP/N | | ML/04 | Calibration | done at | onsite | | | |
| | | | Reference | Standards Detai | ils | • | | |
| | S.No Description | | | Make/ SI No: | | Certificate No | | |
| S.No Description | - | | Make/ SI N | o: | Certificate N | 0 | Validity | |

| S.No | DEVICE UNDER CALIBRATION | STANDARD INSTRUMENTS | DEVIATION | EXPANDED UNCERTAINTY |
|------|--------------------------|----------------------|-----------|----------------------|
| | RPM | RPM | RPM | % |
| 1 | 1000 | 998.6 | -1.4 | 3.68 |
| 2 | 2000 | 1999.1 | -0.9 | 3.68 |
| 3 | 3000 | 2998.7 | -1.3 | 3.68 |

- 1. This Calibration certificate shall not be reproduced except in full, without written approval of the laboratory.
- 2. The user should determine the suitability of the instrument for its intended use.
- 3. The recalibration interval should be determined on the user requirement.
- 4. The results stated in this certificate relate only to the Item calibrated.
- 5. The indicated uncertainties are expanded uncertainty estimated for a confidence level of approximately 95% for a coverage factor k=2.00.
- 6. Equipment used for Calibration were calibrated & traceable to National & International Standards.



Chief Executive

Authorised Signatory