

				CALIE	BRATION C	ERTII	FICATE			
Certificate No: SBS	S/CL/23/1159	5								Page. No: 1 of 1
Customer Name &	Address									
						SRF No.			SRF/23/00387-0002	
GOVERNMENT UPGRADED PRIMARY HEALTH CENTRE,					SRF Date			20-09-2023		
THADDIKKARANKONAM-629851.					Date of Receipt			20-09-2023		
						Date of Calibration			20-09-2023	
						Due Date for Calibration			19-09-2024	
						Issue Date			21-09-2023	
Details of Unit Und	der Calibrati	on								
Description	MICRO PI	PETTE			Make			THERMO SCIENTIFIC		
Range		10-100μ1				Model			FINNPIPETTE F3	
Resolution		0.2μl				Material			PVC	
Serial Number		PW14222				Operating Range			10-100µl	
ID Number		NA				Condition of UUC			Good	
Cal. At		Mechanical Lab				Instrument Location			LABORATORY	
Environmental Condition Calibration Method Us									Used	
Temperature (°C)		23.6	Humidity (%RH)		54	National / International Standard			ISO 8655-6:2002	
Atmospheric Pressure (mbar)		1006	Water Temperature (°C)		21.6	Cal Procedure No			SBS/CP/ML/08	
Standard Used					•					
SI. No. Desc	ription	ID.No. / Sl. No. Certificate No.		Certificate No.	Make/Model		Trac	eability	Valid till	
1 Electronic Weighing Balance		15112918		VCSPL22/12/2115-01		A&D & GH-252 Nationa		l Standards	09-12-2023	
Z Factor: 1.00319									1.00319	

Result of Calibration in μl										
Sl. No.	Nominal Value	Observed Readings						Systematic Error	Random Error	Measurement Uncertainty (±)
	10.0	9.96	9.95	9.98	9.96	9.97	9.97	-0.03	0.01	0.47
1	10.0	9.98	9.96	9.97	9.98	9.95				
_	50.0	49.86	49.85	49.87	49.86	49.85	49.91	-0.09	0.05	0.47
2	50.0	49.95	49.96	49.97	49.95	49.95				
3	100.0	99.98	99.97	99.98	99.96	99.98	99.96	-0.04	0.01	0.47
	100.0	99.95	99.96	10 00	99.95	99.96				

Remarks

- 1. This Calibration certificate shall not be reproduced except in full, without written approval of the laboratory.
- 2. The user should determine the suitability of the instrument for its intended use.
- 3. The recalibration interval should be determined on the user requirement.
- 4. The results stated in this certificate relate only to the item calibrated.
- 5. Equipment used for Calibration were calibrated & traceable to National & International Standards
- 6.The indicated uncertainties are expanded uncertainty estimated for a confidence level of approximately 95% for a coverage factor k=2.00.
- Calibration Liquid Used: Distilled or Deionized water conforming Grade3 as specified in ISO 3696.

Calibrated By,

(Calibration Engineer) CSIVABALAN



Authorised by:

(Quality Manager/Chief Executive C.SIVABALAN