

				CAL	IBRAT	ION	I CERT	TIFIC	<u> </u>	E		
CERTIFICATE NO: SBS/CL/23/12044						MEDICAL DEVICES					Page	No:1 of 1
Issue Date						29-09-2023						
SRF No & Date					SRF/23/00464-0003 & 28-09-2023							
Receipt Date					28-09-2023							
Calibration Date					28-09-2023							
Calibration Due					27-09-2024							
Custo	mer Name &	Addre	ss									
GOV	ERNMENT P	RIMA	RY HEA	TH CENTRE	Ξ,							
SEME	BANUR-6303	305,SI	VAGANO	SAI DISTRIC	Τ.							
					Details of De	vice U	nder Calibra	tion (DUC)			
Description : SEMI			AUTO ANALYZER			Make & Model			ROBONIK & PRIETEST TOUCH		Н	
Range : MUL		MULTI	П		Sr. No		:		ATCD0450321RBK			
Resolution : MULTI				Identi	fication No	:		NA				
DUC Condition : SATISFAC		ACTORY		Locat	ion	:		LAB				
				Environ	mental Condi	tions	& Calibration	Procedu	re De	etails	1 2 1 1 1 1	
Environmental Details Temperature:25.6°C			25.6°C	Relative Humidity 52% RH			52% RH					
Calibration Procedure No SBS/CP/MD/2			20 Calibration de		one at ONSITE							
					Refere	nce S	tandards De	ails				
S.No Description Make				Make/ SI No:	ake/ SI No:		Certificate No				Validity	
1 Electrical Safety Analyser			Rigel Medical & 44L-1059			M-230809-16-4				10-08-202		

		ELECTRICAL SAFETY			
RESULTS	<u>S</u>				
S.no	SPECIFICATION	MEASURED VALUES	EXPANDED UNCERTAINTY (±)		
1	Insulation Resisitance >20MΩ	Measured values in MΩ	Uncertainty in % (±)		
2	Earth Leakage	97 Measured values in μA	13.92 Uncertainty in % (±)		
3	<5000µAfor B,BF,CF Enclosure Leakage	187 Measured values in µA	9.5		
-	<500µAfor B,BF,CF	227	Uncertainty in % (±) 8.6		

REMARKS


- 1. This Calibration certificate shall not be reproduced except in full, without written approval of the laboratory.
- 2. The user should determine the suitability of the instrument for its intended use.
- 3. The recalibration interval should be determined on the user requirement.
- 4. The results stated in this certificate relate only to the item calibrated.
- 5.The indicated uncertainties are expanded uncertainty estimated for a confidence level of approximately 95% for a coverage factor k=2.00 .
- 6. Equipment used for Calibration were calibrated & traceable to National & International Standards.

 Calibrated By

 Authorised Signatory

(Calibration Engineer) P.PRASANNA





Chief Executive