

			CA	LIBRA	TIO	N C	ERT	<i>IFICATE</i>			
Certific	ate No: SBS/CL/22/07974	ŀ									Page. No: 1 of 1
Custom	er Name & Address										
						5	SRF No.			SRF/22/00182-0027 &	
GOVERNMENT PRIMARY HEALTH CENTRE,						5	SRF Date		18-08-2022		
						ī	Date of Receipt			18-08-2022	
RAMESHWARAM MAIN ROAD, NARIKUDI-626607.							Date of Calibration			20-08-2022	
							Due Date for Calibration			19-08-2023	
							Issue Date			20-08-2022	
Details o	of Unit Under Calibratio	on									
Descript	ion	Micro Pipette					Make			THERMO SCIENTIFIC	
Range		100-1000µl				N	Model			FINNPIPETTE F3	
Resoluti	on	1μl				N	Material			PVC	
Serial Number		QW13939				(	Operating	g Range			
ID Number						(	Condition of UUC			Good	
Cal. At		Mechanical Lab				a I	Instrument Location			LAB	
	Enviro	onmental C	ondition	TEN I			THE REAL PROPERTY.	Calibrati	ion Metho	d Used	
Temperature (°C)		23.9	9 Humidity (%RH)		55	N	National / International Standard		ırd	ISO 8655-6:2002	
Atmospheric Pressure (mbar)		1006	Water Temperature (°C)		21.6	C	Cal Procedure No		SBS/CP/ML/08		
Standard	Used		ME BALL	MARIA	Test of	A	A CONTRACTOR OF THE PARTY OF TH	是空风雨温光	E		
SI. No.	Description	ID.No.	/ SI. No.	C	ertifica	te No.	. Make/Model Trace		eability	Valid till	
1	Electronic Semi Micro Balance	1511	2918	TVCS	PL21/1	12/1587-	-01	A&D & GH-252	Nationa	National Standards 10-12-2022	

Z Factor: 1.00319

Result of Calibration in µl												
SI. No.	Nominal Value		Obs	served Readi	ings	Mean Value	Systemati c Error	Random Error	Measurement Uncertainty (±)			
	100	99.93	99.92	99.93	99.92	99.93	99.87	-0.13	0.06	0.47		
1		99.81	99.82	99.81	99.82	99.81						
2	500	499.94	499.95	499.94	499.95	499.94	499.93	-0.08	0.02	0.47		
		499.91	499.90	499.91	499.90	499.91						
3	1000	999.84	999.85	999.84	999.85	999.84	999.85	-0.15	0.01	0.47		
		999.87	999.86	999.84	999.86	999.87						

## Remarks

- 1. This Calibration certificate shall not be reproduced except in full, without written approval of the laboratory.
- 2. The user should determine the suitability of the instrument for its intended use.
- 3. The recalibration interval should be determined on the user requirement.
- 4. The results stated in this certificate relate only to the item calibrated.
- 5. Equipment used for Calibration were calibrated & traceable to National & International Standards
- 6. The indicated uncertainties are expanded uncertainty estimated for a confidence level of approximately 95% for a coverage factor k=2.00.
- 7. Calibration Liquid Used: Distilled or Deionized water conforming Grade3 as specified in ISO 3696.

Calibrated By,

(Calibration Engineer)
S.LAKSHMANAN MURUGAN

Chennal Control Contro

Authorised by:

(Quality Manager/Chief Executive)