

| | | CALIE | BRAT | TION | CERT | FICATI | <u>E</u> _ | |
|--|-------------|-------------|------------|--------------------------|----------------|---------------|-----------------|---------------|
| CERTIFICATE NO: | SBS/CL/2 | 3/13352 | | | ME | CHANICAL | Pa | age No:1 of 1 |
| Issue Date | | | | 07-10-20 | 23 | | | |
| SRF No & Date SRF/23/00729-0001 & 07-10-2023 | | | | | | | | |
| Receipt Date | | | | 07-10-20 | 23 | | | |
| Calibration Date | | | | 07-10-20 | 23 | | | |
| Calibration Due | | | | 06-10-20 | 24 | | | |
| Customer Name & Addre | ess | | | | | | | |
| GOVERNMENT PRIMA | RY HEALTH | CENTRE, | | | | | | |
| PANJAPATTY-639119, | KARUR DISTI | RICT. | | | | | | |
| | | Deta | ails of D | evice Un | der Calibrat | ion (DUC) | | 1107.55 |
| Description : | CENTRIFL | JGE | | Make & | Model | : | LABOTECH & NA | |
| Range : | 3500 | RPM | | Sr. No : NA | | | | |
| Resolution : | 1 | RPM | | Identification No : 9163 | | | | |
| DUC Condition : | Satisfactor | у | | Location | | : | LAB | |
| | Envi | ronmental C | ondition | ns & Star | dard Opera | ting Procedu | ire Details | |
| Environmental Details | | Temperature | e: 24.3 °C | С | Relative Hur | nidity | 54 % Rh | |
| Calibration Procedure N | lo | SBS/CP/ML/ | /04 | | Calibration of | lone at | ONSITE | |
| | | | Refer | ence Sta | ndards Deta | ails | | |
| S.No Description | | | Make/ S | SI No: | | Certificate N | lo | Validity |
| 1 Digital Tachome | ter | | Lutron 8 | & Q63838 | 0 | JRPM-CCTF | R-A&S-2022-0036 | 03-10-2023 |
| CALIBRATION RESUL | TS | | • | | | | | |

CALIBRATION RESULTS

| S.No | DEVICE UNDER CALIBRATION READINGS | STANDARD INSTRUMENTS | DEVIATION | EXPANDED UNCERTAINTY (±) |
|------|--------------------------------------|----------------------|-----------|--------------------------|
| | RPM | RPM | RPM | % |
| 1 | 1000 | 999.7 | 0.3 | 4.2 |
| 2 | 2000 | 1998 | 2 | 4.2 |
| 3 | 3000 | 2999 | 1 | 4.2 |

REMARKS

- 1. This Calibration certificate shall not be reproduced except in full, without written approval of the laboratory.
- 2. The user should determine the suitability of the instrument for its intended use.
- 3. The recalibration interval should be determined on the user requirement.
- 4. The results stated in this certificate relate only to the item calibrated.
- 5.The indicated uncertainties are expanded uncertainty estimated for a confidence level of approximately 95% for a coverage factor k=2.00.

Authorised Signatory

Chief Executive

6. Equipment used for Calibration were calibrated & traceable to National & International Standards.

Calibrated By

(Calibration Engineer)

K.SATHYAMOORTHY

(Calibration Engineer)

(Calibration Engineer)

(Calibration Engineer)

(Calibration Engineer)

SUNSHINE BIOMEDICAL SOLUTIONS

No:68, First Floor, Poomagal Main Road, Ekkattuthangal, Chennai - 600 032, Tel: 044 - 2225 2087, E-Mail: calibration@sunshinebiomedical.com, Website: www.sunshinebiomedical.com.



| | | | | CAL | BRAT | ΙΟN | I CERT | TIFIC | A | Γ <u>Ε</u> | | |
|-----------------------|--------------|---------|---------|---------------|---------------|--------|---------------|----------|------------|--------------|------|-----------|
| CERT | IFICATE N | O: SBS | CL/23/ | 13353 | | | М | EDICAL | DE\ | /ICES | Page | No:1 of 1 |
| Issue Date 07-10-2023 | | | | | | | | | | | | |
| SRF I | No & Date | | | | | SRF/ | 23/00729-00 | 02 & 07- | 10-2 | 023 | | |
| Recei | pt Date | | | | | 07-10 | -2023 | | | | | |
| Calibr | ation Date | | | | | 07-10 | -2023 | | | | | |
| Calibr | ation Due | | | | | 06-10 | -2024 | | | | | |
| Custo | mer Name & | & Addre | ss | | | | | | | | | |
| GOVE | RNMENT | PRIMA | RY HEA | LTH CENTRE | Ξ, | | | | | | | |
| PANJ | APATTY-6 | 39119,k | (ARUR [| DISTRICT. | | | | | | | | |
| | | | | | Details of De | vice U | nder Calibra | tion (DU | ;) | | | |
| | | | ELECT | RICAL | | | | | | | | |
| Descri | iption | : | SAFET | Y(MICROSCO | PE) | Make | & Model | : | | LABOMED & NA | | |
| Range | • | : | MULTI | | | Sr. No |) | : | | 170901170 | | |
| Resolu | ution | 1 | MULTI | | | Identi | fication No | : | | NA | | |
| DUC (| Condition | : | SATISF | ACTORY | | Locat | ion | : | | LAB | | |
| | | | | Environ | nental Condi | tions | & Calibration | Procedu | re D | etails | | |
| Enviro | nmental Det | ails | | Temperature:2 | 25.6°C | | Relative Hun | nidity | | 52% RH | | |
| Calibra | ation Proced | ure No | | SBS/CP/MD/2 | 9 | | Calibration d | one at | | ONSITE | | |
| | | | | | Refere | ence S | tandards Det | tails | | • | | |
| S.No | Description | 1 | | | Make/ SI No: | | | Certific | ate N | lo | | Validity |
| 1 | | | | | | | | | 10-08-2024 | | | |

ELECTRICAL SAFETY

| P | FS | 111 | TS |
|---|----|-----|----|

| SPECIFICATION | MEASURED VALUES | EXPANDED UNCERTAINTY (±) |
|------------------------|---|--|
| Insulation Resisitance | Measured values in MΩ | Uncertainty in % (±) |
| >20MΩ | 78 | 13.92 |
| Earth Leakage | Measured values in μA | Uncertainty in % (±) |
| <5000µAfor B,BF,CF | 204 | 9.1 |
| Enclosure Leakage | Measured values in μA | Uncertainty in % (±) |
| <500µAfor B,BF,CF | 214 | 8.9 |
| | Insulation Resisitance >20MΩ Earth Leakage <5000μAfor B,BF,CF Enclosure Leakage | Insulation Resisitance Measured values in MΩ >20MΩ 78 Earth Leakage Measured values in μΑ <5000μAfor B,BF,CF |

REMARKS


- 1. This Calibration certificate shall not be reproduced except in full, without written approval of the laboratory.
- 2. The user should determine the suitability of the instrument for its intended use.
- 3. The recalibration interval should be determined on the user requirement.
- 4. The results stated in this certificate relate only to the item calibrated.
- 5. The indicated uncertainties are expanded uncertainty estimated for a confidence level of approximately 95% for a coverage factor k=2.00.
- 6. Equipment used for Calibration were calibrated & traceable to National & International Standards.

Calibrated By

Authorised Signatory

(Calibration Engineer) K.SATHYAMOORTHY





Chief Executive

SUNSHINE BIOMEDICAL SOLUTIONS



| | | | 9 | CALIB | RATION CE | RTIF | <u>ICATE</u> | | | |
|--|---|-----------|----------------------|------------------|---------------------|-------------------------|-----------------|-------------|---------------|------------------|
| Certificat | e No: SBS/CL/23/13456 | | | | | | | | I | Page. No: 1 of 1 |
| Customer | r Name & Address | | | | | | | | | |
| | | | | | | SRF No. | | | SRF/23/00729- | -0003 |
| GOVERN | MENT PRIMARY HEA | LTH CENTI | RE, | | | SRF Date | | | 07-10-2023 | |
| PANJAPATTY-639119,KARUR DISTRICT. | | | | | | Date of Re | eceipt | | 06-10-2023 | |
| | | | | | | Date of Ca | alibration | | 07-10-2023 | |
| | | | | | | Due Date | for Calibration | | 06-10-2024 | |
| | | | | | | Issue Date | 2 | | 07-10-2023 | |
| Details of | f Unit Under Calibration | n | | | | | | | | |
| Description MICRO PIPETTE | | | | | Make | | | P'FACT | | |
| Range | | 10-100µl | | | | Model | | | NA | |
| Resolutio | on | 1µl | | | | Material | | | PVC | |
| Serial Nu | ımber | 243078 | | | | Operating Range | | | 10-100µl | |
| ID Numb | per | NA | | | | Condition | of UUC | | Good | |
| Cal. At | | Mechanica | l Lab | | | Instrument Location LAB | | | | |
| | T | | tal Condition | | | | Calibratio | on Method | l Used | |
| | | | Parties Programme in | 510240020011104 | | N 1 | | - Trictilot | T | |
| Tempera | erature (°C) 23.6 Humidity (%RH) 54 National / International Standard | | | | ISO 8655-6:2002 | | | | | |
| Atmospheric Pressure (mbar) 1006 Water Temperature (°C) 21.6 | | | 21.6 | Cal Procedure No | | | SBS/CP/ML/08 | | | |
| Standard | Used | | | | | | | | | |
| SI. No. | Description | ID.No. | / SI. No. | | Certificate No. | | Make/Model | Trac | ceability | Valid till |
| 1 | Electronic Weighing Balance | 1511 | 2918 | Т | CVCSPL22/12/2115-01 | | A&D & GH-252 | Nationa | al Standards | 09-12-2023 |

Z Factor: 1.00319

| | Result of Calibration in μl | | | | | | | | | | |
|---------|-----------------------------|-------|-------|-------------|--------|-------|---------------|---------------------|-----------------|--------------------------------|--|
| Sl. No. | Nominal Value | | | Observed Re | adings | | Mean Value | Systematic Error | Random Error | Measurement Uncertainty (±) | |
| | | 9.96 | 9.95 | 9.98 | 9.96 | 9.97 | 9.97 | -0.03 | 0.01 | 0.47 | |
| 1 | 1 10 | 9.98 | 9.96 | 9.97 | 9.98 | 9.95 | | | | | |
| | | 49.86 | 49.85 | 49.87 | 49.86 | 49.85 | 49.91 | -0.09 | 0.05 | 0.47 | |
| 2 | 50 | 49.95 | 49.96 | 49.97 | 49.95 | 49.95 | 49.91 | -0.09 | | | |
| | 100 | 99.98 | 99.97 | 99.98 | 99.96 | 99.98 | 99.96 | -0.04 | 0.01 | 0.47 | |
| 3 100 | 99.95 | 99.96 | 99.94 | 99.95 | 99.96 | 33.30 | -0.04 | 0.01 | 3.17 | | |

Remarks

- 1. This Calibration certificate shall not be reproduced except in full, without written approval of the laboratory.
- 2. The user should determine the suitability of the instrument for its intended use.
- 3. The recalibration interval should be determined on the user requirement.
- 4.The results stated in this certificate relate only to the item calibrated.
- 5. Equipment used for Calibration were calibrated & traceable to National & International Standards
- 6. The indicated uncertainties are expanded uncertainty estimated for a confidence level of approximately 95% for a coverage factor k=2.00.

Chennai 600 032

7. Calibration Liquid Used: Distilled or Deionized water conforming Grade3 as specified in ISO 3696.

Balance

(Calibration Engineer) M.RAGUL

Authorised by:

(Quality Manager/Chief Executive)

SUNSHINE BIOMEDICAL SOLUTIONS

No:68, First Floor, Poomagal Main Road, Ekkattuthangal, Chennai - 600 032, Tel: 044 - 2225 2087, E-Mail: calibration@sunshinebiomedical.com, Website: www.sunshinebiomedical.com.



| | | | (| CALIB | RATION CE | RTIF | <u>ICATE</u> | | | |
|-----------------------------------|--|------------|---------------|-------|---------------------|-----------------------------------|-----------------|-----------|-----------------|-------------------|
| Certificat | te No: SBS/CL/23/13355 | | | | | | | | 1 | Page. No : 1 of 1 |
| Custome | r Name & Address | | | | | | | | | |
| | | | | | | SRF No. | | | SRF/23/00729 | -0004 |
| GOVERN | GOVERNMENT PRIMARY HEALTH CENTRE, | | | | | | | | 07-10-2023 | |
| PANJAPATTY-639119,KARUR DISTRICT. | | | | | | Date of Re | eceipt | | 06-10-2023 | |
| | | | | | | Date of Ca | alibration | | 07-10-2023 | |
| | | | | | | Due Date | for Calibration | | 06-10-2024 | |
| | | | | | | Issue Date | 2 | | 07-10-2023 | |
| Details o | f Unit Under Calibration | n | | | | | | | • | |
| Description MICRO PIPETTE | | | | | Make | | | MICROLUX | | |
| Range | | 100-1000µl | | | | Model | | | NA | |
| Resolutio | on | 10µl | | | | Material | | | PVC | |
| Serial Nu | umber | NA | | | | Operating Range | | | 100-1000µl | |
| ID Numl | ber | NA | | | | Condition of UUC | | | Good | |
| Cal. At | | Mechanica | l Lab | | | Instrument Location | | | LAB | |
| | F | nvironmen | tal Condition | n | | | Calibratio | on Method | d Used | |
| Tempera | | 23.6 | Humidity | | 54 | National / International Standard | | | ISO 8655-6:2002 | |
| | Atmospheric Pressure (mbar) 1006 Water Temperature (°C) 21.6 | | | | 21.6 | Cal Procedure No | | | SBS/CP/ML/08 | |
| Standard | | | | | | | | | | |
| SI. No. | Description | ID No. | / SI. No. | | Certificate No. | | Make/Model | Trac | ceability | Valid till |
| 51. No. | Electronic Weighing Balance | | 12918 | 7 | TVCSPL22/12/2115-01 | | A&D & GH-252 | | al Standards | 09-12-2023 |

| | | | 8 | | | | | | | Z Factor: 1.00319 | |
|-----------------------------|------------------|--------|--------|------------|---------|--------|---------------|---------------------|-----------------|--------------------------------|------|
| Result of Calibration in µl | | | | | | | | | | | |
| Sl. No. | Nominal Value | | | Observed R | eadings | | Mean Value | Systematic Error | Random Error | Measurement Uncertainty (±) | |
| 1 | | 99.94 | 99.96 | 99.94 | 99.92 | 99.93 | 99.95 | -0.05 | 0.02 | 0.47 | |
| 1 | 100 | 99.94 | 99.95 | 99.96 | 99.97 | 99.98 | 99.93 | | | | |
| 2 | 500 | 499.85 | 499.86 | 499.87 | 499.89 | 499.86 | 499.87 | 499.87 -0.13 | -0.13 | 0.02 | 0.47 |
| 2 | 500 | 499.86 | 499.87 | 499.89 | 499.85 | 499.89 | | -0.15 | 0.02 | 0.47 | |
| 2 | 1000 | 999.96 | 999.97 | 999.98 | 999.96 | 999.95 | 000.06 | 99.96 -0.04 | 0.01 | 0.47 | |
| 3 10 | 1000 | 999.98 | 999.94 | 999.96 | 999.95 | 999.95 | 777.90 | | | 0.47 | |

Remarks

- 1. This Calibration certificate shall not be reproduced except in full, without written approval of the laboratory.
- 2. The user should determine the suitability of the instrument for its intended use.
- 3. The recalibration interval should be determined on the user requirement.
- 4. The results stated in this certificate relate only to the item calibrated.
- $5.\ Equipment\ used\ for\ Calibration\ were\ calibrated\ \&\ traceable\ to\ National\ \&\ International\ Standards$
- 6. The indicated uncertainties are expanded uncertainty estimated for a confidence level of approximately 95% for a coverage factor k=2.00.
- 7. Calibration Liquid Used: Distilled or Deionized water-conforming Grade3 as specified in ISO 3696.

Calibrated By,

(Calibration Engineer) M.RAGUL Chennai 600 032

Authorised by:

(Quality Manager/Chief Executive)
C.SIVABALAN

SUNSHINE BIOMEDICAL SOLUTIONS

No:68, First Floor, Poomagal Main Road, Ekkattuthangal, Chennai - 600 032, Tel: 044 - 2225 2087, E-Mail: calibration@sunshinebiomedical.com, Website: www.sunshinebiomedical.com.