

		CA	LIBR	ATION	CER	TIFICAT	<u>E</u>		
CERTIFICATE NO: SBS/CL/23/13469						IECHANICAL	P	Page No:1 of 1	
Issue Date				07-10-2	023				
SRF No & Date				SRF/23/00756-0001 & 07-10-2023					
Receipt Date				07-10-2023					
Calibration Date				07-10-2023					
Calibration Due				06-10-2024					
Customer Nam	e & Ad	dress_		554					
GOVERNMENT	PRIMA	RY HEALTH CENTR	E,						
MANDAPAM,RA	AMANA	THAPURAM DISTRIC	T.						
			Details o	f Device Un	der Calibr	ation (DUC)			
Description : CENTRIFUGE				Make & Model		:	B.D INSTRUMENTATION & BDI-152		
Range	:	3500 RPM		Sr. No		:	NA		
Resolution : 1 F		1 RPM		Identification		:	NA		
DUC Condition : Satisfactory				Location		:	LABORATORY		
		Environmer	tal Condit	tions & Star	ndard Ope	rating Procedu	ure Details		
Environmental Details Temperature			ature: 24.	e: 24.3 °C Rela		lumidity	54 % Rh		
Calibration Procedure No SBS/CP/MI			P/ML/04	/04 Calibra		on done at ONSITE			
			Re	eference St	andards De	etails	1		
S.No Descript	.No Description				Make/ SI No:		Certificate No		
1 Digital Tachometer				Lutron & DT-2238		JRPM-CCTR-A&S-2022-0036		03-10-2023	
CALIBRATION	RESUL	TS							

## 3 REMARKS

S.No

1

2

1. This Calibration certificate shall not be reproduced except in full, without written approval of the laboratory.

STANDARD INSTRUMENTS

**RPM** 

999.9

1999.8

2999.7

- The user should determine the suitability of the instrument for its intended use.
- The recalibration interval should be determined on the user requirement.
- 4. The results stated in this certificate relate only to the item calibrated.
- 5. The indicated uncertainties are expanded uncertainty estimated for a confidence level of approximately 95% for a coverage factor k=2.00.
- 6. Equipment used for Calibration were calibrated & traceable to National & International Standards.

Calibrated By

**DEVICE UNDER** 

CALIBRATION READINGS

**RPM** 

1000

2000

3000

(Calibration Engineer)
P.PRASANNA

Chennai 600 032

Authorised Signatory

DEVIATION

**RPM** 

0.1

0.2

0.3

Quality Manager Chief Executive (C.SIVABALAN)

EXPANDED UNCERTAINTY (±)

%

4.2

4.2

4.2