

CAL	IBRATION	I CERT	IFICA	<u>ΓΕ</u>		
CERTIFICATE NO: SBS/CL/23/13517		M	EDICAL DE	/ICES	Page No:1 of 1	
Issue Date	07-1	0-2023				
SRF No & Date	SRF	23/00671-000	03 & 06-10-2	2023		
Receipt Date	06-1	0-2023				
Calibration Date	06-1	0-2023				
Calibration Due	05-1	0-2024				
Customer Name & Address						
GOVERNMENT PRIMARY HEALTH CENTE	RE(KANDAMANAD	Y BLOCK),				
VILLUPURAM-605602, VILLUPURAM DISTR	ICT.					
	Details of Device U	nder Calibrat	ion (DUC)			
Description : SEMI AUTOANALYZER		& Model	:	ROBONIK & PRISTES	ST TOUCH	
Range : MULTI	Sr. N)	: ATCD1670818RBK			
Resolution : MULTI	Identi	fication No	:	NA		
DUC Condition : SATISFACTORY	Locat	Location : LABORATORY				
Environ	mental Conditions	& Calibration	Procedure D	etails		
Environmental Details Temperature	:25.6°C	Relative Humidity 52% RH				
Calibration Procedure No SBS/CP/MD/20		Calibration done at ONSITE				
	Reference S	tandards Deta	ails	•		
S.No Description	Make/ SI No:	Certificate No		Validity		
1 Electrical Safety Analyser	Rigel Medical & 44I	-1059	M-230809-16-4 10-			

ELECTRICAL SAFETY

RESULTS	2		
S.no	SPECIFICATION	MEASURED VALUES	EXPANDED UNCERTAINTY (±)
1	Insulation Resisitance	Measured values in MΩ	Uncertainty in % (±)
	>20MΩ	87	13.92
2	Earth Leakage	Measured values in μA	Uncertainty in % (±)
	<5000µAfor B,BF,CF	202	9.1
3	Enclosure Leakage	Measured values in µA	Uncertainty in % (±)
	<500µAfor B,BF,CF	236	8.5

REMARKS

- 1. This Calibration certificate shall not be reproduced except in full, without written approval of the laboratory.
- 2. The user should determine the suitability of the instrument for its intended use.
- 3. The recalibration interval should be determined on the user requirement.
- 4. The results stated in this certificate relate only to the item calibrated.
- 5. The indicated uncertainties are expanded uncertainty estimated for a confidence level of approximately 95% for a coverage factor k=2.00 .
- 6. Equipment used for Calibration were calibrated & traceable to National & International Standards.

 Calibrated By

 Authorised Signatory

(Calibration Engineer)
M.DINESH



Г	Technical Manager
	C.SHANMUGARAJ

Chief Executive



	CALIBI	RATION (CERTIF	ICATE				
CERTIFICATE NO: SBS/C	/23/13518		ME	CHANICAL	Pag	ge No:1 of 1		
Issue Date		07-10-2	07-10-2023					
SRF No & Date		SRF/23	/00671-0004	& 06-10-2023				
Receipt Date		06-10-2	023					
Calibration Date		06-10-2	023					
Calibration Due		05-10-2	024					
Customer Name & Address								
GOVERNMENT PRIMARY HEAL	TH CENTRE(KA	ANDAMANADY B	LOCK),					
VILLUPURAM-605602,VILLUPUR	AM DISTRICT.							
	Details	s of Device Unde	r Calibration	ı (DUC)				
Description : CENTR	IFUGE	Make &	Model	:	REMI & R-8C			
Range : 5250	RPM	Sr. No	Sr. No		ZEBN-04621			
Least Count : 10	RPM	Identific	Identification No		NA			
DUC Condition : Satisfac	tory	Location	Location : [
Envi	ronmental Con	ditions & Standa	ard Operatin	g Procedure D	Details			
Environmental Details	e: 25.6 °C Relative Hu		midity 57% Rh					
Calibration Procedure No	04 Calibration done at		done at	ONSITE				
		Reference Stand	dards Details					
S.No Description		Make/ SI No:	/ SI No:			Validity		
1 Digital Tachometer	Digital Tachometer LINE SE			75-0034V JRPM-CCTR-A&S-2023-0013 09		09-06-2024		

CALIBRATION RESULTS

S.No	DEVICE UNDER CALIBRATION	STANDARD INSTRUMENTS	DEVIATION	EXPANDED UNCERTAINTY (±)
	RPM	RPM	RPM	%
1	1000	999.7	0.3	4.2
2	2000	1999.7	0.3	4.2
3	3000	2999.6	0.4	4.2

REMARKS

- 1. This Calibration certificate shall not be reproduced except in full, without written approval of the laboratory.
- 2. The user should determine the suitability of the instrument for its intended use.
- 3. The recalibration interval should be determined on the user requirement.
- 4. The results stated in this certificate relate only to the item calibrated.
- 5. The indicated uncertainties are expanded uncertainty estimated for a confidence level of approximately 95% for a coverage factor k=2.00.
- 6. Equipment used for Calibration were calibrated & traceable to National & International Standards.

Calibrated By

(Calibration Engineer)

M.DINESH

Authorised Signatory

Chennai

Chennai

Chennai

Control

Chennai

Control

Chennai

Control

Cont

SUNSHINE BIOMEDICAL SOLUTIONS



				CAL	IBRAT	101	I CERT	TIFIC	A	TE_		
CERT	TIFICATE N	O: SB	S/CL/23/	13519			M	IEDICAL	DE	VICES	Page N	o:1 of 1
Issue	Date					07-10)-2023			•		
SRF	No & Date					SRF	23/00671-00	05 & 06	10-2	2023		
Rece	ipt Date					06-10)-2023					
Calibi	ration Date					06-10)-2023					
Calibi	ration Due					05-10)-2024					
Custo	omer Name 8	& Addr	ess									
GOVI	ERNMENT	PRIMA	RY HEA	LTH CENTR	E(KANDAMA	ANAD'	/ BLOCK),					
				RAM DISTRI			, .					
					Details of De	vice U	nder Calibra	tion (DU	C)			
			ELECT	DICAL SAFET	~			· · · · · ·				
Description : (MICROSCOPE)			Make	& Model			LABOMED & CXL PLUS	S				
Range			MULTI	,		Sr N				130661136	•	
Resol		:	MULTI			Identification No : NA						
DUC (Condition	:	SATISE	ACTORY		Location :			LABORATORY			
					nental Condi			Proced	ıre D			
Enviro	onmental Det	ails		Temperature:			Relative Hun			52% RH		
Calibration Procedure No SBS/CP/MD/29						ONSITE						
						nce S	tandards Det					
S.No	Description	Ü			Make/ SI No			No	\	/alidity		
1	Electrical Sa	fety Ar	alyser		Rigel Medica	I & 44I	-1059					0-08-2024

ELECTRICAL SAFETY

RESULTS

S.no	SPECIFICATION	MEASURED VALUES	EXPANDED UNCERTAINTY (±)
1	Insulation Resisitance	Measured values in $M\Omega$	Uncertainty in % (±)
	>20MΩ	77	13.92
2	Earth Leakage	Measured values in μA	Uncertainty in % (±)
	<5000µAfor B,BF,CF	225	8.7
3	Enclosure Leakage	Measured values in µA	Uncertainty in % (±)
	<500µAfor B,BF,CF	214	8.9

REMARKS

- 1. This Calibration certificate shall not be reproduced except in full, without written approval of the laboratory.
- 2. The user should determine the suitability of the instrument for its intended use.
- 3. The recalibration interval should be determined on the user requirement.
- 4. The results stated in this certificate relate only to the item calibrated.
- 5. The indicated uncertainties are expanded uncertainty estimated for a confidence level of approximately 95% for a coverage factor k=2.00 .
- Equipment used for Calibration were calibrated & traceable to National & International Standards.
 Calibrated By

Calibrated by

Authorised Signatory

(Calibration Engineer) M.DINESH



-	Technical Manager
	C.SHANMUGARAJ

Chief Executive