

CALIBRATION CERTIFICATE											
Certificate No: SBS/CL/23/1385	1								Page. No: 1 of 1		
Customer Name & Address											
GOVERNMENT PRIMARY HEALTH CENTRE,					SRF No.		SRF/23/00826-0005				
SIRUVACHUR-636112,SALEM DISTRICT.					SRF Date		13-09-2023				
					Date of R	eceipt		12-09-2023			
					Date of C	alibration		13-09-2023			
					Due Date	for Calibration	12-09-2024				
					Issue Dat	e	14-09-2023				
Details of Unit Under Calibrati	on										
Description	escription Micro Pipette				Make			HANDY PETTE			
Range	10-100µl				Model			NA			
Resolution	1µl				Material			PVC			
Serial Number NA					Operating Range			10-100µl			
ID Number NA					Condition of UUC			Good			
Cal. At	Mechanical Lab Instrument Location LABORATORY					RY					
Env	ironmental	Condition				Calibrat	ion Meth	od Used			
emperature (°C) 23.9 Hum		Humidity (lumidity (%RH) 55		National / International Standard			ISO 8655-6:2002			
Atmospheric Pressure (mbar)	tmospheric Pressure (mbar) 1006 Water Temperature (°C) 21			21.6	Cal Procedure No			SBS/CP/ML/08			
Standard Used											
SI. No. Description	ID.No.	/ SI. No.		Certificate No.	Make/Model Trac		ceability Valid till				

Z Factor: 1.00319

09-12-2023

National Standards

Result of Calibration in µl										
SI. No.	Nominal Value	Observed Readings						Systemati c Error	Random Error	Measurement Uncertainty (±)
1 10	10	9.94	9.97	9.94	9.96	9.93	9.95	-0.05	0.02	0.47
	9.98	9.95	9.92	9.97	9.96	9.95	-0.05	0.02	0.47	
2 50	49.85	49.86	49.87	49.82	49.83	49.85	-0.15	0.02	0.47	
	49.87	49.85	49.82	49.89	49.87					
3	100	99.94	99.97	99.96	99.95	99.98	99.95	-0.05	0.02	0.47
		99.93	99.95	99.97	99.94	99.95				

TVCSPL22/12/2115-01

A&D & GH-252

Remarks

1

- 1. This Calibration certificate shall not be reproduced except in full, without written approval of the laboratory.
- 2.The user should determine the suitability of the instrument for its intended use.
- 3. The recalibration interval should be determined on the user requirement.
- 4. The results stated in this certificate relate only to the item calibrated.

15112918

- 5. Equipment used for Calibration were calibrated & traceable to National & International Standards
- 6.The indicated uncertainties are expanded uncertainty estimated for a confidence level of approximately 95% for a coverage factor k=2.00.
- 7. Calibration Liquid Used: Distilled or Deionized water conforming Grade3 as specified in ISO 3696.

Calibrated By,

Electronic Weighing

Balance

(Calibration Engineer) M.RAGUL



Authorised by:

Quality Manager/Citief Executive)