

				CAL	IBRA1	ΓΙΟΙ	V CERT	TIFIC	A	<u>E</u>		
CERTIFICATE NO: SBS/CL/23/12885					MEDICAL DEVICES					Page	No:1 of 1	
Issue Date						06-10-2023						
SRF No & Date						SRF/23/00638-0001 & 05-10-2023						
Receipt Date						05-10-2023						
Calibration Date						05-10-2023						
Calibration Due						04-10-2024						
	omer Name											
				LTH CENTRI								
SILLA	AMARATHU	PATTI-	625521,	THENI DISTF	RICT.							
					Details of D	evice	Under Calibra	ation (DU	C)			
Description SE		SEMI A	SEMI AUTO ANALYZER			Make & Model			ALPHA & CHEM-100			
Range MULTI				Sr. No	o			03363-0017-000002				
Resolution MULTI			Identi	fication No			NA					
DUC Condition SATISFACTORY			Location		LABORATORY							
	100 Z			Environ	mental Con	ditions	& Calibration	n Proced	ure D			
Environmental Details Tempera			Temperature:	e:25.6 ° C		Relative Humidity		52% RH				
Calibration Procedure No SE			SBS/CP/MD/20		Calibration done at ON		ONSITE					
					Refe	rence	Standards De					
S.No	S.No Description Make/ SI			Make/ SI No	lo:		Certificate No				Validity	
1 Electrical Safety Analyser Rig			Rigel Medical & 44L-1059		M-230809-16-4				10-08-2024			

ELECTRICAL SAFETY

RESULTS

RESULIS		MEAGURED VALUES	EXPANDED UNCERTAINTY (±)	
S.no	SPECIFICATION	MEASURED VALUES	EXPANDED UNCERTAINTT (±)	
1	Insulation Resisitance	Measured values in MΩ	Uncertainty in % (±)	
	>20ΜΩ	79	13.92	
2	Earth Leakage	Measured values in μA	Uncertainty in % (±)	
-	<5000µAfor B,BF,CF	209	7.3	
3	Enclosure Leakage	Measured values in μA	Uncertainty in % (±) 7.2	
	<500µAfor B,BF,CF	229		

REMARKS

- 1. This Calibration certificate shall not be reproduced except in full, without written approval of the laboratory.
- 2. The user should determine the suitability of the instrument for its intended use.
- 3. The recalibration interval should be determined on the user requirement.
- 4. The results stated in this certificate relate only to the item calibrated.
- 5. The indicated uncertainties are expanded uncertainty estimated for a confidence level of approximately 95% for a coverage factor k=2.00
- 6. Equipment used for Calibration were calibrated & traceable to National & International Standards.

Calibrated By

Authorised Signatory





Technical Manager
C.SHANMUGARAJ

Chief Executive