

				CAL	IBRAT	101	V CERT	TIFIC/	47	<u>E</u>		
CERT	IFICATE N	O: SB	S/CL/23/	12889			M	DICAL D	EVI	CES	Page	No:1 of 1
Issue	Date					07-10	)-2023			•		
SRF I	No & Date					SRF/	23/00640-000	01 & 06-10	)-20	23		
Recei	pt Date					06-10	0-2023					
Calibr	ation Date					06-10	0-2023					
Calibr	ation Due					05-10	0-2024					
Custo	mer Name	& Ad	dress									
GOVE	RNMENT	PRIMA	RY HEA	LTH CENTR	E,							
KADA	MALAIKUN	NDU-62	25579,TH	ENI DISTRIC	T.							
					Details of De	evice l	Jnder Calibra	tion (DUC)				
Descri	ption	:	SEMI A	UTO ANALYZ	ER	Make & Model : ROBONIK & PRIETEST TOUCH						
Range	!	:	MULTI			Sr. No : ATCD3641220RE			ATCD3641220RBK	RBK		
Resolu	ution	:	MULTI			Identification No : NA						
DUC (	Condition	:	SATISF	ACTORY		Location : LABORATORY						
				Environ	mental Cond	itions	& Calibration	Procedure	e De	tails		
Enviro	nmental Det	ails		Temperature:2	25.6 ° C		Relative Hum	idity		52% RH		
Calibra	ation Proced	ure No		SBS/CP/MD/2	0		Calibration do	ne at		ONSITE		
					Refer	ence S	Standards Det	ails				
S.No	Description	1			Make/ SI No:		Certificate N		No	10		Validity
1				Rigel Medica	l & 44L	44L-1059 M-230809-16-4			10-08-2024			

S.no	SPECIFICATION	MEASURED VALUES	EXPANDED UNCERTAINTY (±)
1	Insulation Resisitance	Measured values in $M\Omega$	Uncertainty in % (±)
	>20MΩ	97	13.92
2	Earth Leakage	Measured values in μA	Uncertainty in % ( ±)
	<5000µAfor B,BF,CF	125	8.0
3	Enclosure Leakage	Measured values in μA	Uncertainty in % (±)
	<500µAfor B,BF,CF	235	7.2

**ELECTRICAL SAFETY** 

#### **REMARKS**

RESULTS

- 1. This Calibration certificate shall not be reproduced except in full, without written approval of the laboratory.
- 2. The user should determine the suitability of the instrument for its intended use.
- 3. The recalibration interval should be determined on the user requirement.
- 4. The results stated in this certificate relate only to the item calibrated.
- 5. The indicated uncertainties are expanded uncertainty estimated for a confidence level of approximately 95% for a coverage factor k=2.00 .
- 6. Equipment used for Calibration were calibrated & traceable to National & International Standards.

(Calibration Engineer) P.PRASANNA

Calibrated By



Technical Manager
C.SHANMUGARAJ

001

Chief Executive

**Authorised Signatory** 



CALIBRATION CERTIFICATE								
CERTIFICATE NO: SBS/CL/	23/12890		ME	CHANICAL	Pag	je No:1 of 1		
Issue Date		07-10-20	)23					
SRF No & Date		SRF/23/	00640-0002 8	& 06-10-2023				
Receipt Date		06-10-20	)23					
Calibration Date		06-10-20	)23					
Calibration Due		05-10-20	)24					
Customer Name & Address								
GOVERNMENT PRIMARY HEALT	H CENTRE,							
KADAMALAIKUNDU-625579,THEN	I DISTRICT.							
	Details of	Device Un	der Calibrati	on (DUC)				
Description : CENTRI	FUGE	Make &	Model	:	M.C.DALAL&CO &	NA		
Range : 350	0 RPM	Sr. No		:	MCD-419			
Resolution :	1 RPM	Identifica	ation No	:	NA			
DUC Condition : Satisfact	ory	Location		:	LABORATORY			
En	vironmental Condit	ions & Star	ndard Opera	ting Procedur	e Details			
Environmental Details	Temperature: 24.3	24.3 °C Relative Hu		midity 54 % Rh				
Calibration Procedure No	SBS/CP/ML/04	04 Calibration d		done at ONSITE				
	Re	ference Sta	ndards Deta	ails				
S.No Description	Make	Make/ SI No:		Certificate No		Validity		
1 Digital Tachometer	Lutro	n & DT-223	8	JRPM-CCTR-A	&S-2022-0036	03-10-2023		

### **CALIBRATION RESULTS**

S.No	DEVICE UNDER CALIBRATION READINGS	STANDARD INSTRUMENTS	DEVIATION	EXPANDED UNCERTAINTY (±)
	RPM	RPM	RPM	%
1	1000	999.9	0.1	4.2
2	2000	1998	2	4.2
3	3000	2999	1	4.2

## **REMARKS**

- 1. This Calibration certificate shall not be reproduced except in full, without written approval of the laboratory.
- 2. The user should determine the suitability of the instrument for its intended use.
- 3. The recalibration interval should be determined on the user requirement.
- 4. The results stated in this certificate relate only to the item calibrated.
- 5. The indicated uncertainties are expanded uncertainty estimated for a confidence level of approximately 95% for a coverage factor k=2.00.
- 6. Equipment used for Calibration were calibrated & traceable to National & International Standards.

Calibrated By

(Calibration Engineer)

P.PRASANNA

Authorised Signatory

Chennai

Ch

# SUNSHINE BIOMEDICAL SOLUTIONS



				CAL	IBRAT	ΓΙΟ	N CER	TIF	IC/	\TE	
CERTIFICATE	N	D: SB	S/CL/23/	12891			М	EDIC	AL DE	/ICES	Page No:1 of 1
Issue Date						07-10	0-2023			•	
SRF No & Dat	e					SRF/	23/00640-00	003 &	06-10-	2023	
Receipt Date						06-10	0-2023				
Calibration Da	ate					06-10	0-2023				
Calibration Di	Je					05-10	0-2024				
<b>Customer Na</b>	me	& Add	ress								
GOVERNMEN	IT F	PRIMA	RY HEA	ALTH CENTR	E,						
KADAMALAIK	UN	DU-62	25579,T⊢	IENI DISTRIC	CT.						
					Details of D	evice	Under Calib	ration	(DUC)		
			ELECT	RICAL SAFET	Υ						
Description		:	(MICRO	OSCOPE)		Make	& Model		:	LABOMED & VISION 20	00
Range		:	MULTI			Sr. No	)		:	CM/L943785	
Resolution		:	MULTI			Identi	fication No		:	NA	
<b>DUC</b> Condition		:	SATISF	ACTORY		Location : LABORATORY					
				Enviro	nmental Con	ditions	& Calibration	on Pro	cedure	Details	
Environmental I	Deta	ils		Temperature:2	25.6°C		Relative Humidity 52% R		52% RH		
Calibration Prod	edu	ire No		SBS/CP/MD/2	9		Calibration of	lone at		ONSITE	
					Refe	rence	Standards D	etails			
S.No Descript	ion				Make/ SI No:	: Certif		icate N	Validity		
1 Electrica	Electrical Safety Analyser Rig			Rigel Medica	al & 44L-1059		M-230809-16-4			10-08-2024	

# ELECTRICAL SAFETY

### RESULTS

S.no	SPECIFICATION	MEASURED VALUES	EXPANDED UNCERTAINTY (±)
1	Insulation Resisitance	Measured values in MΩ	Uncertainty in % (±)
	>20MΩ	97	13.92
2	Earth Leakage	Measured values in μA	Uncertainty in % (±)
	<5000µAfor B,BF,CF	125	12.3
3	Enclosure Leakage	Measured values in μA	Uncertainty in % (±)
	<500µAfor B,BF,CF	229	8.6

### **REMARKS**

- 1. This Calibration certificate shall not be reproduced except in full, without written approval of the laboratory.
- 2. The user should determine the suitability of the instrument for its intended use.
- 3. The recalibration interval should be determined on the user requirement.
- 4. The results stated in this certificate relate only to the item calibrated.
- 5. The indicated uncertainties are expanded uncertainty estimated for a confidence level of approximately 95% for a coverage factor k=2.00 .
- 6. Equipment used for Calibration were calibrated & traceable to National & International Standards.

Calibrated By Authorised Signatory

(Calibration Engineer)
P.PRASANNA



Chief Executive





				CAL	.IBRA	ΤΙΟ	N CER	RTIF	-IC	<u>ATE</u>	
CERT	IFICATE N	O: SB	S/CL/23/	12892			M	EDIC/	AL DI	EVICES	Page No:1 of 1
Issue	Date					07-10	)-2023				
SRF N	No & Date					SRF	23/00640-0	004 &	06-10	0-2023	
Recei	pt Date					06-10	)-2023				
Calibra	ation Date					06-10	0-2023				
Calibra	ation Due					05-10	)-2024				
Custo	mer Name	& Add	dress								
GOVE	RNMENT	PRIMA	RY HEA	LTH CENTR	E,						
KADA	MALAIKUI	NDU-62	25579,TH	ENI DISTRIC	T.						
					Details of D	evice	Under Calib	ration	(DUC	)	
Descri	otion	:	HEAMO	OTOLOGY AN	ALYZER	Make	& Model		:	SYSMEX & XP-100	
Range		:	MULTI			Sr. N	)		:	B5903	
Resolu	ition	:	MULTI			Identi	fication No			NA	
DUC C	ondition	:	SATISF	ACTORY		Locat	ion		:	LABORATORY	
				Enviro	nmental Con	ditions	& Calibration	on Pro	cedu	re Details	
Enviror	nmental Det	ails		Temperature:2	25.6°C	Relative Humidity 52% RH		52% RH			
Calibration Procedure No SBS/CP/MD/24			Calibration done at ONSITE								
					Refe	rence	Standards D	etails		•	
S.No	Descriptior	1			Make/ SI No:	):		Certificate No		No	Validity
1 Electrical Safety Analyser Rigel Medic				I & 44L-1059 M-230809-16-4		6.4	10-08-2024				

## **ELECTRICAL SAFETY**

#### **RESULTS**

S.no	SPECIFICATION	MEASURED VALUES	EXPANDED UNCERTAINTY (±)
1	Insulation Resisitance	Measured values in MΩ	Uncertainty in % (±)
	>20MΩ	88	13.92
2	Earth Leakage	Measured values in μA	Uncertainty in % (±)
	<5000µAfor B,BF,CF	175	9.9
3	Enclosure Leakage	Measured values in μA	Uncertainty in % (±)
	<500µAfor B,BF,CF	235	8.5

#### **REMARKS**

- 1. This Calibration certificate shall not be reproduced except in full, without written approval of the laboratory.
- 2. The user should determine the suitability of the instrument for its intended use.
- 3. The recalibration interval should be determined on the user requirement.
- 4. The results stated in this certificate relate only to the item calibrated.
- $5. The \ indicated \ uncertainties \ are \ expanded \ uncertainty \ estimated \ for \ a \ confidence \ level \ of \ approximately \\ 95\% \ for \ a \ coverage \ factor \ k=2.00 \ .$
- 6. Equipment used for Calibration were calibrated & traceable to National & International Standards.

Calibrated By

Authorised Signatory

(Calibration Engineer) P.PRASANNA



Technical Manager
C.SHANMUGARAJ