

				CALIBI	RATI	ON	I CERT	<u>IFIC</u>	<u> </u>	<u>E</u>		
SERTIFICATE NO: SBS/CL/23/11793						MECHANICAL					Page No:	1 of 1
Issue Date						2	27-09-2023					
SRF No & Date						1	SRF/23/0041	7-0001	& 26-0	9-2023		
						1:	26-09-2023					
Receipt							26-09-2023					
	tion Date					1	25-09-2024					
	tion Due						25-09-2024					
	ner Name				D.F.							
				EALTH CENT	RE,							
CHEYL	JR-641654	,TIRUF	PUR DISTRI	CT.								
				Detai	ls of De	vice l	Jnder Calibra	ation (D	UC)			
Descri	ntion		CENTRIFL	JGE		Make	& Model	:		B.D INSTRUM	MENTATION & E	3DI-152
				3000 RPM	Sr. No			:		NA		
Range				10 RPM	Identification No			:		NA		
Resolu		:	0 11 1 - 1			Loca				LABORATOR	Υ	
DUC C	Condition		Satisfactor	onmental Co	ndition			rating F	roce	dure Details		
			Envir				Relative Hur			52%Rh		
	nmental D			Temperature			Calibration d	maty				
Calibra	ation Proce	dure N	0	SBS/CP/ML/						ONOTIL		
					Refere	ence	Standards D					Validity
S.No	Descripti	on			Make/ SI No:		c: Certificate		cate N	ate No		Validity
1	Digital Tachometer				LINE SEIKI / 175-0034V		JRPM-CCTR-A&S-2023-0013		3	09-06-202		

#### CALIBRATION RESULTS

S.No	DEVICE UNDER CALIBRATION	STANDARD INSTRUMENTS	DEVIATION	EXPANDED UNCERTAINTY	
		RPM	RPM	%	
	RPM		1.0	4.2	
1	1000	999.0	1.0	4.2	
2	2000	1999.6	0.4	4.2	
-		2999.5	0.5	4.2	
3	3000	2333.0			

## REMARKS

- 1. This Calibration certificate shall not be reproduced except in full, without written approval of the laboratory.
- 2. The user should determine the suitability of the instrument for its intended use.
- 3. The recalibration interval should be determined on the user requirement.
- 4. The results stated in this certificate relate only to the item calibrated.
- 5. The indicated uncertainties are expanded uncertainty estimated for a confidence level of approximately 95% for a coverage factor k=2.00
- 6. Equipment used for Calibration were calibrated & traceable to National & International Standards.

Calibrated By

(Calibration Engineer) K.SATHYAMOORTHY



**Authorised Signatory** (Chief Executive) (C.SIVABALAN)

## SUNSHINE BIOMEDICAL SOLUTIONS



				CAL	IBRAT	101	I CER	TIFI	CA	TE_	
CERT	TIFICATE N	IO: SBS	S/CL/23/	11794			N	/IEDIC/	L DE	VICES	Page No:1 of 1
Issue	Date					27-09	9-2023				
SRF I	No & Date					SRF/	23/00417-00	002 & 2	6-09-	2023	
Recei	ipt Date					26-09	9-2023				
Calibr	ration Date					26-09	9-2023				
Calibi	ration Due					25-09	9-2024				
Custo	mer Name	& Addre	ess_								
GOV	ERNMENT	URBAN	PRIMA	RY HEALTH	CENTRE,						
CHE	/UR-64165	4,TIRUI	PPUR D	ISTRICT.							
					Details of De	vice U	nder Calibra	ation (D	UC)		
Descr	iption		ELECT	RICAL Y(MICROSCO	PE)	Make	& Model		:	UNILAB & JP-MIA	
Range	Э	:	MULTI			Sr. No			:	NA	
Resol	ution	;	MULTI			Identi	fication No		*	NA	
DUC (	Condition	:	SATISI	FACTORY		Locat	ion		:	LABORATORY	
				Environi	mental Condi	tions	& Calibration	n Proce	dure	Details	
Enviro	onmental De	tails		Temperature:	25.6°C	Relative Hun		midity	midity 52% RH		
Calibration Procedure No SBS/CP/MD/29				Calibration done at ONSITE							
					Refere	nce S	tandards De	tails			
S.No	Description	n			Make/ SI No	);		Certificate No			Validity
1	Electrical S	afety An	alyser		Rigel Medica	1 & 441	& 44L-1059 M-230809-16-4		10-08-20		

#### **ELECTRICAL SAFETY**

#### RESULTS

ILLOOLIC			
S.no	SPECIFICATION	MEASURED VALUES	EXPANDED UNCERTAINTY (±)
1	Insulation Resisitance	Measured values in $M\Omega$	Uncertainty in % (±)
	>20MΩ	91	13.92
2	Earth Leakage	Measured values in µA	Uncertainty in % (±)
	<5000µAfor B,BF,CF	195	9.3
3	Enclosure Leakage	Measured values in μA	Uncertainty in % (±)
	<500µAfor B,BF,CF	237	8.5

#### REMARKS

- 1. This Calibration certificate shall not be reproduced except in full, without written approval of the laboratory.
- 2. The user should determine the suitability of the instrument for its intended use.
- 3. The recalibration interval should be determined on the user requirement.
- 4. The results stated in this certificate relate only to the item calibrated.
- 5. The indicated uncertainties are expanded uncertainty estimated for a confidence level of approximately 95% for a coverage factor k=2.00.
- 6. Equipment used for Calibration were calibrated & traceable to National & International Standards. **Authorised Signatory**

Calibrated By

Technical Manager

(C.SHANMUGARAJ)

Chief Executive

(Calibration Engineer) K.SATHYAMOORTHY





			0	CAL	IBRAT	101	CER	TIFICA	ATE	
CER	TIFICATE N	O: SBS	/CL/23/	11795			N	IEDICAL D	EVICES	Page No:1 o
Issue Date						27-09	9-2023			
SRF	No & Date					SRF	23/00417-00	003 & 26-09	9-2023	
Rece	ipt Date					26-09	9-2023			
Calib	ration Date					26-09	9-2023			
Calib	ration Due					25-09	9-2024			
Custo	omer Name	& Addre	<u>ss</u>			122700000000000000000000000000000000000				
GOV	ERNMENT	URBAN	PRIMA	RY HEALTH	CENTRE,					
CHE	YUR-64165	4,TIRUF	PPUR D	STRICT.						
					Details of De	evice U	nder Calibra	tion (DUC)		
Descr	ription		SEMI A	UTO ANALY	ZER	Make & Model : ROBONIK & PF		ROBONIK & PRIETES	T TOUCH	
Range	Э		MULTI			Sr. No		1	ATCD0900519RBK	
Resol	ution		MULTI			Identification No		1	NA	
DUC (	Condition	1	SATISE	ACTORY		Locat	ion		LABORATORY	
				Environ	mental Cond	itions	& Calibration	Procedure	Details	
Enviro	onmental De	tails		Temperature	:25.6°C	Relative Hum		midity	52% RH	
Calibration Procedure No SBS/CP/MD/20				Calibration done at ONSITE		ONSITE				
					Refer	ence S	tandards De	tails		
S.No	Description	1			Make/ SI No	o:		Certificate No		Validit
1 Electrical Safety Analyser Rigel Medica				al & 441	I & 44L-1059 M-230809-		1-16-4	10-08-2		

### ELECTRICAL SAFETY

# RESULTS

S.no	SPECIFICATION	MEASURED VALUES	EXPANDED UNCERTAINTY (±)
1	Insulation Resisitance	Measured values in $M\Omega$	Uncertainty in % (±)
	>20MΩ	94	13.92
2	Earth Leakage	Measured values in µA	Uncertainty in % (±)
	<5000µAfor B,BF,CF	161	10.4
3	Enclosure Leakage	Measured values in µA	Uncertainty in % (±)
	<500µAfor B,BF,CF	216	8.8

## REMARKS

- 1. This Calibration certificate shall not be reproduced except in full, without written approval of the laboratory.
- 2. The user should determine the suitability of the instrument for its intended use.
- 3. The recalibration interval should be determined on the user requirement.
- 4. The results stated in this certificate relate only to the item calibrated.
- 5. The indicated uncertainties are expanded uncertainty estimated for a confidence level of approximately 95% for a coverage factor k=2.00.
- 6. Equipment used for Calibration were calibrated & traceable to National & International Standards.

Calibrated By

Authorised Signatory

(Calibration Engineer) K.SATHYAMOORTHY



Technical Manager	
(C.SHANMUGARAJ)	_

Chief Executive