

| | | | CALIE | BRATIO | N CER | TIFICA | <u>TE</u> | | | |
|-----------------------------|--------------------|------------|-------------------|--------------------------------|---------------------|-------------------------|---------------|--------------|--------|--|
| CERTIFICA | TE NO: | SBS/CL/ | 23/14186 | <u> </u> | | MECHANIC | CAL | Page No:1 of | 1 | |
| Issue Date | | | | 12-10-20 | 023 | _ | | | | |
| SRF No & Date | | | SRF/23/ | SRF/23/00864-0002 & 11-10-2023 | | | | | | |
| Receipt Date | | | | 11-10-20 | 11-10-2023 | | | | | |
| Calibration Date | | | | 11-10-20 | 11-10-2023 | | | | | |
| Calibration Due | | | | 10-10-20 | 10-10-2024 | | | | | |
| Customer N | lame & Add | ress | | | | | | | | |
| GOVERNM | ENT PRIMA | RY HEALTH | I CENTRE, | | | | | | , | |
| NAGAMAN | GALAM-6351 | 113,KRISHI | NAGIRI DIS | TRICT. | | | | | | |
| | | | Det | ails of Device | Under Calib | ration (DUC) |) | | | |
| Description | : | CENTRI | FUGE | Make & | Model | : | MICROSIL & N | MK-10 | | |
| Range | : | 3500 | RPM | Sr. No | | : | NA | | | |
| Resolution | : | 1 | RPM | Identific | ation No | : | NA | | | |
| DUC Condit | ion : | Satisfact | ory | Location | 1 | : | LABORATOR | Υ | | |
| _ | | Envir | onmental C | Conditions & S | tandard Ope | erating Proc | edure Details | | | |
| Environmental Details Tem | | Temperatur | mperature: 25.3°C | | Relative Humidity | | | | | |
| Calibration Procedure No SI | | | SBS/CP/ML/04 | | Calibration done at | | ONSITE | | | |
| | | | | Reference | Standards D | etails | | <u> </u> | | |
| S.No Desc | .No Description | | | Make/ SI No: | Make/ SI No: | | No | Vali | lidity | |
| 1 Digit | Digital Tachometer | | | LINE SEIKI / 175-0034V | | JRPM-CCTR-A&S-2023-0013 | | 3 09-06- | -2024 | |

CALIBRATION RESULTS

| S.No | DEVICE UNDER CALIBRATION | STANDARD INSTRUMENTS | DEVIATION | EXPANDED UNCERTAINTY | |
|------|--------------------------|-------------------------|-----------|----------------------|--|
| | RPM | RPM | RPM | % | |
| 1 | 1000 | 998.8 | 1.2 | 4.2 | |
| 2 | 2000 | 1999.6 | 0.4 | 4.2 | |
| 3 | 3500 | 3499.6 | 0.4 | 4.2 | |

REMARKS

- 1. This Calibration certificate shall not be reproduced except in full, without written approval of the laboratory.
- $2. The \ user \ should \ determine \ the \ suitability \ of \ the \ instrument \ for \ its \ intended \ use.$
- 3. The recalibration interval should be determined on the user requirement.
- ${\bf 4. The\ results\ stated\ in\ this\ certificate\ relate\ only\ to\ the\ item\ calibrated.}$
- 5. The indicated uncertainties are expanded uncertainty estimated for a confidence level of approximately 95% for a coverage factor k=2.00.
- 6. Equipment used for Calibration were calibrated & traceable to National & International Standards.

Calibrated By

(Calibration Engineer)

M.DINESH



Authorised Signatory

(Cuality Manager) (Chief Executive)

(C.SIVABALAN)