

			<u>C/</u>	LIBR	<u>ATION</u>	<u>I CERTI</u>	<u>FICATE</u>				
Certificate No	: SBS/CL/23/14188									Page. No : 1 of 1	
Customer Nar	ne & Address				_						
						SRF No.			SRF/23/00864	-0004	
GOVERNMENT PRIMARY HEALTH CENTRE,						SRF Date		11-10-2023			
NAGAMANGALAM-635113,KRISHNAGIRI DISTRICT.					Date of R	eceipt	10-10-2023				
						Date of C	alibration	11-10-2023			
					Due Date	Due Date for Calibration			10-10-2024		
					Issue Dat	Issue Date			12-10-2023		
Details of Uni	it Under Calibratio	n									
Description		MICRO PIPETTE				Make	Make			MICROLUX	
Range		5-50µl				Model	Model			NA	
Resolution		1μl				Material	Material			PVC	
Serial Number		NA				Operating	g Range	10-50μ1			
ID Number		NA				Condition	Condition of UUC			Good	
Cal. At		Mechanical Lab				Instrume	Instrument Location			LABORATORY	
	Env	ironmenta	ıl Condition		-		Calibrat	ion Metho	d Used		
Temperature (°C)		23.9	Humidity (%RH)		55	National	National / International Standard		ISO 8655-6:2002		
Atmospheric Pressure (mbar)		1006	Water Temperature (°C)		21.6	Cal Proce	Cal Procedure No		SBS/CP/ML/08		
Standard Use		<u></u>				<u> </u>					
SI. No.	Description	ID.No	o. / SI. No.	Certificate N		No.	Make/Model Tr		eability	Valid till	
1 Ele	ectronic Weighing Balance	15112918		TV	TVCSPL22/12/2115-01		A&D & GH-252 Nation		al Standards	09-12-2023	
					-				Z Factor:	1.00319	

Result of Calibration in μl											
Sl. No.	Nominal Value		OI	served Read	lings		Mean Value	Systematic Error	Random Error	Measurement Uncertainty (±)	
1	10	9.96	9.97	9.96	9.97	9.98	9.95	-0.05	0.02	0.47	
		9.95	9.94	9.92	9.93	9.92					
2	30	29.85	29.86	29.87	29.85	29.84	29.84	-0.16	0.02	0.47	
		29.82	29.83	29,82	29.81	29.82					
3	50	49.99	49.98	49.97	49.98	49.98	49.86	-0.14	0.32	0.47	
		49.92	49.91	49.93	49.94	48.96					

Remarks

- $1. This\ Calibration\ certificate\ shall\ not\ be\ reproduced\ except\ in\ full,\ without\ written\ approval\ of\ the\ laboratory.$
- 2. The user should determine the suitability of the instrument for its intended use.
- 3. The recalibration interval should be determined on the user requirement.
- 4. The results stated in this certificate relate only to the item calibrated.
- $5.\ Equipment\ used\ for\ Calibration\ were\ calibrated\ \&\ traceable\ to\ National\ \&\ International\ Standards$
- 6.The indicated uncertainties are expanded uncertainty estimated for a confidence level of approximately 95% for a coverage factor k=2.00.
- 7. Calibration Liquid Used: Distilled or Deionization Liq

Calibrated By,

(Calibration Engineer) M.RAGUL

Authorised by:

Quality Manager/Chief Executive) C.SIVABALAN

SUNSHINE BIOMEDICAL SOLUTIONS