

CALIE	BRATION CERTIFICATE	
Certificate No: SBS/CL/23/12728		Page. No : 1 of 1
Customer Name & Address		
	SRF No.	SRF/23/00590-0001
GOVERNMENT PRIMARY HEALTH CENTRE,	SRF Date	03-10-2023
VEMBI-605203, VILLUPURAM DISTRICT.	Date of Receipt	03-10-2023
	Date of Calibration	03-10-2023
	Due Date for Calibration	02-10-2024
	Issue Date	04-10-2023
Details of Unit Under Calibration		

CALIDDATION CEDTIEICATE

Description	MICRO PIPETTE	Make	THERMO SCIENTIFIC			
Range	البر100-10	Model	FINNPIPETTE F3			
Resolution	ابر0.2	Material	PVC			
Serial Number	RW09041	Operating Range	10-100μΙ			
ID Number	NA	Condition of UUC	Good			

Environmental Condition				Calibration Method Used				
Temperature (°C) 23.2		Humidity (%RH)	53	National / International Standard	ISO 8655-6:2002			
Atmospheric Pressure (mbar) 1006		Water Temperature (°C)	21.6	Cal Procedure No	SBS/CP/ML/08			

Instrument Location

Standard Used

Cal. At

SI. No.	Description	ID.No. / SI. No.	Certificate No.	Make/Model	Traceability	Valid till
1	Electronic Weighing Balance	15112918	TVCSPL22/12/2115-01	A&D & GH-252	National Standards	09-12-2023

Z Factor: 1.00319

LABORATORY

	Result of Calibration in μl									
SI. No.	Nominal Value	Observed Readings					Mean Value	Systematic Error	Random Error	Measurement Uncertainty (±)
1	100	9.87	9.86	9.88	9.88	9.88		-0.13	0.01	0.47
•	10.0	9.88	9.88	9.87	9.86	9.87	9.87			
2	2 50.0	49.74	49.76	49.78	49.74	49.76	49.76	-0.24	0.02	0.47
4	30.0	49.78	49.74	49.78	49.78	49.78				
3	3 100.0	99.84	99.86	99.87	99.87	99.88	00.07	-0.13	0.01	0.47
3 100.0	100.0	99.87	99.88	99.86	99.87	99.88	99.87			

Remarks

- This Calibration certificate shall not be reproduced except in full, without written approval of the laboratory.
- 2. The user should determine the suitability of the instrument for its intended use.
- 3. The recalibration interval should be determined on the user requirement.

Mechanical Lab

- 4. The results stated in this certificate relate only to the item calibrated.
- 5. Equipment used for Calibration were calibrated & traceable to National & International Standards
- 6.The indicated uncertainties are expanded uncertainty estimated for a confidence level of approximately 95% for a coverage factor k=2.00.
- 7. Calibration Liquid Used: Distilled or Deionized water conforming Grade3 as specified in ISO 3696.

Calibrated By,

(Calibration Engineer)

M.ADHIBAN

Chennai 3

Authorised by:

Quality Marager Chaef Executive) CSIVABALAN