

				CAL	IBRAT	101	V CERT	TIFICA	TE		
CERTIFICATE NO: SBS/CL/23/12889						ME	DICAL DE	VICES	Page	No:1 of 1	
Issue Date				07-10	0-2023						
SRF I	No & Date					SRF/	23/00640-000	01 & 06-10-	2023		
Recei	pt Date					06-10	0-2023				
Calibr	ation Date					06-10	0-2023				
Calibr	ation Due					05-10	0-2024				
Custo	omer Name	& Add	dress								
GOVE	ERNMENT F	RIMA	RY HEA	ALTH CENTR	E,						-
KADA	MALAIKUN	DU-62	5579,TH	IENI DISTRIC	T.						
					Details of De	evice l	Jnder Calibrat	tion (DUC)			
Descri	ption	:	SEMI A	UTO ANALYZ	ER	Make	& Model	:	ROBONIK & PRIETES	ST TOUCH	
Range		0	MULTI			Sr. No		:	ATCD3641220RBK	ATCD3641220RBK	
Resolu	ution	:	MULTI			Identi	fication No	:	NA		
DUC (Condition	:	SATISF	ACTORY		Location : LABORATORY					
				Environ	mental Cond	litions	& Calibration	Procedure	Details		
Enviro	nmental Deta	ils		Temperature:2	25.6 ° C		Relative Humi	idity	52% RH		
Calibration Procedure No SBS/CP/MD/20			Calibration done at ONSITE								
					Refer	ence S	Standards Det	ails			
S.No	Description				Make/ SI No:):		Certificate No			Validity
1 Electrical Safety Analyser Rigel Medica			l & 44L	& 44L-1059 M-230809-16-4			10-08-2024				

ELECTRICAL SAFETY

RESULTS

S.no	SPECIFICATION	MEASURED VALUES	EXPANDED UNCERTAINTY (±)
1	Insulation Resisitance	Measured values in MΩ	Uncertainty in % (±)
	>20MΩ	97	13.92
2	Earth Leakage	Measured values in µA	Uncertainty in % (±)
	<5000µAfor B,BF,CF	125	8.0
3	Enclosure Leakage	Measured values in μA	Uncertainty in % (±)
	<500µAfor B,BF,CF	235	7.2

REMARKS

- 1. This Calibration certificate shall not be reproduced except in full, without written approval of the laboratory.
- 2. The user should determine the suitability of the instrument for its intended use.
- 3. The recalibration interval should be determined on the user requirement.
- 4. The results stated in this certificate relate only to the item calibrated.
- 5.The indicated uncertainties are expanded uncertainty estimated for a confidence level of approximately 95% for a coverage factor k=2.00 .
- 6. Equipment used for Calibration were calibrated & traceable to National & International Standards.

Calibrated By

Authorised Signatory

(Calibration Engineer)
P.PRASANNA





Chief Executive

SUNSHINE BIOMEDICAL SOLUTIONS



		<u>CALII</u>	BRAT	TION	CERT	IFICATI	<u> </u>	
CERTIFICATE NO:	SBS/CL/2	3/12890			MI	CHANICAL	P	age No:1 of 1
Issue Date					23			
SRF No & Date				SRF/23/	00640-0002	& 06-10-2023		
Receipt Date				06-10-20	23			
Calibration Date				06-10-20	23			
Calibration Due				05-10-20	24			
Customer Name & Add	ress							
GOVERNMENT PRIMA	RY HEALTH	CENTRE,						
KADAMALAIKUNDU-62	5579,THENI	DISTRICT.						
		Det	ails of D	evice Un	der Calibra	tion (DUC)		
Description :	CENTRIF	JGE		Make &	Model	:	M.C.DALAL&CO	& NA
Range :	3500	RPM		Sr. No		:	MCD-419	
Resolution :	1	RPM		Identification No		:	NA	
OUC Condition :	Satisfacto	у		Location		:	LABORATORY	
	Env	ronmental C	ondition	ns & Star	dard Oper	ating Procedu	re Details	
Environmental Details		Temperature	e: 24.3 °C	4.3 °C Relative Hu		midity 54 % Rh		
Calibration Procedure No SBS/CP/ML/04			/04	Calibration done at ONSITE				
			Refer	ence Sta	ndards De	tails		
S.No Description			Make/ SI No:		Certificate No		Validity	
1 Digital Tachomet	er		Lutron 8	on & DT-2238		JRPM-CCTR-	A&S-2022-0036	03-10-2023
CALIBRATION RESUL	TS					•		

S.No	DEVICE UNDER CALIBRATION READINGS	STANDARD INSTRUMENTS	DEVIATION	EXPANDED UNCERTAINTY (±)
	RPM	RPM	RPM	%
1	1000	999.9	0.1	4.2
2	2000	1998	2	4.2
3	3000	2999	1	4.2

REMARKS

- 1. This Calibration certificate shall not be reproduced except in full, without written approval of the laboratory.
- 2. The user should determine the suitability of the instrument for its intended use.
- 3. The recalibration interval should be determined on the user requirement.
- 4. The results stated in this certificate relate only to the item calibrated.
- 5.The indicated uncertainties are expanded uncertainty estimated for a confidence level of approximately 95% for a coverage factor k=2.00.
- 6. Equipment used for Calibration were calibrated & traceable to National & International Standards.

Calibrated By

(Calibration Engineer)

P.PRASANNA

Authorised Signatory

Quality Manager

(C.SIVABALAN)

Chief Executive

SUNSHINE BIOMEDICAL SOLUTIONS



<u>CA</u>	LIBRATIO	N CER	RTIFIC	ATE_	
CERTIFICATE NO: SBS/CL/23/12891		M	EDICAL DE	VICES	Page No:1 of 1
Issue Date	07-1	0-2023			
SRF No & Date	SRF	/23/00640-0	003 & 06-10	-2023	
Receipt Date	06-1	0-2023			
Calibration Date	06-1	0-2023			
Calibration Due	05-1	0-2024			
Customer Name & Address					
GOVERNMENT PRIMARY HEALTH CENT	RE,				
KADAMALAIKUNDU-625579, THENI DISTRI	CT.				
	Details of Device	Under Calib	ration (DUC)	
ELECTRICAL SAFE	TY				
Description : (MICROSCOPE)	Make	& Model	:	LABOMED & VISION 2	000
Range : MULTI	Sr. N	0	:	CM/L943785	
Resolution : MULTI	Ident	ification No	:	NA	
DUC Condition : SATISFACTORY	Locat	tion		LABORATORY	
Envir	onmental Condition	s & Calibration	on Procedu	e Details	
Environmental Details Temperature	:25.6°C	Relative Humidity 52% RH			
Calibration Procedure No SBS/CP/MD	/29	Calibration done at ONSITE			
	Reference	Standards D	etails		
S.No Description	Make/ SI No:		Certificate No		Validity
1 Electrical Safety Analyser	Rigel Medical & 44l	44L-1059 M-230809-16-4 1		10-08-2024	

ELECTRICAL SAFETY

RESULTS

S.no	SPECIFICATION	MEASURED VALUES	EXPANDED UNCERTAINTY (±)
1	Insulation Resisitance	Measured values in $M\Omega$	Uncertainty in % (±)
	>20MΩ	97	13.92
2	Earth Leakage	Measured values in μA	Uncertainty in % (±)
	<5000µAfor B,BF,CF	125	12.3
3	Enclosure Leakage	Measured values in μA	Uncertainty in % (±)
	<500µAfor B,BF,CF	229	8.6

REMARKS

- 1. This Calibration certificate shall not be reproduced except in full, without written approval of the laboratory.
- 2. The user should determine the suitability of the instrument for its intended use.
- 3. The recalibration interval should be determined on the user requirement.
- 4. The results stated in this certificate relate only to the item calibrated.
- 5. The indicated uncertainties are expanded uncertainty estimated for a confidence level of approximately 95% for a coverage factor k=2.00.
- 6. Equipment used for Calibration were calibrated & traceable to National & International Standards.

Calibrated By Authorised Signatory

(Calibration Engineer) P.PRASANNA









		CA	LIBRA	TIO	N CER	RTIF	ICA	TE	
CERTIFICATE N		M	EDICA	L DEV	ICES	Page No:1 of 1			
Issue Date					0-2023				
SRF No & Date				SRF/	23/00640-0	004 &	06-10-2	2023	
Receipt Date				06-10	0-2023				
Calibration Date				06-10	0-2023				
Calibration Due				05-10	0-2024				
Customer Name	& Ad	dress							
GOVERNMENT	PRIMA	ARY HEALTH CENTE	RE,						
KADAMALAIKUN	1DU-6	25579,THENI DISTRI	CT.						
			Details of D	Device	Under Calib	ration	(DUC)		
Description	:	HEAMOTOLOGY AN	IALYZER	Make	& Model		:	SYSMEX & XP-100	
Range	:	MULTI		Sr. No)		:	B5903	
Resolution	1	MULTI		Identi	fication No		:	NA	
DUC Condition	1	SATISFACTORY		Locat	ion		:	LABORATORY	
		Enviro	onmental Con	ditions	& Calibration	on Pro	cedure	Details	
Environmental Det	ails	Temperature	25.6°C		Relative Hur	midity		52% RH	
Calibration Proced	ure No	SBS/CP/MD/	24		Calibration of	lone at		ONSITE	
			Refe	rence	Standards D	etails			-
S.No Description			Make/ SI No:	Ce		Certificate No			Validity
1 Electrical Safety Analyser Rigel Medical			I & 44L	& 44L-1059 M-230809-16-4		10-08-2024			

ELECTRICAL SAFETY

RESULTS

S.no	SPECIFICATION	MEASURED VALUES	EXPANDED UNCERTAINTY (±)
1	Insulation Resisitance	Measured values in MΩ	Uncertainty in % (±)
	>20MΩ	88	13.92
2	Earth Leakage	Measured values in μA	Uncertainty in % (±)
	<5000µAfor B,BF,CF	175	9.9
3	Enclosure Leakage	Measured values in μA	Uncertainty in % (±)
	<500µAfor B,BF,CF	235	8.5

REMARKS

- 1. This Calibration certificate shall not be reproduced except in full, without written approval of the laboratory.
- 2. The user should determine the suitability of the instrument for its intended use.
- 3. The recalibration interval should be determined on the user requirement.
- 4. The results stated in this certificate relate only to the item calibrated.
- 5. The indicated uncertainties are expanded uncertainty estimated for a confidence level of approximately 95% for a coverage factor k=2.00.
- ${\small 6. \ Equipment\ used\ for\ Calibration\ were\ calibrated\ \&\ traceable\ to\ National\ \&\ International\ Standards.}$

Calibrated By Authorised Signatory

(Calibration Engineer) P.PRASANNA





Chief Executive

SUNSHINE BIOMEDICAL SOLUTIONS