

	CALIBRAT	<u>ION CER</u>	TIFICA	<u>TE</u>	
CERTIFICATE NO: SBS/CL/23/12002		MEDICAL DEVICES		VICES	Page No:1 of 1
Issue Date		29-09-2023			
SRF No & Date		SRF/23/00447-0004 & 28-09-2023			
D = == != 4 D = 4 =		28-09-2023			
Calibration Date		28-09-2023			
Calibration Due		27-09-2024			
Customer Name & Address					
GOVERNMENT PRIMARY HEALT					
THAYAMPALAYAM-638703,TIRUF	PPUR DISTRICT.				1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 -
		vice Under Calib	ration (DUC)		
Description	ELECTRICAL SAFETY (MICROSCOPE)		:	LABOMED & VISION	2000
Range : MULTI	MULTI		:	170699461	
Resolution : MULTI	MULTI		:	NA	
DUC Condition : SATISFAC	CTORY	Location	:	LABORATORY	
	Environmental Condit	tions & Calibration	on Procedure	Details	
Environmental Details Temperature:25.6°C		Relative Humidity 52% RH		52% RH	
alibration Procedure No SBS/CP/MD/29		Calibration done at ONSITE			
	Refere	nce Standards D	etails		
.No Description	Make/ SI No:		Certificate	No	Validity
Electrical Safety Analyser Rigel Medica		& 44L-1059	M-230809-16-4 10-08		

ELECTRICAL SAFETY

RESULTS

SPECIFICATION	MEASURED VALUES	EXPANDED UNCERTAINTY (±)
Insulation Resisitance	Measured values in MΩ	Uncertainty in % (±)
>20MΩ	79	13.92
Earth Leakage	Measured values in uA	
<5000µAfor B,BF,CF	208	Uncertainty in % (±)
Enclosure Leakage	Measured values in µA	Uncertainty in % (±)
<500µAfor B,BF,CF	241	7.2
	Insulation Resisitance >20MΩ Earth Leakage <5000μAfor B,BF,CF Enclosure Leakage	Insulation Resisitance >20MΩ Parth Leakage Measured values in MΩ >20MΩ Farth Leakage Measured values in μA <5000μAfor B,BF,CF Enclosure Leakage Measured values in μA

REMARKS

- 1. This Calibration certificate shall not be reproduced except in full, without written approval of the laboratory.
- 2. The user should determine the suitability of the instrument for its intended use.
- 3. The recalibration interval should be determined on the user requirement.
- 4. The results stated in this certificate relate only to the item calibrated.
- 5. The indicated uncertainties are expanded uncertainty estimated for a confidence level of approximately 95% for a coverage factor k=2.00.
- 6. Equipment used for Calibration were calibrated & traceable to National & International Standards.

Calibrated By

Authorised Signatory

(Calibration Engineer) K.SATHYAMOORTHY



Technical Manager
C.SHANMUGARAJ

Chief Executive
Excount