MK BEST CALIBRATION SERVICES

NABL ACCREDITED CALIBRATION LABORATORY AS PER ISO/IEC17025: 2017



No. 27, F-2, 1st Floor, 2nd Street, Varalakshmi Nagar, Maduravoyal, (Opp. MGR Engineering College), Chennai - 600 095.

Ph.: 044 - 23780211, Cell : 93802 66480 / 86958 18108 / 90032 77250 E-mail: mkbestcalibration@gmail.com, www.mkbestcalibrationservices.com



CERTIFICATE OF CALIBRATION

CC-3340

FF/7.8/01							Page No	1 of 1	
ULR No	CC3340	34023000007859F Date of Calibration		22.09.2023	D	ate of Reciept	22.09.2023		
Certificate No	MKBL/2	23/09/0881-001	01 Due Date of Calibration		21.09.2024	D	ate of Issue	25.09.2023	
CUSTOMER I	NFORMAT	TION			DETAILS OF UN	IT UNDE	R CALIBRATION		
M/S. KB DIAGNOSTICS.,					Description		MIC	MICROPIPETTE 3	
VANDAVASI.					Make / Model		P FACT	P FACT PIPETTE / VA-500	
					Range/Resolution	N.	10 to	100 µl / 0.5 µl	
					Serial No			396435	
					Identification No		KBI	KBD/CB/GEN/04	
					Location				
					Calibrated at			LAB	
STANDARD IN	STRUMEN	NTS DETAILS	(The Star	ndards Used are Ti	raceable to National	/Internati	ional Standards)		
S.No	Description		Id.No.	Id.No/Sl. No		Certificate No			
01 ELEC	ELECTRONIC SEMI MICRO BALANCI		LANCE	MK/CAL-96/477904		TVCSPL 23/07/638-01		20.07.2024	
02	DIGITAL BAROMETER			MK/CAL-143		CC287922000005116F		12.10.2023	
03 DIGIT	DIGITAL PEN TYPE THERMOMETER		METER	MK/C	AL-160	CRMTL/01/423101578-A4		03.07.2024	
ENVIRONMEN	TAL & DU	JC CONDITIO	NS	REFERENCE ST	ANDARD				
Temperature		23.5 °C		Reference Std		ISO 8655-6:2002		5-6:2002	
Humidity		53 % RH	ł	Pr	ocedure No		MKBCS - MBV - 03		
Condition of UU	Receipt	Good							

CALIBRATION RESULTS

1.VOLUME CALIBRATION

S.No	UUC Reading (Mean) μl	STD Reading (Mean) µl	Deviation μl	Expanded Uncertainity (±) µl 1.18	
1	20	20.00	0.00		
2	40	40.00	0.00	1.18	
3	60	60.05	-0.05	1.18	
4	80	80.05	-0.05	1.18	
5	100	100.05	-0.05	1.18	

Remarks:

- 1. The Expanded Uncertainty Associated with the Results is Calculated at a Confidence Level of Approximately 95% with a Coverage factor of K=2.
- 2. The Calibration Certificate Shall not be Reproduced Expect In Full, Without Written Approval Of The Laboratory.
- 3. The Recalibration Interval Should be Determined on the User Requirement.
- 4. The Results Stated In This Certificate Relate Only to the Item Calibrated.
- 5. The User Should Determine The Suitablity Of The Instrument For Is Intended Use.
- 6. Resulted Volume Convert at 27°c of Water Temperature.
- 7. Expanded Uncertainity is also Included Correction Factors.

Calibrated by

S.Chandrabose (Calibration Engineer) CHENNAI OF CHENNAI

Authorised By

L.Magesh (MD/QM)