

Certificate No: SBS/CL/23/14. Customer Name & Address	201			CERTIFICATE		
Customer Name & Address					Page. No:1 of 1	
Customer Hame & Address						
GOVERNMENT PRIMARY HEALTH CENTRE,				SRF No.	SRF/23/00867-0002 11-10-2023	
				SRF Date		
MINJUR-601203,THIRUVALLUR DISTRICT.			Date of Receipt	10-10-2023		
				Date of Calibration	11-10-2023	
			Due Date for Calibration	10-10-2024		
				Issue Date	12-10-2023	
Details of Unit Under Calibra	ition					
Description	MICRO PIPETTE			Make	DIAGNOPETTE	
Range	1000μΙ			Model	NA	
Resolution	FIXED			Material	PVC	
erial Number	NA			Operating Range	1000μl	
D Number	NA			Condition of UUC	Good	
al. At	Mechanical Lab			Instrument Location	LABORATORY	
Er	vironmen	tal Condition	Calibration Method Used			
emperature (°C)	23.9	Humidity (%RH)	55	National / International Standard	ISO 8655-6:2002	
tmospheric Pressure (mbar)	1006	Water Temperature (°C)	21.6	Cal Procedure No SBS/CP/ML/08		
andard Used			1			

			_	

SI. No.	Description	ID.No./SI. No.	Certificate No.	Make/Model	Traceability	Valid till	
1	Electronic Weighing Balance	15112918	TVCSPL22/12/2115-01	A&D & GH-252	National Standards	09-12-2023	

7. Factor 1.00319

				Re	sult of Calibr	ation in µl				
SI. No.	Nominal Value	Observed Readings					Mean Value	Systematic Error	Random Error	Measurement Uncertainty (±)
1 1000	1000	999.98	999.97	999.95	999.96	999.97	000.04	0.00	0.04	0.45
	999.96	999.97	999.98	999.96	999.97	999.97	-0.03	0.01	0.47	

Remarks

- 1. This Calibration certificate shall not be reproduced except in full, without written approval of the laboratory.
- 2. The user should determine the suitability of the instrument for its intended use.
- 3. The recalibration interval should be determined on the user requirement.
- 4. The results stated in this certificate relate only to the item calibrated.
- 5. Equipment used for Calibration were calibrated & traceable to National & International Standards
- 6. The indicated uncertainties are expanded uncertainty estimated for a confidence level of approximately 95% for a coverage factor k=2.00.
- 7. Calibration Liquid Used: Distilled or Deionized water control Ca

Calibrated By,

3 as specified in ISO 3696.

Authorised by:

chief Executive)