

Reltec Calibration Pvt. Ltd.

98/50/1, 1st Floor, 2nd Main Road, Industrial Town, Rajajinagar, Bangalore - 560 044. Ph.: 080 42021540, E-mail: rcplcalibration@gmail.com, rcplbangalore@gmail.com Website: www.relteccalibration.com



CALIBRATION CERTIFICATE

Page 1 of 1

1. Customer Name; 2. SRF No:		M/s.CLUEPATH DIAGNOSTICS LLP., No.19A, New High School Road, VV Puram, Bangalore – 560004			6. Certificate No:		RCPL/23-24/ML/I5353-02
					7.ULR No:		CC221523000018721F
					8.Date of Issue:		27-11-2023
		15353			9.Date of Calibration:		17-11-2023
3. Date of SRF/Receipt:		17-11-2023			10. Next Cal Due:		16-11-2024
4. Discipline:		Mechanical Calibration			11. Calibration SOP no:		
5. Cı	alibrated At:	Mass & Volume Lab			12. Condition of DUC on Receipt:		RCPL/SOP/ML-21 Satisfactory
4. 1	bient Pressure: : DUC DETAILS: enclature:	910.2 hpa, V	Vater Temperature:	20 °C	10		
					Serial. No:		YE186AL0014288
Make & Model :		' & DRAGON LAB			Code/ID No:		CPD/EQP/02
lange : ocation:		100 to 1000 μl Laboratory			Resolution:		5 μl
5 6	TANDARD INCO						
ome	TANDARD INST	RUMENT USED:					
		Electronic Semi Micro Balance			Serial. No:		33604236
		Sartorius / CPA225D 0 to 220g			Cal Due Date:		10-09-2024
1101		· ·			Traceable to:		True Value Calibration Service
. Cz	ALIBRATION RE						Pvt. Ltd., Chennai
1. o.	DUC Value	Standard value	Systematic Error	Permissible Systematic Error ±	Random Error	Permissible Random Error ±	Measurement Uncertainty±
4	μl	μl	μΙ	μl	μl	ul	
1	100	100.17	-0.17	0.80	0.10	μl 0.30	μl
1	500	502.57	-2.57	4.00	0.25	1.50	0.16
	1000	1005.25	-5.25	8.00	0.12	2.00	0.46

0.12

3.00

17. REMARKS & CONCLUSION:

- a. Reported Values of DUC are Average of 10 Measuring Series.
- b. The Measurement Uncertainty is estimated at a confidence level of 95.45 % with a coverage factor k=2.0.
- c. Calibration certificate issued for Pipette is used for scientific or industrial purpose only.
- d. Calibration of pipette is done as per ISO8655-6 & Permissible Systematic & Random error are given as per ISO 8655-2

- e. Coefficient of cubic thermal expansion (°C-1 × 10-6) of Borosilicate Glass 5.0 is 15 * 10^-6.
- f. The mesurement data reported is "As found "- Without any Adjustment.

- g. This Certificate refer only to particular item submitted for Calibration.
- h. Volume at the reference temperature of 27°C, V27 from the apparent mass of water.
- i. The Std.used for calibration are calibrated and Traceable to National/International Standards.

Calibrated By

MOHAN KUMAR CALIBRATION ENGINEER



End of certificate

bration MANJUNATH CHAND DY TECHNICAL MANAGER

0.46

FM-GL-67