


ADVANC CALIBRATION SERV



(ISO: 17025 NABL ACCREDITED LAB.)

'C' - 23, SECTOR-10, NOIDA - 201301 (U.P.)

Mob.: +91-9891121066, 9868309579 • E-mail: advance.cal@gmail.com

Calibration Certificate

CERTIFICATE NO.	: 240123A/N-117		Page	: 1 of 1
CALIBRATED ON. CALIBRATION DUE	: 25 / 01 / 2024 E. : 24 / 01 / 2025		Ref. Std. C.P. No.	: CG-11
SRF No. & DATE : 240123A/N Dt. 23.01.2024			Phy. Inspection : O.K.	
ULR No. & ISSUE DATE : CC342724000000126F Dt. 27.01.2024			24 Cal. At	: Site / Lab
CALIBRATED FOR	: M/s Redcliffe Life Ground Floo Majura Gate	etech Pvt. Ltd. r Shop No 1, Leela H , Surat, Gujrat 39500	lealth Care, Kailash Na	
ITEM CALIBRATED				
Make : Make			Range : (-50 to 110) °C	
	L. Count : 0.1	The second secon	ID No. : RCL/BIO/D.TEMP-02	
		nical Biochemistry	S. No. : N.A	
ENVIRONMENT CO	NDITION: Temp. { 30	°C ± 10°C} R.H. {	30% to 80%}	
STANDARD INSTRU	MENTS USED ·			
INSTT. NAME 💹 📐	ID No. / S. No.	TRACEABILITY	CERTIFICATE No.	
Universal Calibrator	ACS/UC/01 / 300561	Anshaankan	AIPL/041123/1-1	07/11/2024
RESULTS :	ET Discipline			<u> </u>
*U.C. INSTT.		STANDARD READING (°C)	ERROR (°C)	
2.0 4.1	11/2	CINS	CE CALIBRA	10N EEP
6.2		6 NA	0.1	

REMARKS

: The Expanded uncertainty of measurement at 95% confidence level is + 1.00°C at coverage Factor k=2.

Under Calibration.

- Instrument has been Calibrated against laboratory Standard instruments whose values are traceable to National Standard as mention in above.
- The calibration results reported in this certificate are valid at the time of and under the stated conditions of measurement for a particular sample identified above. This Certificate should not be reproduced in full or in an abstract form without obtaining prior written permission from Advance Calibration Services.

(average of readings)

- The Calibration Certificate is not to be used for any legal purpose and shall not be produced in the court of law.
- Instruments has been Calibrated only for Scientific, in house, Testing and Industrial use & should not be used for trade / commercial use



