

ADVANCE CALIBRATION SERVIC (ISO: 17025 NABL ACCREDITED LAB.)





'C' - 23, SECTOR-10, NOIDA - 201301 (U.P.) Mob. : +91-9891121066, 7982584097 • E-mail : advance.cal@gmail.com

Calibration Certificate

	: 240201A	/N-104		S.	Page	: 1	of 1
CALIBRATED ON. CALIBRATION DU		The state of the s	e OP	SPA	Ref. Std. C.P. No.		O:8655:6 CS/CP/08
SRF No.& Dt.OF R	ECPT : 240201A	/N Dt. 01.02	2.2024	741	Phy. Inspecti	on : O	.K.
ULR No. & ISSUE DATE : CC342724000000154F Dt. 05.02.2024					Cal. At	Cal. At : Site / Lab	
CALIBRATED FOR	War	cliffe Lifetecl d No.61, Ind oura Patta B		l Pump, -180002	Adjoining Pizza	Wings	NOES!
ITEM CALIBRATED	: Micro Pip	ette			2.1		
Make : Thermo Scientific					Range : (2 to 20) µl		
C. Count :-					ID No. : RCL/BIO/PIP-04		
Deptt. : Clinical Biochemistry					S. No. : TW08238		
			nical Diochei	ilistry	3. NO I	VVU02	230
ENVIRONMENT CO		emp. { 25°C			to 75%}	VVU02	(36
	ONDITION: Te	emp. { 25°C				VVU02	30
ENVIRONMENT CO STANDARD INSTR INSTT. NAME	ONDITION: Te	emp. { 25°C		H. {30%			
STANDARD INSTR	ONDITION: Te	emp. { 25°C ; : lo.	<u>+</u> 4°C} R.	H. {30%	to 75%}	No.	DUE DATE
STANDARD INSTR INSTT. NAME	DNDITION: Te UMENTS USED ID No. / S. N ACS/DB/02/D4	emp. { 25°C ; : lo. 49927064	+ 4°C} R.	H. {30%	to 75%}	No.	DUE DATE
STANDARD INSTR INSTT. NAME Weighing Balance	ONDITION: Te	emp. { 25°C ; : lo. 49927064	+ 4°C} R. TRACEAE BlueBox Value	H. {30%	to 75%}	No.	DUE DATE
STANDARD INSTR INSTT. NAME Weighing Balance RESULTS: Nominal Capacity (µI)	DNDITION: Telluments USED ID No. / S. N ACS/DB/02/D4 Mechanical Graduation (µl)	emp. { 25°C : ilo. 49927064 Discipline Nominal	+ 4°C} R. TRACEAE BlueBox Value	H. {30%	to 75%} CERTIFICATE BBT/691/JAN/2	No.	DUE DATE 04/01/2025 Error
STANDARD INSTRINSTT. NAME Weighing Balance RESULTS: Nominal Capacity	DNDITION: Tell UMENTS USED ID No. / S. N ACS/DB/02/D4 Mechanical Graduation	emp. { 25°C ; : lo. 49927064 Discipline Nominal (µl)	+ 4°C} R. TRACEAE BlueBox Value	H. {30%	to 75%} CERTIFICATE BBT/691/JAN/2	No.	DUE DATE 04/01/2025 Error (μl)

REMARKS

: The Expanded uncertainty of measurement at 95% confidence level is ± 0.4 µl at coverage factor k=2.

- Instrument has been Calibrated against laboratory Standard instruments whose values are traceable to National Standard as mention in above.

 The calibration results reported in this certificate are valid at the time of and under the stated conditions of measurement for a particular sample identified above.
- This Certificate should not be reproduced in full or in an abstract form without obtaining prior written permission from Advance Calibration Services.
- The Calibration Certificate is not to be used for any legal purpose and shall not be produced in the court of law.
- Instruments has been Calibrated only for Scientific, in house, Testing and Industrial use & should not be used for trade / commercial use
- Confirmity statement not provided since not required



