

CAL	IBRATION	I CERT	IFICAT	<u>E</u>	
CERTIFICATE NO: SBS/CL/23/12163		ME	EDICAL DEV	ICES	Page No:1 of 1
Issue Date	30-09	9-2023			
SRF No & Date	SRF/	23/00495-000	01 & 29-09-2	023	
Receipt Date	29-09	9-2023			
Calibration Date	29-09	9-2023			
Calibration Due	28-09	9-2024			
Customer Name & Address	•				
GOVERNMENT PRIMARY HEALTH CENTR	E,				
MUDHALIPALAYAM-641606, TIRUPPUR DIS	STRICT.				
	Details of Device U	nder Calibrat	ion (DUC)		
ELECTRICAL					
Description : SAFETY(MICROSCOPE)				LABOMED & VISION	1 2000 LED
Range : MULTI	Sr. N	0	:	220135395	
Resolution : MULTI	Identi	fication No	:	NA	
DUC Condition : SATISFACTORY	Locat		:	LABORATORY	
Environ	mental Conditions	& Calibration	Procedure D	etails	
Environmental Details Temperature:25.6°C		Relative Humidity		52% RH	
Calibration Procedure No SBS/CP/MD/29		Calibration done at ONSITE			
	Reference S	tandards Det	ails		
S.No Description	Make/ SI No:		Certificate N	Validity	
1 Electrical Safety Analyser	Rigel Medical & 44	4L-1059 M-230809-16-4		10-08-20	

ELECTRICAL SAFETY

R	FSI	11	TS

S.no	SPECIFICATION	MEASURED VALUES	EXPANDED UNCERTAINTY (±)
1	Insulation Resisitance	Measured values in MΩ	Uncertainty in % (±)
	>20MΩ	93	13.92
2	Earth Leakage	Measured values in μA	Uncertainty in % (±)
_	<5000µAfor B,BF,CF	187	9.5
3	Enclosure Leakage	Measured values in μA	Uncertainty in % (±)
	<500µAfor B,BF,CF	237	8.4

REMARKS

- 1. This Calibration certificate shall not be reproduced except in full, without written approval of the laboratory.
- 2. The user should determine the suitability of the instrument for its intended use.
- 3. The recalibration interval should be determined on the user requirement.
- 4. The results stated in this certificate relate only to the item calibrated.
- 5. The indicated uncertainties are expanded uncertainty estimated for a confidence level of approximately 95% for a coverage factor k=2.00 .
- Equipment used for Calibration were calibrated & traceable to National & International Standards.
 Calibrated By

(Calibration Engineer)
C.SIVABALAN



Authorised Signatory

Technical Manager (C.SHANMUGARAJ) Chief Executive



				CAL	IBRAT	101	I CERT	TIFIC	<u> 47</u>	<u>E</u>		
CERT	IFICATE N	IO: SB	S/CL/23/	12164			M	EDICAL	DEV	ICES	Page	No:1 of 1
Issue	Date					30-09	9-2023					
SRF I	No & Date					SRF/	23/00495-00	02 & 29-0	9-20	023		
Recei	ipt Date					29-09	9-2023					
Calibr	ration Date					29-09	9-2023					
Calibr	ration Due					28-09	9-2024					
Custo	mer Name	& Addr	ess									
GOVE	ERNMENT	PRIMA	RY HEA	LTH CENTRE	≣,							
MUDI	HALIPALAY	AM-64	1606,TIF	RUPPUR DIS	TRICT.							
					Details of De	vice U	nder Calibra	tion (DUC)			
Descr	intion		SEMIA	UTO ANALYZ	rep	Make	& Model			ROBONIK & PRIETEST	TOUCH	
Range			MULTI			Sr. No	11201000212121		ATCD2950321RBK		1	
Resol			MULTI				fication No			NA		
	Condition											
DUC	Condition	•	SATISI		nental Condi	Locat		Procedu	ro D	LABORATORY		
Enviro	onmental De	taile		Militar Complete (Complete Complete Com		LIONS			ie De	52% RH		
Temperature 2012		Relative Humidity										
Calibration Procedure No SBS/CP/MD/20		Calibration done at ONSITE rence Standards Details										
C N	Danasisti	_					tandards De					
S.No	Descriptio	n			Make/ SI No	:	C		Certificate No			Validity
1	Electrical S	afety Ar	nalyser		Rigel Medica	1 & 441	4L-1059 M-230809-16-4		-4		10-08-2024	

ELECTRICAL SAFETY

			_	
R	FS	1	П	TS

S.no	SPECIFICATION	MEASURED VALUES	EXPANDED UNCERTAINTY (±)
1	Insulation Resisitance	Measured values in MΩ	Uncertainty in % (±)
	>20MΩ	86	13.92
2	Earth Leakage	Measured values in µA	Uncertainty in % (±)
	<5000µAfor B,BF,CF	196	9.3
3	Enclosure Leakage	Measured values in μA	Uncertainty in % (±)
	<500µAfor B,BF,CF	241	8.4

REMARKS

- 1. This Calibration certificate shall not be reproduced except in full, without written approval of the laboratory.
- 2. The user should determine the suitability of the instrument for its intended use.
- 3. The recalibration interval should be determined on the user requirement.
- 4. The results stated in this certificate relate only to the item calibrated.
- 5. The indicated uncertainties are expanded uncertainty estimated for a confidence level of approximately 95% for a coverage factor k=2.00.
- Equipment used for Calibration were calibrated & traceable to National & International Standards.
 Calibrated By,

(Calibration Engineer)
C.SIVABALAN



Authorised Signatory

Technical Manager (C.SHANMUGARAJ)

Chief Executive