

MEASURE TECHNO LAB

2, B.T. ROAD (JAYANTI CINEMA COMPLEX), BARRACKPORE, KOLKATA - 700120, W.B.

Phone: 033 - 2215 - 0032, 2215 - 9687, 8100875519, Mobile: 9831190974, LAB:- 8100143376, E-mail: measuretechno@yahoo.co.in



CC - 2545

CALIBRATION CERTIFICATE OF MICRO PIPETTE

CALIBRATION CERTIFICATE NO.:MTL / SQDPL / R08 / 03 - 24

ULR - CC254524000012786F

Page: 1 of 1

1.0 Service Request No.: MTL / 18A / 03 / 23 - 24

1.1 Issued to:

M/s. SpectroQ Diagnostics Pvt. Ltd.

Plot No. - 853 / 4786, 1st Floor,

Jharapada, Govinda Prasad, Cuttack Road.

Bhubaneswar, Khordha - 751006.

1.2 Description &

a) Name:

Micro Pipette

b) Code No.:

PPT - 01

Identification of item to be Calibrated:

c) Sl. No .: e) Model / Type: 245973

d) Make:

P'fact

g) Sensor:

1.8 Environmental Conditions During Calibration:

N.S.

f) Range:

5 μl to 50 μl

N.A.

h) Resolution:

 $0.5 \mu l$

i) End User:

Lab

j) Accuracy:

N.S.

k) Calibration done at:

On Site / √ In House

1.3 Date of receipt of item:

16-03-24

1.4 Physical Condition of DUC:

1.5 Date of calibration:

19-03-24

1.6 Recommended date of next calibration:

19-03-25

1.7 Date of Issue:

21-03-24

Temperature:

20 °C ± 2 °C

Humidity:

30 % RH to 75 % RH

Pressure:

1008 mbar

1.9 Method of Calibration:

SOP / MASS / 02 (As Per ISO: 8655 - 6: 2022)

2.0 Traceability:

a)Standards used for calibration are traceable to National standards through NABL Accredited Laboratory.

b) The following standards / Equipment have been used.

ii) Digital Thermometer With Sensor Cal. Certificate No. MTL / TH / DTM / R01 / 09 - 23

i) Weights Cal. Certificate No. NC-210

(NSTAR, Ahmedabad) (Cal. Date: 16/05/22, Due Date: 15/05/25)

(MTL, Barrackpore)

(Cal. Date: 15/09/23, Due Date: 15/09/24)

2.1 Result:

Mechanical Calibration: (Mass & Volume)

SI. No.	Parameter/ Range	Nominal Value µl	Mass of Water mg	Volume of Water at 20 °C μl	Error µl	Measurement Expanded Uncertainty ± μl
1.	Volume	5	5.0545	5.0747	0.0747	0.032
2.	5 μl to 50 μl	25	25.0623	25.1625	0.1625	0.33
3.		50	50.1290	50.3295	0.3295	0.34

Remarks: i) Cubical Expansion co - efficient of pipette material taken as 10⁻⁵ μl / °k.

- ii) This result has an expanded uncertainty with a coverage factor k=2 at approximately 95% confidence level.
- iii) The calibration certificate issued for this instrument is to be used for scientific or industrial purposes only.
- iv) Calibrations are carried out without any adjustment or repair.

DUC - Device Under Calibration

N.S. - Not Specified

N.A. - Not Applicable

Opinions and Interpretations					
Calibrated	√	Accepted / Valid for use			
Limited Use		Rejected / Out of use			

Calibration Engineer S.Mahapatratas . Calibration Engineer

Technical Manager S Pandey