

ASIAN TECHNOLOGY

(A HOUSE OF CALIBRATION)



CALIBRATION CERTIFICATE

Customen nome	M/C. Anlaus Dathology	Service request No. & date	P/00/19/03/24&19/03/2024
Customer name	M/S: Ankur Pathology	Service request No. & date	P/00/19/03/24&19/03/2024
And	KL Tower Kadma Market Main	ULR no.	CC223924000002148F
Address	Road Opposite Kadma Market	Cert. No.	AT24000002148
	Auto Stand Kadma Jamshedpur	Date of Receipt of DUC	19/03/2024
	831005 Dist-East Singhbhum	Date of calibration	19/03/2024
	Jharkhand.	Date of issue	20/03/2024
		Suggested due date	18/03/2025

Instrument Details					
Instrument name	Thermo Hygre	ometer	Location		
Make / Model No.	HTC-1		Accuracy		
Range / Size	-10 to 70 °C/1	0 to 99% RH	Visual Inspection	OK	
Least Count	0.1 °C / 1 %R	Н	Calibration Performed at	Lab	
I.D. No. / Sr. no.	TH-01 /				

	287			
Detail of reference standards & Major equipments used				
Equipment Name	Dig. Humidity Indicator With	SPRT With		
- 1	Sensor	Indicator		
Make	Yudian / Rotronic	Tempsans & Fluke		
Model / SR No.	11F183060/20274168	PT-100X1 & 1586A /		
		05640		
Certificate No.	CC325723000001173F	CC350823000000098F		
Calibration Validity	30/10/2024	25/10/2024		
Calibration by	KL Technology	S.B International		

Environmental	Temperature	(25± 4) °C	Calibration Reference	ITS:90 (1990)
Condition	Relative Humidity	(50±20) %	Work Instruction	AT/WI-12TH

Serial No.	Standard Average Valuein (°C)	Measured Average Value in (°C)	Standard Average Valuein (%RH) At @25°C	Measured Average Value in (%RH) At @25°C	Uncertainty At 95% C.L. (coverage factor $k=2$)
01.	10.011	10.0	30.1	30	A. The state of th
02.	20.017	20.1	49.3	50	± 0.3°C
03.	30.025	30.3	67.8	69	
04.	50.039	49.8	79.6	81	±2%RH
05.	65.081	65.5	89.5	90	

Remarks:

- (1) Standard equipment use for calibration are traceable to national/ international standards.
- (2)The reported expended uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by coverage factork = 2 such that the coverage probability corresponds to approximately 95%.(3)The above results are valid at the time of and under the stated conditions measurement.(4)This certificate is refers only to the particular item submitted for calibration. (5) Next calibration due date given as requested by the customer.

Calibrated By (Calibration Engg./TM) (D.K.SAXENA) Form No.- QF-47



Approved By (QM/TM) (NERRAT TYAGI)
Page No. 1 of 1

---End of Report---