

ASIAN TECHNOLOGY

(A HOUSE OF CALIBRATION)



CALIBRATION CERTIFICATE

Customer name	M/S: Global Ultrascan And	Service request No. & date	P/06/03/06/24&03/06/2024	
And	Diagnostic Centre, 200, NSC Bose	ULR no.	CC223924000004118 F	
Address	Road, Narendrapur, Kolkata -	Cert. No.	AT24000004118	
	700103	Date of Receipt of DUC	03/06/2024	
		Date of calibration	03/06/2024	
	u.	Date of issue	04/06/2024	
		Suggested due date	02/06/2025	

Instrument Details				
Instrument name	Digital Thermo Hygrometer	I.D. No.	DTM-01	
Make	Amicisense	Location		
Range / Size	-10 to 50 °C / 10 to 99 %RH	Accuracy		
Least Count	0.1 °C / 1 %RH	Visual Inspection	OK	

Equipment Name SPRT With Indicator		Dig. Humidity Indicator With Sensor		
Make ,	Tempsans & Fluke	Yudian / Rotronic		
Model / SR No.	PT-100X1 & 1586A ≠ 05640	11F1830601/20274168		
Certificate No.	CC350823000000098F	CC325723000001173F		
Calibration Validity	25/10/2024	30/10/2024		
Calibration by	S.B International	KL Technology		

Environmental	Temperature	25± 4 °C	Calibration Reference	ITS:90
Condition	Relative Humidity	50±20%	Calibration Procedure	CP-04T

Calibration Results

Campiation Results					
Serial	Standard	Measured	Standard	Measured	Uncertainty At 95%
No.	Average Value in	Average Value in	Average Value in	Average Value in	C.L.
	(°C)	(°C)	(%RH) @25 °C	(%RH) @25 °C	(coverage factor k=2)
01.	-10.224	-10.1	30.2	30	
02.	10.126	10.2	49.8	50	± 0.6°C
03.	20.245	20.1	69.4	70	15
04.	29.626	30.2	79.5	80	± 2.0%RH
05.	48.442	49.2	91.3	90	

Remarks:

(1) Standard equipment use for calibration are traceable to national/international standards.

(2) The reported expended uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by coverage factor k = 2 such that the coverage probability corresponds to approximately 95%.(3) The above results are valid at the time of and under the stated conditions measurement.(4) This certificate is refers only to the particular item submitted for calibration. (5) Next calibration due date given as requested by the customer.

Calibrated By (Calibration Engg./TM) (D/B/SAXSENA) Form No.QF-47



Approved By (QM/TM) (NEERA) TYAGI) Page No. 1 of 1

---End of Report---