Parashar Micro Measurement Pvt. Ltd.

The way to Technology (21 Years of Excellence)

B-59, SECTOR-64, NOIDA (U.P.) 201 307 PH.: 0120-4252360-65, Email : pmmpl.india@gmail.com Website : www.pmmpl.in, www.parashar.info



Calibration Certificate

ULR -	- CC279524000	060814F					Page 1 of 1
Certific	cate Number : PM	UUC Red	ceived on	17.09.2024			
T.B.		M/s. Pathology Leb. T.B. Combined Hospital,			Calibrated on Suggested Due Date		18.09.2024
							17.09.2025
		ucknow.	cknow.			ue Date	25.09.2024
langer and the			Descrip	otion of Equipmen	ts	•	ti.
Nomenclature		Digital	Digital Thermo Hygrometer		lass	Not Mentioned Physically Ok	
		Digital			fUUC		
Range		0 to 70	0 to 70 ° C / 20 to 70 % RH				
Resolution / Least Count			0.1 °C / 1 % RH		rk No.		
Make & Model No.			Mextech		K 110.	Pathology Lab.	
Material / Type			5.0	Location		r utilology Lub.	
			Master Equ	ipment / Standard	Used		
Sr. No.	Nomenclature	Make & Model	Serial No. / I/D Mark	Calibrated Fron	n	Certificate No.	Due Date of Calibration
1	Digital RH Indicator with Sensor	Yudian	15H313252 / PMM/RHI/02	ATCL, Gurgao	n (CC263523000005150F	04.11.2024

Standard used for calibration are traceable to Accredited lab, for Standard ISO/IEC: 17025 - 2017 or National Standards Through unbroken chain of calibration

Calibration Performed at	Laboratory	Environmental	Temperature = 25 ± 4 °C
Calibration Procedure No.	CP/T/ 05	Condition(s)	Humidity = 30 to 75 % RH
Reference Standard / Guideline		9 (1 5	

Thermal Calibration

CALIBRATION RESULTS (HUMIDITY AT 25 °C)							
	± Uncertainty in Mea (in %RH)	Error (in %RH)	Actual Observed Value in Std. (in %RH)	Nominal Value in UUC (in %RH)	S.N.		
	2.0	-0.5	30.5	30	1		
	2.0	-1.1	, 51.1	50	2		
	2.0	-1.8	61.8	60	3		
	2.0	-2.3	72.3	70	4		
		6,000,00					

UUC - Unit Under Calibration

Std. - Standard Instrument

Uncertainty of Measurement (at approx 95% Confidence Level with Coverage factor k = 2)

Calibrated By : Pankaj Yadav
Designation : Calibration Engineer



Approved By : Jai Prakash

Designation: Tech. Manager / Auth. Sign.



Conditions: 1. This certificate refers only to the particular item submitted for calibration.

2. The calibration result reported in this certificate are valid at the time of and under the stated conditions of measurement.

3. This particular certificate can not be reproduced except in full, without prior permission of chief executive officer of the lab.



Parashar Micro Measurement Pvt. Ltd.

The way to Technology (21 Years of Excellence)

B-59, SECTOR-64, NOIDA (U.P.) 201 307 PH.: 0120-4252360-65, Email : pmmpl.india@gmail.com Website : www.pmmpl.in, www.parashar.info

Calibration Certificate

								Page 1 of 1
Certificate Number : PMM/170924/22-1A					U	UUC Received on		17.09.2024
Calibrated For M/s. T.B.		l/s. Pathology Lab.			С	Calibrated on Suggested Due Date		18.09.2024
		B. Combine	3. Combined Hospital,					17.09.2025
	Lucknow.			Cert. Issue Date		Date	25.09.2024	
			Descri	ption of E	quipments	N		
Nomenclature		D: :: 1:	Digital Thermo Hygrometer		Accuracy/Class Condition of UUC		Not Mentioned	
		Digital					Physically Ok	
Range		0 to 70	0 to 70 ° C / 20 to 70 % RH		Serial No.			
Resolution / Least Count			0.1 °C / 1 % RH		Party ID Mark No.			
Make & Model No.			Mextech		Location		Pathology Lab.	
Material / Type							r danology Lub.	
			Master Equ	uipment /	Standard U	sed		
Sr. No.	Nomenclature	Make & Model	Serial No. / I/D Mark	Calib	rated From		Certificate No.	Due Date of Calibration
1	SPRT With Indicator	Fluke Fluke	PMM/SPRT/01 PMM/CTR/01	Temps	ens, Udaipu	гТ	L/023/1142.2.1	03.10.2024

Standard used for calibration are traceable to Accredited lab, for Standard ISO/IEC: 17025 - 2017 or National Standards Through unbroken chain of calibration

Calibration Performed at	Laboratory	Environmental	Temperature = 25 ± 4 °C	
Calibration Procedure No.	CP/T/01	Condition(s)	Humidity = 30 to 75 % RH	
Reference Standard / Guideline	DKD - R 5 - 1	8		

Thermal Calibration

Temperature Scale - ITS-90

S.N.	Nominal Value in UUC (in °C)	Actual Observed Value in Std. (in °C)	Error (in °C)	± Uncertainty in Measurement (in °C)
1	10.3	10.375	-0.075	0.23
2	15.1	15.248	-0.148	0.23
3	20.5	20.756	-0.256	0.23
4	25.2	25.537	-0.337	0.23
5	35.4	35.816	-0.416	0.23

UUC - Unit Under Calibration

Std. - Standard Instrument

Uncertainty of Measurement (at approx 95% Confidence Level with Coverage factor k = 2)

Calibrated By : Pankaj Yadav

Designation : Calibration Engineer



Approved By: Jai Prakash

Designation: Tech. Manager / Auth. Sign.

Conditions: 1. This certificate refers only to the particular item submitted for calibration.

2. The calibration result reported in this certificate are valid at the time of and under the stated conditions of measurement.

3. This particular certificate can not be reproduced except in full, without prior permission of chief executive officer of the lab.

